



MATERIAL SAFETY DATA SHEET

GREEN 3308C

Version Number 1.0 Revision Date 07/16/2004 Page 1 of 6 Print Date 11/15/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GREEN 3308C
Product code	:	CC10056615
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Rutile, antimony chromium buff	68186-90-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

: Inhalation, Ingestion, Skin contact				
 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. 				
: Experience shows no unusual dermatitis hazard from routine handling.				
: Refer to Section 11 for Toxicological Information.				
: None known.				



MATERIAL SAFETY DATA SHEET GREEN 3308C

Version Number 1.0 Revision Date 07/16/2004 Page 2 of 6 Print Date 11/15/2011

	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all case doubt seek medical advice.	s of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	;
Eyes	: Rinse immediately with plenty of water, also under the eyelids, fo least 15 minutes. If eye irritation persists, seek medical attention.	r at
Skin	: Wash off with soap and plenty of water. If skin irritation persists medical attention.	seel
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
Flammable Limits		
Upper explosion limit	: Not applicable	
sower explosion limit	: Not applicable	
Autoignition temperature	: Not applicable	
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positi pressure mode should be worn to prevent inhalation of airborne contaminants.	ve
Unusual Fire/Explosion	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen	
Hazards	(NOx), other hazardous materials, and smoke are all possible.	
	ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should be allowed to enter drains, water courses or the soil.	not
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material plastic, cardboard or metal containers for disposal. Refer to Sectio of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. Here only in areas with appropriate exhaust ventilation.	ıt
Storage	: Keep containers dry and tightly closed to avoid moisture absorption	n



MATERIAL SAFETY DATA SHEET GREEN 3308C

Version Number 1.0 Revision Date 07/16/2004 Page 3 of 6 Print Date 11/15/2011

and contamination. Keep in a dry, cool place.							
8. EXPOSURE CONTROLS / PERSONAL PROTECTION							
Respiratory protection : No personal respiratory protective equipment normally required.							
Eye/Face Protection	ction : Safety glasses with side-shields.						
Hand protection	: Protective gloves.						
Skin and body protection	: Long sleeved clothing.						
Additional Protective Measures	: Sa	: Safety shoes.					
General Hygiene: Handle in accordance with good industrial hygiene and safety practice.ConsiderationsWash hands before breaks and at the end of workday.							
Engineering measures		eat only in areas with appropriate exhaust ventilation		on. Provide			
Exposure limit(s)							
Components	Value	Exposure time	Exposure type	List:			
Rutile, antimony chromium buff	1 mg/m3	PEL:	1	OSHA Z1			
	0.5 mg/m3	PEL:	as Sb	OSHA Z1			
	0.5 mg/m3	Time Weighted Average (TWA):	as Cr	ACGIH			
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH			
	9. PHYSIC	CAL AND CHEMICAL P	ROPERTIES				
Form	: Solid	l Eva	poration rate :	Not applicable			
Appearance	: Pelle	ts Spe		Not determined			
Color: GREENBulk density: Not established							
Odor: Very faintVapor pressure: Not applicable							
Melting point/range							
Boiling Point: Water solubility	: Not a : Insol	applicable pH	:	Not applicable			
water solubility	. 111501	uoic					
10. STABILITY AND REACTIVITY							
Stability : Stable.							
Hazardous Polymerizatio	n : W	/ill not occur.					
Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal							
		3/6					



MATERIAL SAFETY DATA SHEET GREEN 3308C

			Page 4 Print Date 11/15/2		
	decomposi	ition, do not overheat.			
Incompatible Materials : Incompatible with strong acids and oxidizing agents.					
Hazardous decomposition products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.					
	11. TOXICOL	OGICAL INFORMAT	TION		
This mixture has not been nealth data for the indivic Foxicity Overview			osure effects listed are based on ex		
	following component	s which in their pure for	m have the following characteristi		
CAS-No.	Chemical Name	Effect	Target Organ		
	Rutile, antimony chromium buff	Irritant	Eyes, Skin, Respiratory syster		
Rutile, antimony chrom Symptoms may include	ium buff 68186-90- redness and burning	of skin, and other skin	tion. Can cause skin irritation. 1 damage. Additional symptoms		
Rutile, antimony chrom Symptoms may include	ium buff 68186-90- redness and burning e: antimony measles	of skin, and other skin	a damage. Additional symptoms		
Rutile, antimony chrom Symptoms may include skin contact may includ	ium buff 68186-90- redness and burning e: antimony measles <u>12. ECOLOC</u>	of skin, and other skin (a red, pimply rash).	a damage. Additional symptoms		
	ium buff 68186-90- redness and burning e: antimony measles <u>12. ECOLOC</u> ility : Not readily	of skin, and other skin (a red, pimply rash). GICAL INFORMATIC y biodegradable.	a damage. Additional symptoms		
Rutile, antimony chrom Symptoms may include skin contact may includ Persistence and degradab Environmental Toxicity	ium buff 68186-90- redness and burning le: antimony measles <u>12. ECOLOC</u> ility : Not readily : Chemicals polymer m	of skin, and other skir (a red, pimply rash). GICAL INFORMATION y biodegradable. are not readily available natrix.	n damage. Additional symptoms		
Rutile, antimony chrom Symptoms may include skin contact may include Persistence and degradab Environmental Toxicity Bioaccumulation Potentia	ium buff 68186-90- redness and burning e: antimony measles <u>12. ECOLOC</u> ility : Not readily : Chemicals polymer m al : Chemicals	of skin, and other skir (a red, pimply rash). GICAL INFORMATIC y biodegradable. are not readily availabl natrix. are not readily availabl natrix.	a damage. Additional symptoms		
Rutile, antimony chrom Symptoms may include skin contact may include Persistence and degradab Environmental Toxicity Bioaccumulation Potentia	ium buff 68186-90- redness and burning e: antimony measles <u>12. ECOLOC</u> ility : Not readily : Chemicals polymer m al : Chemicals polymer m : No data av	of skin, and other skir (a red, pimply rash). GICAL INFORMATIC y biodegradable. are not readily availabl natrix. are not readily availabl natrix.	a damage. Additional symptoms		
Rutile, antimony chrom Symptoms may include skin contact may includ Persistence and degradab	ium buff 68186-90- redness and burning e: antimony measles 12. ECOLOC ility : Not readily : Chemicals polymer m al : Chemicals polymer m : No data av 13. DISPOSA : Like most possible re generator of classificati	of skin, and other skir (a red, pimply rash). GICAL INFORMATIC y biodegradable. are not readily available atrix. are not readily available atrix. vailable AL CONSIDERATION thermoplastic plastics the cycling is preferred to c of waste material has the	A damage. Additional symptoms DN e as they are bound within the e as they are bound within the within the NS he product can be recycled. Where hisposal or incineration. The e responsibility for proper waste hisposal in accordance with		

14. TRANSPORT INFORMATION



MATERIAL SAFETY DATA SHEET GREEN 3308C

					Prin	Page t Date 11/15
U.S. DOT Classification	:	Not regulated for tra	nsportation.			
ICAO/IATA (air)	:	Refer to specific reg	ulation.			
IMO / IMDG (maritime)	:	Refer to specific reg	ulation.			
	15	. REGULATORY IN	FORMATION			
US Regulations:						
OSHA Status	:	Classified as hazardo	ous based on comp	ponen	ts.	
TSCA Status	:	All components of the Inventory.	nis product are list	ed on	or exemp	ot from the TS
US. EPA CERCLA Hazardou	is Subs	stances (40 CFR 302)				
Not applicable						
California Proposition 65		-	t contain a substa	nce lis	ted by Ca	alifornia Prop
	xtrem	ely Hazardous Substan		nce lis	ted by Ca	alifornia Prop
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 T	xtrem	ely Hazardous Substan	nce	nce lis		
65 SARA Title III Section 302 E Not applicable	oxtremo	ely Hazardous Substan		nce lis	Weight 8.81	
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 T Chemical Name CHROMIUM III COM	oxtremo	ely Hazardous Substan	cas-No.	nce lis	Weight	
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 T Chemical Name CHROMIUM III CON COMPOUNDS Canadian Regulations: National Pollutant Rele	oxic C	ely Hazardous Substan Chemicals:	CAS-No. 68186-90-3		Weight 8.81	%
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 T Chemical Name CHROMIUM III CON COMPOUNDS Canadian Regulations: National Pollutant Rele Chemical Name	oxic C	ely Hazardous Substan Chemicals:	CAS-No.	W	Weight 8.81 eight %	% NPRI ID#
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 T Chemical Name CHROMIUM III CON COMPOUNDS Canadian Regulations: National Pollutant Rele	oxic C MPOU	ely Hazardous Substan Chemicals: VNDSANTIMONY	CAS-No. 68186-90-3		Weight 8.81	%
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 T Chemical Name CHROMIUM III CON COMPOUNDS Canadian Regulations: National Pollutant Rele Chemical Name Phthalocyanine blue	oxic C	ely Hazardous Substan Chemicals: VNDSANTIMONY	CAS-No. 68186-90-3 CAS-No. 147-14-8	W 1. 8.	Weight 8.81 eight % 41	% NPRI ID# 70
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 T Chemical Name CHROMIUM III CON COMPOUNDS Canadian Regulations: National Pollutant Rele Chemical Name Phthalocyanine blue Rutile, antimony chromite	oxic C	ely Hazardous Substan Chemicals: VNDSANTIMONY	CAS-No. 68186-90-3 CAS-No. 147-14-8 68186-90-3	W 1. 8.	Weight 8.81 eight % 41 81	% NPRI ID# 70 68





MATERIAL SAFETY DATA SHEET **GREEN 3308C**

Version Number 1.0 Revision Date 07/16/2004

Page 6 of 6 Print Date 11/15/2011

CAS-No.	
147-14-8	
68186-90-3	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Listed
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Listed
Philippines PICCS	: Listed

:

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.