# MATERIAL SAFETY DATA SHEET BURNT ALMOND 2059 OD

Version Number 1.0 Revision Date 08/12/2004 Page 1 of 6 Print Date 11/15/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	BURNT ALMOND 2059 OD
Product code	:	CC10057774
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

## 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Iron oxide	1309-37-1	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Rutile, antimony chromium buff	68186-90-3	5 - 10

## **3. HAZARDS IDENTIFICATION**

## EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

## POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

# MATERIAL SAFETY DATA SHEET **BURNT ALMOND 2059 OD**

Version Number 1.0 Revision Date 08/12/2004 Page 2 of 6 Print Date 11/15/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foamnone.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

# MATERIAL SAFETY DATA SHEET BURNT ALMOND 2059 OD

Version Number 1.0 Revision Date 08/12/2004 Page 3 of 6 Print Date 11/15/2011

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Iron oxide	5 mg/m3	Time Weighted Average	Dust and fume. as Fe	ACGIH
		(TWA):		
Rutile, antimony	1 mg/m3	PEL:		OSHA Z1
chromium buff				
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average	as Cr	ACGIH
		(TWA):		
	0.5 mg/m3	Time Weighted Average	as Sb	ACGIH
		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
  Pellets
  BROWN
  Very faint
  Not determined
  Not applicable
  Insoluble
- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- Not applicable
  Not determined
  Not established
  Not applicable
  Not applicable
  Not applicable

# MATERIAL SAFETY DATA SHEET BURNT ALMOND 2059 OD

Version Number 1.0 Revision Date 08/12/2004

\_

Page 4 of 6 Print Date 11/15/2011

	1	0. STABILITY AND REACTIVITY
Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

## **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory system.
	chromium buff		

#### Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	ot readily biodegradable.	
Environmental Toxicity	nemicals are not readily available as they olymer matrix.	are bound within the
Bioaccumulation Potential	nemicals are not readily available as they olymer matrix.	are bound within the
Additional advice	o data available	
	DISPOSAL CONSIDERATIONS	

Product

: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The

PolyOne.

# MATERIAL SAFETY DATA SHEET BURNT ALMOND 2059 OD

sion Number 1.0 ision Date 08/12/2004			Print Date	Page 5 11/15/2
	generator of waste m classification, transp applicable federal, st	ortation and disposal	in accordance wit	
Contaminated packaging	: Recycling is preferre has the responsibility and disposal in accor and local regulations	for proper waste cla dance with applicab	assification, transpo	ortation
	14. TRANSPORT IN	FORMATION		
U.S. DOT Classification	: Not regulated for tra	nsportation.		
ICAO/IATA (air)	: Refer to specific reg	ulation.		
IMO / IMDG (maritime)	: Refer to specific reg	ulation.		
	15. REGULATORY IN	FORMATION		
US Regulations:				
OSHA Status	: Classified as hazardo	ous based on compor	ients.	
TSCA Status	: All components of the Inventory.	nis product are listed	on or exempt from	the TSCA
US. EPA CERCLA Hazardou	us Substances (40 CFR 302)			
Not applicable				
California Propositior 65	This product does no	t contain a substance	listed by Californi	ia Prop 65
SARA Title III Section 302 E	Extremely Hazardous Substan	nce		
Not applicable				
SARA Title III Section 313 T	oxic Chemicals:			
Chemical Name CHROMIUM III CO COMPOUNDS	MPOUNDSANTIMONY	CAS-No. 68186-90-3	Weight % 8.32	]
Canadian Degulations:				
Canadian Regulations:				

PolyOne

# MATERIAL SAFETY DATA SHEET BURNT ALMOND 2059 OD

#### Version Number 1.0 Revision Date 08/12/2004

\_

Page 6 of 6 Print Date 11/15/2011

Chemical Name		CAS-No.	Weight %	NPRI ID#
Rutile, antimony chromiu	m buff	68186-90-3	8.32	68
Rutile, antimony chromiu	m buff	68186-90-3	8.32	17
WHMIS Classification WHMIS Ingredient Dis CAS-No. 1309-37-1 68186-90-3 DSL	closure List	of this product are on	the Canadian	Domestic
tional Inventories:		DSL) or are exempt.		
ionar mventories.				
Australia AICS	: Listed			
	: Listed : Listed			
Australia AICS				
Australia AICS China IECS	: Listed			
Australia AICS China IECS Europe EINECS	: Listed : Listed			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.