MATERIAL SAFETY DATA SHEET

TR PURPLE

Version Number 1.0 Revision Date 08/17/2004 Page 1 of 5 Print Date 11/15/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	TR PURPLE
Product code	:	CC10057825
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES



MATERIAL SAFETY DATA SHEET TR PURPLE

sion Number 1.0 ision Date 08/17/2004	Page 2 Print Date 11/15/2
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of
Ingestion	doubt seek medical advice.Do not induce vomiting without medical advice. When symptoms
	persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne
Unusual Fire/Explosion Hazards	 contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by scoop or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXPO	OSURE CONTROLS / PERSONAL PROTECTION



MATERIAL SAFETY DATA SHEET

Hazardous Polymerization

Conditions to avoid

products

Incompatible Materials

Hazardous decomposition

R PURPLE		
rsion Number 1.0 vision Date 08/17/2004		Page 3 c Print Date <i>11/15/20</i>
Respiratory protection		atory protective equipment normally required. If ccur wear appropriate respiratory protection.
Eye/Face Protection	: safety glasses	
Hand protection	: Protective gloves.	
Skin and body protection	: Long sleeved cloth	ing.
Additional Protective Measures	: Safety shoes.	
General Hygiene Considerations		ce before breaks and immediately after handling the accordance with good industrial hygiene and safety stics.
Engineering measures		with appropriate exhaust ventilation. Provide to ventilation at machinery.
Exposure limit(s)		
There are no known hazardou	is components above regul	atory thresholds in this product.
9	PHYSICAL AND CHEM	MICAL PROPERTIES
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	 Solid flakes PURPLE Very faint Greater than 130 °C Not applicable Insoluble 	Evaporation rate:Not applicableSpecific Gravity::Not determinedBulk density:Not determinedVapor pressure:Not determinedVapour density:Not determinedpH:Not applicable
	10. STABILITY ANI	D REACTIVITY
Stability	: Stable.	

There are no known hazardous components above regulatory thresholds in this product.

: Will not occur.

:

:

:

11. TOXICOLOGICAL INFORMATION

(NOx), dense black smoke.

To avoid thermal decomposition, do not overheat.

Incompatible with strong acids and oxidizing agents.

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen



MATERIAL SAFETY DATA SHEET **TR PURPLE**

Version Number 1.0 Revision Date 08/17/2004 Page 4 of 5 Print Date 11/15/2011

	12. ECOLOGICAL INFORMATION			
Persistence and degradability	: Not readily biodegradable.			
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.			
Bioaccumulation Potential	: Not inherently biodegradable.			
Additional advice	: Chemicals are not readily available as they are bound within the polymer matrix.			
	13. DISPOSAL CONSIDERATIONS			
Product	: Where possible recycling is preferred to disposal or incineration. Th generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
	14. TRANSPORT INFORMATION			
U.S. DOT Classification	: Refer to specific regulation.			
ICAO/IATA (air)	: Refer to specific regulation.			
IMO / IMDG (maritime)	: Refer to specific regulation.			
	15. REGULATORY INFORMATION			
US Regulations:				
OSHA Status	: There are no known hazardous components above regulatory thresholds in this product.			
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.			
US. EPA CERCLA Hazardous	Substances (40 CFR 302)			
Not applicable				



MATERIAL SAFETY DATA SHEET **TR PURPLE**

/ersion Number 1.0 Revision Date 08/17/2004		Dri	int Date	Page 5 of 11/15/201
		T1		11/13/201
California Proposition 65	:	This product does not contain a substance listed by	California	a Prop 65.
SARA Title III Section 302 Ext	rem	ely Hazardous Substance		
Not applicable				
SARA Title III Section 313 Tox	ic (Chemicals:		
Not applicable Canadian Regulations:				
National Pollutant Relea	se Iı	aventory (NPRI)		
Not applicable				
WHMIS Classification	:	Not controlled.		
DSL	:	All components of this product are on the Canadian Substances List (DSL) or are exempt.	n Domest	ic
National Inventories:				
Australia AICS	:	Listed		
China IECS	:	Listed		
Europe EINECS	:	Listed		
Japan ENCS	:	Listed		
Korea KECI	:	Listed		
Philippines PICCS	:	Listed		
		16. OTHER INFORMATION		1

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.