MATERIAL SAFETY DATA SHEET

PURPLE T195-2-3

Version Number 1.0 Revision Date 08/17/2004 Page 1 of 7 Print Date 11/15/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone : Emergency telephone : number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PURPLE T195-2-3
Product code	:	CC10057954
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Styrene	100-42-5	0.1 - 1

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET PURPLE T195-2-3

Version Number 1.0 Revision Date 08/17/2004 Page 2 of 7 Print Date 11/15/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures Unusual Fire/Explosion	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards	(NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET PURPLE T195-2-3

Version Number 1.0 Revision Date 08/17/2004 Page 3 of 7 Print Date 11/15/2011

Decrimatory protection	. N			magningd
Respiratory protection	: N	lo personal respiratory protecti	ve equipment normaliy	required.
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		andle in accordance with good Vash hands before breaks and a		safety practic
Engineering measures		leat only in areas with appropr ppropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Styrene	20 ppm 85 mg/m3	Time Weighted Average (TWA):	Vapor.	ACGIH
	40 ppm 170 mg/m3	Short Term Exposure Limit (STEL):	Vapor.	ACGIH
	100 ppm	Time Weighted Average (TWA):	Vapor.	OSHA Z
	200 ppm	Ceiling Limit Value:	Vapor.	OSHA Z
	600 ppm	Maximum concentration:	Vapor.	OSHA Z
	9. PHYSIC	CAL AND CHEMICAL PRO	PERTIES	
Form	. Solia	L Evene	notion note . No	t opplieghle
Form Appearance	: Solic : Pelle			t applicable t determined
Color	: PUR			t established
Odor				t applicable
Melting point/range				t applicable
Boiling Point:		applicable pH	: No	t applicable
Water solubility	: Insol	uble		
	10. 8	STABILITY AND REACTIV	ITY	
Stability	: S	table.		
Hazardous Polymerizatio	n : V	Vill not occur.		



MATERIAL SAFETY DATA SHEET PURPLE T195-2-3

Version Number 1.0 Revision Date 08/17/2004		Page 4 of 7 Print Date <i>11/15/2011</i>
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
100-42-5	Styrene	Irritant	Eyes, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system,
			Liver, central nervous system
			(CNS).

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
100-42-5	Styrene	LC50	12 gm/m3	rat
		Oral LD50	2,650 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	CAS-No. Chemical Name		IARC	NTP
100-42-5 Styrene		no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Styrene 100-42-5 Irritating to eyes, skin, and respiratory tract with many CNS effectssuch as narcosis, cramps and respiratory tract paralysis.

12. ECOLOGICAL INFORMATION



MATERIAL SAFETY DATA SHEET PURPLE T195-2-3

sion Number 1.0 ision Date 08/17/2004	Page 5 Print Date 11/15/2
ISION Date 06/17/2004	
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSC. Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition	: WARNING! This product contains a chemical known to the State of

PolyOne

MATERIAL SAFETY DATA SHEET **PURPLE T195-2-3**

Version Number 1.0 Revision Date 08/17/2004

Page 6 of 7 Print Date <u>11/</u>15/2011

65

California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
STYRENE	100-42-5	0.24

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Styrene	100-42-5	0.24	214
2-Propenoic acid, 2-methyl-, methyl ester	80-62-6	0.38	161

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

:

CAS-No.	
100-42-5	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Listed
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Listed
Philippines PICCS	: Listed

16. OTHER INFORMATION



MATERIAL SAFETY DATA SHEET **PURPLE T195-2-3**

Version Number 1.0 Revision Date 08/17/2004

Page 7 of 7 Print Date 11/15/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.