MATERIAL SAFETY DATA SHEET PG 58261.00 PEARL SI PP

Version Number 1.0 Revision Date 08/26/2004

Page 1 of 6 Print Date 11/15/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	PG 58261.00 PEARL SI PP
Product code :	CC10058261
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Aluminum	7429-90-5	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Mica	12001-26-2	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. 		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 58261.00 PEARL SI PP**

Version Number 1.0 Revision Date 08/26/2004 Page 2 of 6 Print Date 11/15/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET PG 58261.00 PEARL SI PP

Version Number 1.0 Revision Date 08/26/2004 Page 3 of 6 Print Date 11/15/2011

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Aluminum	10 mg/m3	Time Weighted Average	Dust.	ACGIH
		(TWA):		
	5 mg/m3	Time Weighted Average	Welding fume. as Al	ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1
Mica	20 mppcf	PEL:	Total dust.	OSHA
	3 mg/m3	Time Weighted Average	Respirable fraction.	ACGIH
		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
 Pellets
 GREY
 Very faint
 Not determined
 Not applicable
 Insoluble
- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 Not applicable
 Not applicable
 Not applicable

PolyOne

MATERIAL SAFETY DATA SHEET **PG 58261.00 PEARL SI PP**

Version Number 1.0 Revision Date 08/26/2004 Page 4 of 6 Print Date 11/15/2011

10. STABILITY AND REACTIVITY			
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid decomposition, do not overheat.	thermal	
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.		
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitr (NOx), other hazardous materials, and smoke are all possible	\mathcal{U}	

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
12001-26-2	Mica	Systemic effects	Respiratory system.

12. ECOLOGICAL INFORMATION

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 58261.00 PEARL SI PP**

Version Number 1.0 Revision Date 08/26/2004 Page 5 of 6 Print Date 11/15/2011

has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification	: Not regulate	ed for transportation.		
CAO/IATA (air)	: Refer to spe	ecific regulation.		
MO / IMDG (maritime)	: Refer to spe	ecific regulation.		
	15. REGULAT	TORY INFORMATION		
US Regulations:				
OSHA Status	: Classified a	as hazardous based on comp	onents.	
TSCA Status	: All compor Inventory.	nents of this product are liste	ed on or exemp	pt from the TSC
JS. EPA CERCLA Hazardo	us Substances (40 C	CFR 302)		
Not applicable				
California Proposition	n : This produc	ct does not contain a substan	ce listed by C	alifornia Prop 6
65	-		ce listed by C	alifornia Prop 6
	-		ce listed by C	alifornia Prop 6
65	-		ce listed by C	alifornia Prop 6.
65 SARA Title III Section 302 H Not applicable	Extremely Hazardou		ce listed by C	alifornia Prop 6.
65 SARA Title III Section 302 H	Extremely Hazardou		ce listed by C	
65 SARA Title III Section 302 H Not applicable SARA Title III Section 313 T	Extremely Hazardou	as Substance		
65 SARA Title III Section 302 F Not applicable SARA Title III Section 313 T Chemical Name ALUMINUM (FUM	Extremely Hazardou	us Substance	Weight	
65 SARA Title III Section 302 H Not applicable SARA Title III Section 313 T Chemical Name ALUMINUM (FUM Canadian Regulations: National Pollutant Ref	Extremely Hazardou Foxic Chemicals: E OR DUST)	IS Substance CAS-No. 7429-90-5	Weight	
65 SARA Title III Section 302 H Not applicable SARA Title III Section 313 T Chemical Name ALUMINUM (FUM Canadian Regulations:	Extremely Hazardou Foxic Chemicals: E OR DUST)	IS Substance CAS-No. 7429-90-5	Weight	

PolyOne.

MATERIAL SAFETY DATA SHEET PG 58261.00 PEARL SI PP

Version Number 1.0 Revision Date 08/26/2004

Page 6 of 6 Print Date 11/15/2011

WHMIS Classification :	D2B	
WHMIS Ingredient Disclosu	re List	
CAS-No. 7429-90-5 12001-26-2		
DSL :	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National Inventories:		
Australia AICS :	Listed	
China IECS :	Listed	
Europe EINECS :	Listed	
Japan ENCS :	Not determined	
Korea KECI :	Listed	
Philippines PICCS :	Listed	
	16. OTHER INFORMATION	T

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.