## MATERIAL SAFETY DATA SHEET **TR BLUE**

### Version Number 1.1 Revision Date 09/15/2004

Page 1 of 6 Print Date 11/16/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	TR BLUE
Product code	:	CC10058906
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
8-Oxa-3,5-dithia-4-stannatetradecanoic acid,	57583-35-4	1 - 5
10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl		
ester		

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact			
Acute exposure				
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.			
Ingestion	: May be harmful if swallowed.			
Eyes	: Particulates, like other inert materials can be mechanically irritating.			
Skin	: Experience shows no unusual dermatitis hazard from routine handling.			
Chronic exposure	: Refer to Section 11 for Toxicological Information.			



# MATERIAL SAFETY DATA SHEET **TR BLUE**

Version Number 1.1 Revision Date 09/15/2004 Page 2 of 6 Print Date 11/16/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foamnone.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



# MATERIAL SAFETY DATA SHEET **TR BLUE**

				Page	
ion Number 1.1 sion Date 09/15/2004			Print I	. Page /Date 11/16	
			-		
Handling :		: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.			
Storage		Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.			
8. H	EXPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	lo personal respiratory protecti	ve equipment normally	required.	
Eye/Face Protection	: S	afety glasses with side-shields			
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	: Safety shoes.			
General Hygiene Considerations	: H V	safety practic			
Engineering measures		leat only in areas with appropr ppropriate exhaust ventilation		. Provide	
Engineering measures Exposure limit(s)				. Provide	
				. Provide	
<u>Components</u> 8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl	aj	ppropriate exhaust ventilation a	at machinery.	List:	
Components 8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl-	Value	ppropriate exhaust ventilation a Exposure time PEL: Time Weighted Average	at machinery. Exposure type	List: OSHA Z	
<u>Components</u> 8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl	aj Value 0.1 mg/m3	ppropriate exhaust ventilation a Exposure time PEL: Time Weighted Average (TWA): Short Term Exposure Limit	at machinery. Exposure type as Sn	List: OSHA Z ACGIH	
<u>Components</u> 8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl	a Value 0.1 mg/m3 0.1 mg/m3 0.2 mg/m3	Exposure time PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL):	at machinery. Exposure type as Sn as Sn as Sn	List: OSHA Z ACGIH	
Components         8-Oxa-3,5-dithia-4-sta         nnatetradecanoic acid,         10-ethyl-4,4-dimethyl-         7-oxo-, 2-ethylhexyl         ester	aj Value 0.1 mg/m3 0.1 mg/m3 0.2 mg/m3 9. PHYSIC	Exposure time PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	at machinery. Exposure type as Sn as Sn as Sn DPERTIES	List: OSHA Z ACGIH ACGIH	
Exposure limit(s) Components 8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl ester Form	aj Value 0.1 mg/m3 0.1 mg/m3 0.2 mg/m3 9. PHYSIO : Solio	ppropriate exhaust ventilation a Exposure time PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	at machinery.          Exposure type         as Sn         as Sn         DPERTIES         ration rate       : No	List: OSHA Z ACGIH ACGIH	
Exposure limit(s) Components 8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl ester Form Appearance	aj Value 0.1 mg/m3 0.1 mg/m3 0.2 mg/m3 0.2 mg/m3 9. PHYSIO : Solic : Pelle	Exposure time         PEL:         Time Weighted Average         (TWA):         Short Term Exposure Limit         (STEL):         CAL AND CHEMICAL PRO         there is a specific term of the system	at machinery.          Exposure type         as Sn         as Sn         DPERTIES         ration rate       : No         ic Gravity:       : No	List: OSHA Z ACGIH ACGIH t applicable t determined	
Exposure limit(s) Components 8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl ester Form Appearance Color	aj Value 0.1 mg/m3 0.1 mg/m3 0.2 mg/m3 0.2 mg/m3 0.2 mg/m3 0.2 mg/m3 0.2 mg/m3	Exposure time         PEL:         Time Weighted Average         (TWA):         Short Term Exposure Limit         (STEL):         CAL AND CHEMICAL PRO         ets       Specific         E       Bulk d	Exposure type as Sn as Sn as Sn OPERTIES ration rate : No ic Gravity: : No ensity : No	List: OSHA Z ACGIH ACGIH t applicable t determined t established	
Exposure limit(s) Components 8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl ester Form Appearance Color Odor	aj Value 0.1 mg/m3 0.1 mg/m3 0.2 mg/	Exposure time         PEL:         Time Weighted Average         (TWA):         Short Term Exposure Limit         (STEL):         CAL AND CHEMICAL PRO         d       Evapor         ets       Specifi         E       Bulk d         faint       Vapor	Exposure type as Sn as Sn as Sn DPERTIES ration rate : No ic Gravity: : No ensity : No pressure : No	List: OSHA Z ACGIH ACGIH ACGIH	
Exposure limit(s) Components 8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl ester Form Appearance Color Odor Melting point/range	a) Value 0.1 mg/m3 0.1 mg/m3 0.2 mg/m3 0.2 mg/m3 0.2 mg/m3 0.2 mg/m3 0.2 mg/m3 0.2 mg/m3 0.2 mg/m3 0.2 mg/m3 0.2 mg/m3	Exposure time         PEL:         Time Weighted Average         (TWA):         Short Term Exposure Limit         (STEL):         CAL AND CHEMICAL PRO         d       Evapor         ets       Specifi         FE       Bulk d         / faint       Vapor         determined       Vapou	Exposure type as Sn as Sn as Sn DPERTIES ration rate : No ic Gravity: : No ensity : No pressure : No r density : No	List: OSHA Z ACGIH ACGIH ACGIH t applicable t determined t established t applicable t applicable	
Exposure limit(s) Components 8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl ester Form Appearance Color Odor	a) Value 0.1 mg/m3 0.1 mg/m3 0.2 mg/m3 0.2 mg/m3 0.2 mg/m3 0.2 mg/m3 0.2 mg/m3 0.2 mg/m3 0.2 mg/m3 0.2 mg/m3 0.2 mg/m3	Exposure time         PEL:         Time Weighted Average         (TWA):         Short Term Exposure Limit         (STEL):         CAL AND CHEMICAL PRO         d       Evapor         ets       Specifi         E       Bulk d         faint       Vapor	Exposure type as Sn as Sn as Sn DPERTIES ration rate : No ic Gravity: : No ensity : No pressure : No r density : No	List: OSHA ACGI ACGI ACGI t applicable ot determine ot establishe ot applicable	

### **10. STABILITY AND REACTIVITY**



# MATERIAL SAFETY DATA SHEET **TR BLUE**

Version Number 1.1 Revision Date 09/15/2004

Page 4 of 6 Print Date 11/16/2011

Stability Hazardous Polymerization	:	Stable. Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

\_

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
57583-35-4	8-Oxa-3,5-dithia-4-stannat	Irritant	Eyes, Skin.
	etradecanoic acid,		
	10-ethyl-4,4-dimethyl-7-o		
	xo-, 2-ethylhexyl ester		

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS



## MATERIAL SAFETY DATA SHEET TR BLUE

R DLUE	
ersion Number 1.1 evision Date 09/15/2004	Page 5 of Print Date 11/16/201
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
Not applicable	
California Proposition 65	: WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 E	xtremely Hazardous Substance
Not applicable	
SARA Title III Section 313 T	oxic Chemicals:
Not applicable Canadian Regulations:	
National Pollutant Rele	ease Inventory (NPRI)
	5/6



# MATERIAL SAFETY DATA SHEET **TR BLUE**

Version Number 1.1 Revision Date 09/15/2004

Page 6 of 6 Print Date 11/16/2011

Not applicable

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.	
57583-35-4	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

:

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.