MATERIAL SAFETY DATA SHEET **GRV-PV-029-CM-White**

Version Number 1.0 Revision Date 10/21/2004

Page 1 of 6 Print Date 11/16/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	GRV-PV-029-CM-White
Product code :	CC10059554
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
8-Oxa-3,5-dithia-4-stannatetradecanoic acid,	57583-35-4	1 - 5
10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl		
ester		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.		
Ingestion	: May be harmful if swallowed.		
Eyes	: Particulates, like other inert materials can be mechanically irritating.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		

PolyOne.

MATERIAL SAFETY DATA SHEET **GRV-PV-029-CM-White**

Version Number 1.0 Revision Date 10/21/2004 Page 2 of 6 Print Date 11/16/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May
	emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1: of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET **GRV-PV-029-CM-White**

Water solubility

ion Number 1.0 sion Date 10/21/2004			Print D	Page 3 Date 11/16/	
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.				
Storage		Keep containers dry and tigh nd contamination. Keep in		e absorption	
8. 1	EXPOSURE	CONTROLS / PERSONA	L PROTECTION		
Respiratory protection	: N	lo personal respiratory prote	ective equipment normally	required.	
Eye/Face Protection	: S	afety glasses with side-shie	lds.		
Hand protection	: P	Protective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		Iandle in accordance with go Vash hands before breaks an		safety practic	
Engineering measures Exposure limit(s)		Ieat only in areas with appro ppropriate exhaust ventilation		Provide	
Components	Value	Exposure time	Exposure type	List:	
8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl ester	0.1 mg/m3	PEL:	as Sn	OSHA Z	
	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	ACGIH	
	0.2 mg/m3	Short Term Exposure Lim (STEL):	it as Sn	ACGIH	
	9. PHYSI	CAL AND CHEMICAL P	ROPERTIES		
Form	: Solid	1 Eva	poration rate : Not	applicable	
Appearance	: Pelle			t determined	
Color	: WH	1	-	testablished	
Odor			•	applicable	
Melting point/range	: Not	determined Vap	our density : Not	applicable	
Melting point/range Boiling Point:		determined Vap applicable pH			

10. STABILITY AND REACTIVITY

: Insoluble

3/6

PolyOne.

MATERIAL SAFETY DATA SHEET **GRV-PV-029-CM-White**

Version Number 1.0 Revision Date 10/21/2004 Page 4 of 6 Print Date 11/16/2011

Stability Hazardous Polymerization Conditions to avoid	: : :	Stable. Will not occur. Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

_

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
57583-35-4	8-Oxa-3,5-dithia-4-stannat etradecanoic acid, 10-ethyl-4,4-dimethyl-7-o xo-, 2-ethylhexyl ester	Irritant	Eyes, Skin.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS

PolyOne.

MATERIAL SAFETY DATA SHEET **GRV-PV-029-CM-White**

sion Number 1.0 vision Date 10/21/2004	Page 5 of 6 Print Date 11/16/2011		
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
	14. TRANSPORT INFORMATION		
U.S. DOT Classification	: Not regulated for transportation.		
ICAO/IATA (air)	: Refer to specific regulation.		
IMO / IMDG (maritime)	: Refer to specific regulation.		
	15. REGULATORY INFORMATION		
US Regulations:			
OSHA Status	: Classified as hazardous based on components.		
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.		
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)		
Not applicable			
California Proposition 65	: WARNING! This product contains a chemical known to the State of California to cause cancer.		
SARA Title III Section 302 E	stremely Hazardous Substance		
Not applicable			
SARA Title III Section 313 T	oxic Chemicals:		
Chemical Name	CAS-No. Weight %		
ZINC COMPOUNDS	1314-98-3 2.00		
	12036-43-0 65.00		

MATERIAL SAFETY DATA SHEET **GRV-PV-029-CM-White**

Version Number 1.0 Revision Date 10/21/2004

Page 6 of 6 Print Date 11/16/2011

Canadian Regulations:

Chemical Name	CAS-No.	Weight %	NPRI ID#
Zinc sulfide	1314-98-3	2.00	231
Titanium zinc oxide (TiZnO3)	12036-43-0	65.00	231

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.	
57583-35-4	

DSL

All of the components of this product are listed on the Canadian Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations.

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

:

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and beliet at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.