MATERIAL SAFETY DATA SHEET

PG 60035.02 GY PP AS

Version Number 1.0 Revision Date 10/21/2004 Page 1 of 5 Print Date 11/16/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PG 60035.02 GY PP AS
Product code	:	CC10060528
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact	
Acute exposure		
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. Experience shows no unusual dermatitis hazard from routine handling. 	
Chronic exposure	: Refer to Section 11 for Toxicological Information.	
Medical Conditions Aggravated by Exposure:	: None known.	
	4. FIRST AID MEASURES	



MATERIAL SAFETY DATA SHEET PG 60035.02 GY PP AS

ion Number 1.0 sion Date 10/21/2004	Page 2 Print Date 11/16/2
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from
	overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature Suitable extinguishing media	Not applicableCarbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 60035.02 GY PP AS**

Version Number 1.0 Revision Date 10/21/2004 Page 3 of 5 Print Date 11/16/2011

Respiratory protection	: No personal respir	atory protective equipment normally require	ed.
Eye/Face Protection	: Safety glasses with	side-shields.	
Hand protection	: Protective gloves.		
Skin and body protection	: Long sleeved cloth	ing.	
Additional Protective Measures	: Safety shoes.		
General Hygiene Considerations		ce with good industrial hygiene and safety p breaks and at the end of workday.	oractice
Engineering measures		with appropriate exhaust ventilation. Provi t ventilation at machinery.	de
Exposure limit(s)			
Form	: Solid : Pellets	Evaporation rate : Not applic	
Appearance Color	: Pellets : GREY	Specific Gravity::Not deterrBulk density:Not establ	
Odor	: Very faint	Vapor pressure : Not establ	
Melting point/range	: Not determined	Vapour density : Not applic	
Boiling Point:	: Not applicable	pH : Not applic	
Water solubility	: Insoluble		
	10. STABILITY AN	D REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from o decomposition, do	xidizing agents and open flame. To avoid the not overheat.	hermal
Incompatible Materials	: Incompatible with	strong acids and oxidizing agents.	
		O2), carbon monoxide (CO), oxides of nitro dous materials, and smoke are all possible.	ogen
Hazardous decomposition products	(Itox), other hazar		

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **PG 60035.02 GY PP AS**

Version Number 1.0 Revision Date 10/21/2004 Page 4 of 5 Print Date 11/16/2011

There are no known hazardous components above regulatory thresholds in this product.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
INIO / INIDO (Inantinie)	. Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: There are no known hazardous components above regulatory thresholds in this product.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	

4/5

PolyOne

MATERIAL SAFETY DATA SHEET PG 60035.02 GY PP AS

Version Number 1.0 Revision Date 10/21/2004

Page 5 of 5 Print Date 11/16/2011

California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.			
SARA Title III Section 302 Extremely Hazardous Substance					
Not applicable					
SARA Title III Section 313 Toxic Chemicals:					
Not applicable Canadian Regulations:					
National Pollutant Release Inventory (NPRI)					
Not applicable					
WHMIS Classification	:	Not controlled.			
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.			
National Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined			
Korea KECI	:	Listed			
Philippines PICCS	:	Listed			
		16. OTHER INFORMATION			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.