MATERIAL SAFETY DATA SHEET TRANS SEDONA BROWN PEARL

Version Number 1.0 Revision Date 10/21/2004

Page 1 of 7 Print Date 11/16/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	TRANS SEDONA BROWN PEARL
Product code :	CC10060584
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Styrene	100-42-5	0.1 - 1
Aluminum	7429-90-5	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne

MATERIAL SAFETY DATA SHEET TRANS SEDONA BROWN PEARL

Version Number 1.0 Revision Date 10/21/2004 Page 2 of 7 Print Date 11/16/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

PolyOne.

MATERIAL SAFETY DATA SHEET TRANS SEDONA BROWN PEARL

Version Number 1.0 Revision Date 10/21/2004 Page 3 of 7 Print Date 11/16/2011

8.1	EXPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	lo personal respiratory protecti	ve equipment normally re	equired.
Eye/Face Protection : Safety glasses with side-shields.				
Hand protection : Protective gloves.				
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		landle in accordance with good Vash hands before breaks and a		fety practice.
Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Engineering measures				Provide
Exposure limit(s)	aj	ppropriate exhaust ventilation	at machinery.	
Exposure limit(s) Components	aj Value	ppropriate exhaust ventilation Exposure time	at machinery. Exposure type	List:
Exposure limit(s)	aj	ppropriate exhaust ventilation	at machinery.	
Exposure limit(s) Components	aj Value	ppropriate exhaust ventilation Exposure time Time Weighted Average	at machinery. Exposure type Dust. Total dust. as Al	List:
Exposure limit(s) Components	aj Value 10 mg/m3 15 mg/m3 5 mg/m3	Exposure time Time Weighted Average (TWA): PEL: PEL:	at machinery. Exposure type Dust. Total dust. as Al Respirable dust. as Al	List: ACGIH
Exposure limit(s) Components	aj Value 10 mg/m3 15 mg/m3	Exposure time Time Weighted Average (TWA): PEL:	at machinery. Exposure type Dust. Total dust. as Al	List: ACGIH OSHA Z1
Exposure limit(s) Components Aluminum	aj Value 10 mg/m3 15 mg/m3 5 mg/m3 20 ppm 85 mg/m3 40 ppm 170	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit	at machinery. Exposure type Dust. Total dust. as Al Respirable dust. as Al	List: ACGIH OSHA Z1 OSHA Z1
Exposure limit(s) Components Aluminum	aj Value 10 mg/m3 15 mg/m3 5 mg/m3 20 ppm 85 mg/m3	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA):	at machinery. Exposure type Dust. Total dust. as Al Respirable dust. as Al Vapor.	List: ACGIH OSHA Z1 OSHA Z1 ACGIH
Exposure limit(s) Components Aluminum	aj Value 10 mg/m3 15 mg/m3 20 ppm 85 mg/m3 40 ppm 170 mg/m3	Exposure time Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): Time Weighted Average	at machinery. Exposure type Dust. Total dust. as Al Respirable dust. as Al Vapor. Vapor.	List: ACGIH OSHA Z1 OSHA Z1 ACGIH ACGIH

Form
Appearance
Color
Odor
Melting point/range
Boiling Point:
Water solubility

: Solid : Pellets BROWN : Very faint : Not determined : Not applicable : Insoluble

:

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pН

Not applicable : Not determined : : Not established Not applicable : : Not applicable : Not applicable

10. STABILITY AND REACTIVITY

MATERIAL SAFETY DATA SHEET TRANS SEDONA BROWN PEARL

Version Number 1.0 Revision Date 10/21/2004 Page 4 of 7 Print Date 11/16/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
100-42-5	Styrene	Irritant	Eyes, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system,
			Liver, central nervous system
			(CNS).
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
100-42-5	Styrene	LC50	12 gm/m3	rat
		Oral LD50	2,650 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
100-42-5	Styrene	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

PolyOne.

MATERIAL SAFETY DATA SHEET TRANS SEDONA BROWN PEARL

Version Number 1.0 Revision Date 10/21/2004 Page 5 of 7 Print Date 11/16/2011

Additional Health Hazard Information: Styrene 100-42-5 Irritating to eyes, skin, and respiratory tract with many CNS effectssuch as narcosis, cramps and respiratory tract paralysis.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)

MATERIAL SAFETY DATA SHEET TRANS SEDONA BROWN PEARL

Version Number 1.0 Revision Date 10/21/2004 Page 6 of 7 Print Date 11/16/2011

Not applicable

California Proposition:WARNING! This product contains a chemical known to the State of
California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
ALUMINUM (FUME OR DUST)	7429-90-5	16.53
STYRENE	100-42-5	0.19

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Aluminum	7429-90-5	16.53	12
Styrene	100-42-5	0.19	204
2-Propenoic acid, 2-methyl-, methyl ester	80-62-6	0.31	161

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.
7429-90-5
100-42-5

DSL

All of the components of this product are listed on the Canadian Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations.

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Listed
Japan ENCS	:	Not determined

:



MATERIAL SAFETY DATA SHEET TRANS SEDONA BROWN PEARL

Version Number 1.0 Revision Date 10/21/2004 Page 7 of 7 Print Date 11/16/2011

Korea KECI

: Not determined

Philippines PICCS

: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and beliet at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.