## MATERIAL SAFETY DATA SHEET UTAH ORANGE 144C

Version Number 1.0 Revision Date 04/21/2005

Page 1 of 6 Print Date 11/17/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	UTAH ORANGE 144C
Product code :	CC10068733
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous, precipitated and gel	112926-00-8	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Rutile, antimony chromium buff	68186-90-3	10 - 30

### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

## PolyOne.

# MATERIAL SAFETY DATA SHEET UTAH ORANGE 144C

Version Number 1.0 Revision Date 04/21/2005 Page 2 of 6 Print Date 11/17/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foamnone.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	5. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

PolyOne

# MATERIAL SAFETY DATA SHEET UTAH ORANGE 144C

Version Number 1.0 Revision Date 04/21/2005

Storage

Page 3 of 6 Print Date 11/17/2011

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Rutile, antimony	0.5 mg/m3	PEL:	as Sb	OSHA Z1
chromium buff				
	0.5 mg/m3	Time Weighted Average	as Cr	ACGIH
		(TWA):		
	0.5 mg/m3	Time Weighted Average	as Sb	ACGIH
		(TWA):		
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
Silica, amorphous,	10 mg/m3	Time Weighted Average	Dust.	ACGIH
precipitated and gel		(TWA):		
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	0.8 mg/m3	Time Weighted Average		Z3
		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor
- : Solid: Pellets: ORANGE: Very faint

Evaporation rate Specific Gravity: Bulk density Vapor pressure Not applicableNot determinedNot establishedNot applicable



## MATERIAL SAFETY DATA SHEET UTAH ORANGE 144C

Version Number 1.0 Revision Date 04/21/2005 Page 4 of 6 Print Date 11/17/2011

Melting point/range Boiling Point: Water solubility	: N	ot determined ot applicable soluble	Vapour density pH		Not applicable Not applicable
	1	). STABILITY AND R	EACTIVITY		
Stability	:	Stable.			
Hazardous Polymerization	:	Will not occur.			
Conditions to avoid	:	Keep away from oxidiz decomposition, do not		lame.	To avoid thermal
Incompatible Materials	:	Incompatible with stron	ng acids and oxidizing	agen	its.
Hazardous decomposition products	:	Carbon dioxide (CO2), (NOx), other hazardous	,	· ·	ę

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

\_

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
112926-00-8	Silica, amorphous, precipitated and gel	Irritant	Respiratory system, Eyes.
	1 1 0		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory system.
	chromium buff		

#### Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

	12	2. ECOLOGICAL INFORMATION	T
Persistence and degradability	:	Not readily biodegradable.	
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.	
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.	
Additional advice	:	No data available	



# MATERIAL SAFETY DATA SHEET UTAH ORANGE 144C

Version Number 1.0 Revision Date 04/21/2005 Page 5 of 6 Print Date 11/17/2011

Product	· Like most thermonly	actic plactics the prod	uct can be recycled. Wher
Tioduct			or incineration. The
	generator of waste n	naterial has the respon	nsibility for proper waste
		ortation and disposal	
	applicable federal, s	tate/provincial and lo	cal regulations.
Contaminated packaging			e generator of waste mater
			ssification, transportation le federal, state/provincial
	and local regulation		le rederar, state/provinciar
	14. TRANSPORT IN		
U.S. DOT Classification	: Not regulated for tra	insportation.	
ICAO/IATA (air)	: Refer to specific reg	ulation.	
IMO / IMDG (maritime)	: Refer to specific reg	ulation.	
	15. REGULATORY I	NFORMATION	
US Regulations:			
OSHA Status	: Classified as hazard	ous based on compon	ents.
TSCA Status	: All components of t Inventory.	his product are listed	on or exempt from the TSC
US EDA CEDCI A Haranda	·		
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)		
Not applicable			
California Proposition 65	n : Not applicable		
SARA Title III Section 302 I	Extremely Hazardous Substa	nce	
Not applicable			
SARA Title III Section 313	Toxic Chemicals:		
Chemical Name		CAS-No.	Weight %
CHROMIUM III CO	MPOUNDSANTIMONY	68186-90-3	19.29

PolyOne.

## MATERIAL SAFETY DATA SHEET UTAH ORANGE 144C

Version Number 1.0 Revision Date 04/21/2005 Page 6 of 6 Print Date 11/17/2011

Canadian Regulations:

	Chemical Name			Weight %	NPRI ID#
Rutile, antimony chromiun	Rutile, antimony chromium buff		68186-90-3	19.29	69
Rutile, antimony chromiun	m bu	ff	68186-90-3	19.29	17
WHMIS Classification WHMIS Ingredient Disc CAS-No. 68186-90-3 DSL			this product are or	the Considion	Domostia
onal Inventories:	·	Substances List (DS			Domestic
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined			
Korea KECI	:	Listed			
Philippines PICCS	:	Listed			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.