MATERIAL SAFETY DATA SHEET **PG 69224.00 PEARL BU PE**

Version Number 1.1 Revision Date 05/11/2007 Page 1 of 6 Print Date 11/28/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PG 69224.00 PEARL BU PE
Product code	:	CC10069224
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	5 - 10
Mica	12001-26-2	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to available. 		
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 69224.00 PEARL BU PE**

Version Number 1.1 Revision Date 05/11/2007 Page 2 of 6 Print Date 11/28/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit		Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	:	Not applicable
	•	11
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

2/6

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 69224.00 PEARL BU PE**

Version Number 1.1 Revision Date 05/11/2007 Page 3 of 6 Print Date 11/28/2011

ð. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: No personal respiratory protective equipment normally required.				
Eye/Face Protection	: \$: Safety glasses with side-shields			
Hand protection	: Protective gloves				
Skin and body protection	: I	: Long sleeved clothing			
Additional Protective Measures	: Safety shoes				
General Hygiene Considerations		Handle in accordance with good Wash hands before breaks and a		afety practice	
Engineering measures		Heat only in areas with appropri propriate exhaust ventilation a		Provide	
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Mica	20 mppcf	PEL:	Total dust.	OSHA	
				ODIIII	
	3 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH	
	3 mg/m3 3 mg/m3	(TWA): Time Weighted Average	Respirable fraction.		
Titanium dioxide		(TWA): Time Weighted Average (TWA): Time Weighted Average	Respirable fraction.	ACGIH	
Titanium dioxide	3 mg/m3 10 mg/m3	(TWA): Time Weighted Average (TWA):	Respirable fraction.	ACGIH MX OEL	
Titanium dioxide	3 mg/m3	(TWA): Time Weighted Average (TWA): Time Weighted Average (TWA):		ACGIH MX OEL ACGIH	
Titanium dioxide	3 mg/m3 10 mg/m3 15 mg/m3	(TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average	Total dust.	ACGIH MX OEL ACGIH OSHA Z1	
Titanium dioxide	3 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3	(TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit	Total dust. as Ti as Ti	ACGIH MX OEL ACGIH OSHA Z1 MX OEL	
	3 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSI	(TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Total dust. as Ti as Ti PERTIES	ACGIH MX OEL ACGIH OSHA Z1 MX OEL MX OEL	
Form	3 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSI : Soli	(TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Total dust. as Ti as Ti PERTIES ration rate : Not	ACGIH MX OEL ACGIH OSHA Z1 MX OEL MX OEL	
Form Appearance	3 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSI	(TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL):	Total dust. as Ti as Ti PPERTIES ration rate : Not c Gravity : Not	ACGIH MX OEL ACGIH OSHA Z1 MX OEL MX OEL	
Form	3 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSI : Soli- : pelle : BLU	(TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL):	Total dust. as Ti as Ti PERTIES ration rate : Not c Gravity : Not ensity : Not	ACGIH MX OEL ACGIH OSHA Z1 MX OEL MX OEL applicable determined established	
Form Appearance Color	3 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSI : Solit : pelle : BLU : Ver	(TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapor ets Specifi JE Bulk day y faint Vapour	Total dust. as Ti as Ti PPERTIES ration rate : Not c Gravity : Not ensity : Not r pressure : Not	ACGIH MX OEL ACGIH OSHA Z1 MX OEL MX OEL MX OEL	
Form Appearance Color Odour	3 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSI : Solit : pelle : BLU : Ver : Not	(TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapor ets Specifi JE Bulk day y faint Vapour	Total dust. as Ti as Ti PERTIES ration rate : Not c Gravity : Not ensity : Not r pressure : Not r density : Not	ACGIH MX OEL ACGIH OSHA Z1 MX OEL MX OEL applicable determined established	

MATERIAL SAFETY DATA SHEET **PG 69224.00 PEARL BU PE**

Version Number 1.1 Revision Date 05/11/2007 Page 4 of 6 Print Date 11/28/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
12001-26-2	Mica	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 69224.00 PEARL BU PE**

Version Number 1.1 Revision Date 05/11/2007 Page 5 of 6 Print Date 11/28/2011

Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	us Substances (40 CFR 302)
Not applicable	
California Proposition 65	: Not applicable
0.5	
SARA Title III Section 302 E	extremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regula

MATERIAL SAFETY DATA SHEET **PG 69224.00 PEARL BU PE**

Version Number 1.1 Revision Date 05/11/2007 Page 6 of 6 Print Date 11/28/2011

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

:

Not applicable

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No. 12001-26-2

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.