MATERIAL SAFETY DATA SHEET UV WHITE 3101-159

Version Number 1.0 Revision Date 05/18/2005

Page 1 of 7 Print Date 11/18/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number		Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	UV WHITE 3101-159
Product code	:	CC10070027
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Phenol,	25973-55-1	5 - 10
2-(2H-benzotriazol-2-yl)-4,6-bis(1,1-dimeth		
ylpropyl)-		
Cobalt aluminate blue spinel (C.I. Pigment	1345-16-0	0.1 - 1
Blue 28)		
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion Eyes	May be harmful if swallowed.Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET UV WHITE 3101-159

Version Number 1.0 Revision Date 05/18/2005 Page 2 of 7 Print Date 11/18/2011

Medical Conditions	: None known.
Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not applicable
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne
	contaminants.
Unusual Fire/Explosion	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards	(NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1: of this MSDS for proper disposal methods.



MATERIAL SAFETY DATA SHEET **UV WHITE 3101-159**

Version Number 1.0 Revision Date 05/18/2005

Boiling Point:

Water solubility

Page 3 of 7 Print Date 11/18/2011

: Not applicable

	7.	HANDLING AND STORAG	E				
Handling		ake measures to prevent the bu nly in areas with appropriate ex		harge. Heat			
Storage		: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.					
8.	EXPOSURE	CONTROLS / PERSONAL	PROTECTION				
Respiratory protection	: N	o personal respiratory protectiv	ve equipment normally	required.			
Eye/Face Protection	: S	afety glasses with side-shields.					
Hand protection	: P	rotective gloves.					
Skin and body protectior	n : L	ong sleeved clothing.					
Additional Protective Measures	: S	afety shoes.					
General Hygiene Considerations		andle in accordance with good Vash hands before breaks and a		safety practic			
Engineering measures		eat only in areas with appropri ppropriate exhaust ventilation a		Provide			
				Provide			
Exposure limit(s)		ppropriate exhaust ventilation a	at machinery.	Provide List:			
	aj						
Exposure limit(s) Components Cobalt aluminate blue spinel (C.I. Pigment	ap Value 0.10 mg/m3 0.02	Exposure time PEL: Time Weighted Average	at machinery. Exposure type	List:			
Exposure limit(s) Components Cobalt aluminate blue spinel (C.I. Pigment	aj Value 0.10 mg/m3	Exposure time PEL: Time Weighted Average (TWA): Time Weighted Average	at machinery. Exposure type Total dust. as Co	List: OSHA ZI			
Exposure limit(s) Components Cobalt aluminate blue spinel (C.I. Pigment Blue 28)	aj Value 0.10 mg/m3 0.02 mg/m3	Exposure time PEL: Time Weighted Average (TWA):	at machinery. Exposure type Total dust. as Co	List: OSHA ZI ACGIH ACGIH			
Exposure limit(s) Components Cobalt aluminate blue spinel (C.I. Pigment Blue 28)	aj Value 0.10 mg/m3 0.02 mg/m3 10 mg/m3 15 mg/m3	Exposure time PEL: Time Weighted Average (TWA): Time Weighted Average (TWA):	at machinery. Exposure type Total dust. as Co as Co Total dust.	List: OSHA ZI ACGIH			
Exposure limit(s) Components Cobalt aluminate blue spinel (C.I. Pigment Blue 28) Titanium dioxide Form Appearance	aj Value 0.10 mg/m3 0.02 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle	Exposure time PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Exposure type Total dust. as Co as Co Total dust. PERTIES ration rate : No c Gravity: : No	List: OSHA ZI ACGIH ACGIH OSHA ZI			
Exposure limit(s) Components Cobalt aluminate blue spinel (C.I. Pigment Blue 28) Titanium dioxide Form Appearance Color	aj Value 0.10 mg/m3 0.02 mg/m3 10 mg/m3 15 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI	Exposure time PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapor ts Specifi TE Bulk do	Exposure type Total dust. as Co as Co Total dust. PPERTIES ration rate : No c Gravity: : No ensity : No	List: OSHA Z ACGIH ACGIH OSHA Z t applicable t determined t established			
Exposure limit(s) Components Cobalt aluminate blue spinel (C.I. Pigment Blue 28) Titanium dioxide Form Appearance	aj Value 0.10 mg/m3 0.02 mg/m3 10 mg/m3 15 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very	Exposure time PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO L Evapor ts Specifi TE Bulk do faint Vapor	Exposure type Total dust. as Co as Co Total dust. PPERTIES ration rate : No c Gravity: : No ensity : No pressure : No	List: OSHA ZI ACGIH ACGIH OSHA ZI			

pН

: Not applicable

: Insoluble

PolyOne

MATERIAL SAFETY DATA SHEET **UV WHITE 3101-159**

Version Number 1.0 Revision Date 05/18/2005

_

Page 4 of 7 Print Date 11/18/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
25973-55-1	Phenol, 2-(2H-benzotriazol-2-yl)-4 ,6-bis(1,1-dimethylpropyl) -	Systemic effects	Kidney, Liver, reproductive system.
1345-16-0	Cobalt aluminate blue spinel (C.I. Pigment Blue 28)	Irritant	Eyes, Skin, Respiratory system.
		sensitizer	Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP

PolyOne.

MATERIAL SAFETY DATA SHEET UV WHITE 3101-159

Version Number 1.0

Revision Date 05/18/2005

Page 5 of 7 Print Date 11/18/2011

		minate blue spinel ent Blue 28)			
IARC Carcinogen Classif 1 - The component is carc 2A - The component is pr 2B - The component is pr	cinogenic robably ca	rcinogenic to humans.			
NTP Carcinogen Classifi 1 - The component is kno 2 - The component is reas	wn to be a	Ũ	n carcinogen.		
	1	2. ECOLOGICAL IN	FORMATION		
Persistence and degradab	ility :	Not readily biodegra	dable.		
Environmental Toxicity	:	Chemicals are not re polymer matrix.	adily available as	s they are bound	within the
Bioaccumulation Potentia	al :	Chemicals are not re polymer matrix.	adily available as	s they are bound	within the
Additional advice	:	No data available			
	1	3. DISPOSAL CONS	IDERATIONS		
Product	:	Like most thermopla possible recycling is generator of waste m classification, transp applicable federal, st	preferred to disp naterial has the re ortation and disp	osal or incineration sponsibility for provident of the second sec	ion. The proper waste ce with
Contaminated packaging	:	Recycling is preferred has the responsibility and disposal in accor and local regulations	for proper waste dance with appli	e classification, t	ransportation
	1	14. TRANSPORT IN	FORMATION		
		NT-1			
U.S. DOT Classification	:	Not regulated for tra	-		
ICAO/IATA (air)	:	Refer to specific reg			
IMO / IMDG (maritime)	:	Refer to specific reg	ulation.		
	15	5. REGULATORY IN	FORMATION		
US Regulations:					

POLYONE CORPORATION	

PolyOne.

MATERIAL SAFETY DATA SHEET UV WHITE 3101-159

sion Number 1.0 /ision Date 05/18/2005						Prin	t Date	Page 6 11/18/2
OSHA Status	:	Classified as hazardou	us t	based on compo	onen	ts.		
TSCA Status	:	All components of the Inventory.	is p	roduct are liste	d on	or exemp	ot from	the TSCA
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)						
Not applicable								
California Proposition 65	:	Not applicable						
SARA Title III Section 302 Ext Not applicable	rem	ely Hazardous Substand	ce					
SARA Title III Section 313 Tox	cic C	Chemicals:						
Chemical Name				CAS-No.		Weight	%	
COBALT COMPOUNI	DS			1345-16-0		0.44		
National Pollutant Releas Chemical Name Cobalt aluminate blue spin				CAS-No. 345-16-0		/eight % .44	NPRI 70	ID#
Cobait aluminate blue spin Chromium (III) oxide	el (.I. Pigment Blue 28)		308-38-9		.44 .49	70 69	
Iron chromite brown spinel	1			2737-27-8		.42	69	
WHMIS Classification DSL	:	D2B All components of th Substances List (DSL			he C	Canadian	Domest	tic
National Inventories:								
Australia AICS	:	Not determined						
China IECS	:	Not determined						
Europe EINECS	:	Not determined						
Japan ENCS	:	Not determined						
Korea KECI	:	Not determined						
Philippines PICCS	:	Not determined						

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET UV WHITE 3101-159

Version Number 1.0 Revision Date 05/18/2005 Page 7 of 7 Print Date 11/18/2011

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.