MATERIAL SAFETY DATA SHEET **ESB-BLUE**

Version Number 1.1 Revision Date 10/30/2007 Page 1 of 8 Print Date 12/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	ESB-BLUE
Product code	:	CC10070055
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
2,4,8,10-Tetraoxa-3,9-diphosphaspiro[5.5]un	26741-53-7	1 - 5
decane,		
3,9-bis[2,4-bis(1,1-dimethylethyl)phenoxy]-		
Phenol,	25973-55-1	1 - 5
2-(2H-benzotriazol-2-yl)-4,6-bis(1,1-dimeth		
ylpropyl)-		
Decanedioic acid,	52829-07-9	1 - 5
bis(2,2,6,6-tetramethyl-4-piperidinyl) ester		
Aluminum	7429-90-5	1 - 5
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation	Resin particles, like other inert materials, can be mechanica	ally irritating.
Ingestion	May be harmful if swallowed.	



MATERIAL SAFETY DATA SHEET **ESB-BLUE**

ion Number 1.1 sion Date 10/30/2007	Page 2 Print Date 12/2/2
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not applicable
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in



MATERIAL SAFETY DATA SHEET **ESB-BLUE**

ision Date 10/30/2007		Print Date 12/2/2
		plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXF	OSUI	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne

MATERIAL SAFETY DATA SHEET **ESB-BLUE**

Version Number 1.1 Revision Date 10/30/2007

Page 4 of 8 Print Date 12/2/2011

Components	Value	alue Exposure time Exposure type		List:
Aluminum	10 mg/m3	0 mg/m3 Time Weighted Average Dust.		ACGIH
		(TWA):		
	5 mg/m3	Time Weighted Average	Pyrophoric powder. as	ACGIH
		(TWA):	Al	
	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1
	5 mg/m3	Time Weighted Average	Pyrophoric powder.	MX OEL
	(TWA):			
	10 mg/m3	Time Weighted Average	Dust.	MX OEL
		(TWA):		
Titanium dioxide 10 mg		Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
	(TWA):			
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
		(STEL):		

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range Boiling Point: Water solubility
- Solid
 pellets
 BLUE
 Very faint
 Not determined
 Not applicable
 Insoluble

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not applicable
Not determined
Not established
Not applicable
Not applicable
Not applicable

10. STABILITY AND REACTIVITY

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

PolvOne

MATERIAL SAFETY DATA SHEET **ESB-BLUE**

Version Number 1.1 Revision Date 10/30/2007 Page 5 of 8 Print Date 12/2/2011

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
26741-53-7	2,4,8,10-Tetraoxa-3,9-diph	Toxic	Refer to LC50 / LD50 Data on
	osphaspiro[5.5]undecane,		MSDS
	3,9-bis[2,4-bis(1,1-dimeth		
	ylethyl)phenoxy]-		
25973-55-1	Phenol,	Systemic effects	Kidney, Liver, reproductive
	2-(2H-benzotriazol-2-yl)-4		system.
	,6-bis(1,1-dimethylpropyl)		
	-		
52829-07-9	Decanedioic acid,	Irritant	Eyes.
	bis(2,2,6,6-tetramethyl-4-p		
	iperidinyl) ester		
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
26741-53-7	2,4,8,10-Tetraoxa-3,9-diph	LC50	> 2 gm/m3	rat
	osphaspiro[5.5]undecane,	Oral LD50	5,580 mg/kg	rat
	3,9-bis[2,4-bis(1,1-dimeth	Dermal LD50	> 200 mg/kg	rabbit
	ylethyl)phenoxy]-			
52829-07-9	Decanedioic acid,	Oral LD50	3,700 mg/kg	rat
	bis(2,2,6,6-tetramethyl-4-p	Dermal LD50	> 3,100 mg/kg	rabbit
	iperidinyl) ester			

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

ĺ	CAS-No.	Chemical Name	OSHA	IARC	NTP
	13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.



MATERIAL SAFETY DATA SHEET **ESB-BLUE**

sion Number 1.1	Page 6
vision Date 10/30/2007	Print Date 12/2/2
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous S	ubstances (40 CFR 302)
Not applicable	
California Proposition 65	: Not applicable

MATERIAL SAFETY DATA SHEET **ESB-BLUE**

Version Number 1.1 Revision Date 10/30/2007 Page 7 of 8 Print Date 12/2/2011

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

U	nless specific chemicals are identified under this section, this	s product is Not Ap	plicable under this	s regulation
	Chemical Name	CAS-No.	Weight %	
	ALUMINUM (FUME OR DUST)	7429-90-5	1.00 - 5.00	

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Aluminum	7429-90-5	1.00 - 5.00	12

WHMIS Classification : D1B

WHMIS Ingredient Disclosure List

7429-90-5	

:

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Austra	alia AICS	:	Listed
China	IECS	:	Listed
Europ	e EINECS	:	Listed
Japan	ENCS	:	Not determined
Korea	KECI	:	Not determined
Philip	pines PICCS	:	Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The

PolyOne.

MATERIAL SAFETY DATA SHEET **ESB-BLUE**

Version Number 1.1 Revision Date 10/30/2007 Page 8 of 8 Print Date 12/2/2011

information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.