MATERIAL SAFETY DATA SHEET

ESB-WHITE

Version Number 1.0 Revision Date 05/18/2005 Page 1 of 6 Print Date 11/18/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	ESB-WHITE
Product code	:	CC10070056
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
2,4,8,10-Tetraoxa-3,9-diphosphaspiro[5.5]un	26741-53-7	1 - 5
decane,		
3,9-bis[2,4-bis(1,1-dimethylethyl)phenoxy]-		
Phenol,	25973-55-1	5 - 10
2-(2H-benzotriazol-2-yl)-4,6-bis(1,1-dimeth		
ylpropyl)-		
Decanedioic acid,	52829-07-9	5 - 10
bis(2,2,6,6-tetramethyl-4-piperidinyl) ester		
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Ingestion, Skin contact	
--	--

Acute exposure

Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.



MATERIAL SAFETY DATA SHEET **ESB-WHITE**

Version Number 1.0 Revision Date 05/18/2005 Page 2 of 6 Print Date 11/18/2011

		Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	:	Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	:	None known.
		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	: : :	Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A(CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.



MATERIAL SAFETY DATA SHEET **ESB-WHITE**

Version Number 1.0 Revision Date 05/18/2005

Page 3 of 6 Print Date 11/18/2011

		HANDLING AND STORA	-			
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.					
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.					
8. 1	XPOSURE	CONTROLS / PERSONAL	PROTECTION			
Respiratory protection	: N	o personal respiratory protect	ive equipment normally	v required.		
Eye/Face Protection	: S	afety glasses with side-shields	S.			
Hand protection	: P	rotective gloves.				
Skin and body protection	: L	ong sleeved clothing.				
Additional Protective Measures	: S	afety shoes.				
General Hygiene Considerations		andle in accordance with good ash hands before breaks and		safety practic		
Engineering measures		eat only in areas with approproprion of the second se		. Provide		
			•			
Exposure limit(s)			·			
Exposure limit(s) Components	Value	Exposure time	Exposure type	List:		
	Value 10 mg/m3	Exposure time Time Weighted Average (TWA):	Exposure type	List: ACGIH		
Components		Time Weighted Average	Exposure type Total dust.	ACGIH		
Components	10 mg/m3 15 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH		
Components Titanium dioxide	10 mg/m3 15 mg/m3 9. PHYSIC	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Total dust.	ACGIH OSHA ZI		
Components Titanium dioxide Form	10 mg/m3 15 mg/m3 9. PHYSIC : Solic	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Total dust. DPERTIES pration rate : No	ACGIH OSHA ZI		
Components Titanium dioxide Form Appearance	10 mg/m3 15 mg/m3 9. PHYSIC	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo ts Specifi	Total dust. DPERTIES Dration rate : No fic Gravity: : No	ACGIH OSHA ZI		
Components Titanium dioxide Form	10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : WHI	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo Its Specifi TE Bulk of	Total dust. DPERTIES pration rate : No fic Gravity: : No density : No	ACGIH OSHA Z1 ot applicable ot determined ot established		
Components Titanium dioxide Form Appearance Color Odor	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Evapo ts Specif TE Bulk of faint Vapor	Total dust. Total dust. DPERTIES oration rate : No fic Gravity: : No lensity : No pressure : No	ACGIH OSHA ZI		
Components Titanium dioxide Form Appearance Color	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not of	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Evapo ts Specif TE Bulk of faint Vapor	Total dust. DPERTIES oration rate : No fic Gravity: : No lensity : No pressure : No ur density : No	ACGIH OSHA Z1 ot applicable ot determined ot established		
Components Titanium dioxide Form Appearance Color Odor Melting point/range	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not of	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO ts Specifi TE Bulk of faint Vapor determined Vapor applicable pH	Total dust. DPERTIES oration rate : No fic Gravity: : No lensity : No pressure : No ur density : No	ACGIH OSHA ZI		
Components Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : WHI : Very : Not a : Insol	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO ts Specifi TE Bulk of faint Vapor determined Vapor applicable pH	Total dust. DPERTIES Dration rate : No Tic Gravity: : No lensity : No pressure : No ur density : No : No	ACGIH OSHA ZI		
Components Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not a : Insol 10. §	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO ts Specifi TE Bulk of faint Vapor determined Vapor applicable pH uble	Total dust. DPERTIES Dration rate : No Tic Gravity: : No lensity : No pressure : No ur density : No : No	ACGIH OSHA Z1 ot applicable ot determined ot established ot applicable ot applicable		



MATERIAL SAFETY DATA SHEET **ESB-WHITE**

Version Number 1.0 Revision Date 05/18/2005		Page 4 of 6 Print Date 11/18/2011
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
26741-53-7	2,4,8,10-Tetraoxa-3,9-diph	toxic	Refer to LC50 / LD50 Data on
	osphaspiro[5.5]undecane,		MSDS
	3,9-bis[2,4-bis(1,1-dimeth		
	ylethyl)phenoxy]-		
25973-55-1	Phenol,	Systemic effects	Kidney, Liver, reproductive
	2-(2H-benzotriazol-2-yl)-4		system.
	,6-bis(1,1-dimethylpropyl)		
	-		
52829-07-9	Decanedioic acid,	Irritant	Eyes.
	bis(2,2,6,6-tetramethyl-4-p		
	iperidinyl) ester		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
26741-53-7	2,4,8,10-Tetraoxa-3,9-diph	LC50	> 2 gm/m3	rat
	osphaspiro[5.5]undecane,	Oral LD50	5,580 mg/kg	rat
	3,9-bis[2,4-bis(1,1-dimeth	Dermal LD50	> 200 mg/kg	rabbit
	ylethyl)phenoxy]-			
52829-07-9	Decanedioic acid,	Oral LD50	3,700 mg/kg	rat
	bis(2,2,6,6-tetramethyl-4-p	Dermal LD50	> 3,100 mg/kg	rabbit
	iperidinyl) ester			

12. ECOLOGICAL INFORMATION

4/6

Persistence and degradability

: Not readily biodegradable.

Environmental Toxicity

: Chemicals are not readily available as they are bound within the

polymer matrix.



MATERIAL SAFETY DATA SHEET **ESB-WHITE**

Version Number 1.0 Revision Date 05/18/2005 Page 5 of 6 Print Date 11/18/2011

	polymer matrix.	
Additional advice	: No data available	
	13. DISPOSAL CONSIDERATIONS	
Product	: Like most thermoplastic plastics the product can be recycled. W possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper wast classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
Contaminated packaging	: Recycling is preferred when possible. The generator of waste ma has the responsibility for proper waste classification, transportati and disposal in accordance with applicable federal, state/provinci and local regulations.	on
	14. TRANSPORT INFORMATION	
U.S. DOT Classification	: Not regulated for transportation.	
ICAO/IATA (air)	: Refer to specific regulation.	
IMO / IMDG (maritime)	: Refer to specific regulation.	
	15. REGULATORY INFORMATION	
US Regulations:		
OSHA Status	: Classified as hazardous based on components.	
TSCA Status	: All components of this product are listed on or exempt from the T Inventory.	SC.
US. EPA CERCLA Hazardou	Substances (40 CFR 302)	
Not applicable		
California Proposition 65	: Not applicable	
SARA Title III Section 302 E Not applicable	tremely Hazardous Substance	

PolyOne.

MATERIAL SAFETY DATA SHEET

ESB-WHITE

Version Number 1.0 Revision Date 05/18/2005 Page 6 of 6 Print Date 11/18/2011

SARA Title III Section 313 Toxic Chemicals:

Not applicable Canadian Regulations:

Chemical Name			CAS-No.	Weight %	NPRI ID#
Aluminum oxide			1344-28-1	0.35	13
WHMIS Classification	:	D1B			
DSL	:	All components of th Substances List (DSL		n the Canadian	Domestic
ional Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined			
Korea KECI	:	Listed			
Philippines PICCS	:	Listed			

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.