#### MATERIAL SAFETY DATA SHEET

## STAN-TONE VC-29872 DA4 SILVER STEEL MET

Version Number 1.0 Revision Date 05/23/2005 Page 1 of 6 Print Date 11/18/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).	
Product name	STAN-TONE VC-29872 DA4 SILVER STEEL MET	
Product code	CC10070535	
Chemical Name	Mixture	
CAS-No.	Mixture	
Product Use	Industrial Applications	

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Mica	12001-26-2	1 - 5
Aluminum	7429-90-5	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

## PolyOne.

MATERIAL SAFETY DATA SHEET

## STAN-TONE VC-29872 DA4 SILVER STEEL MET

Version Number 1.0 Revision Date 05/23/2005 Page 2 of 6 Print Date 11/18/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foamnone.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen</li> </ul>
Hazards	(NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1: of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



### MATERIAL SAFETY DATA SHEET STAN-TONE VC-29872 DA4 SILVER STEEL MET

#### Version Number 1.0 Revision Date 05/23/2005

Page 3 of 6 Print Date 11/18/2011

Handling		ake measures to prevent the neasures to prevent the nly in areas with appropriate	ne build up of electrostatic c ate exhaust ventilation.	harge. Heat
Storage		Leep containers dry and tig nd contamination. Keep in	htly closed to avoid moistur n a dry, cool place.	e absorption
8. E	XPOSURE	CONTROLS / PERSON	AL PROTECTION	
Respiratory protection	: N	lo personal respiratory pro	tective equipment normally	required.
Eye/Face Protection	: S	afety glasses with side-shi	elds.	
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations			good industrial hygiene and a and at the end of workday.	safety practice.
Engineering measures Exposure limit(s)		leat only in areas with app ppropriate exhaust ventilat	ropriate exhaust ventilation. tion at machinery.	Provide
	X7 1			<b>.</b>
Components Aluminum	Value	Exposure time	Exposure type	List: ACGIH
Alummum	10 mg/m3	Time Weighted Averag (TWA):	ge Dust.	ACGIH
	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1
Mica	20 mppcf	PEL:	Total dust.	OSHA
	3 mg/m3	Time Weighted Averag (TWA):	ge Respirable fraction.	ACGIH
	9. PHYSIC	CAL AND CHEMICAL	PROPERTIES	
Form	: Solic	4 D-	vaporation rate : No	t applicable
Appearance	: Pelle			t determined
Color	: GRE		-	t established
Odor			•	t applicable
Melting point/range				t applicable
Boiling Point:		applicable pH		t applicable
Water solubility	: Insol			11

#### **10. STABILITY AND REACTIVITY**

Stability

: Stable.



# MATERIAL SAFETY DATA SHEET STAN-TONE VC-29872 DA4 SILVER STEEL MET

Version Number 1.0 Revision Date 05/23/2005 Page 4 of 6 Print Date 11/18/2011

Hazardous Polymerization Conditions to avoid	:	Will not occur. Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
12001-26-2	Mica	Systemic effects	Respiratory system.
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The

Page 5 of 6

## POLYONE CORPORATION

### MATERIAL SAFETY DATA SHEET STAN-TONE VC-29872 DA4 SILVER STEEL MET Version Number 1.0 Revision Date 05/23/2005 Print Date 11/18/2011 generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. **14. TRANSPORT INFORMATION** U.S. DOT Classification Not regulated for transportation. : ICAO/IATA (air) Refer to specific regulation. IMO / IMDG (maritime) Refer to specific regulation. **15. REGULATORY INFORMATION US Regulations: OSHA Status** Classified as hazardous based on components. ÷ **TSCA Status** All components of this product are listed on or exempt from the TSCA ÷ Inventory. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable California Proposition : Not applicable 65 SARA Title III Section 302 Extremely Hazardous Substance Not applicable SARA Title III Section 313 Toxic Chemicals: Chemical Name CAS-No. Weight % ALUMINUM (FUME OR DUST) 7429-90-5 13.45 Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name CAS-No. Weight % NPRI ID#

# MATERIAL SAFETY DATA SHEET STAN-TONE VC-29872 DA4 SILVER STEEL MET

Version Number 1.0 Revision Date 05/23/2005 Page 6 of 6 Print Date 11/18/2011

Chemical Name	CAS-No.	Weight %	NPRI ID#
Aluminum	7429-90-5	13.45	12
Misc00005- Misc Zinc Cpd's	Not Available	0.69	241

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

·

CAS-No.
7429-90-5
12001-26-2

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.