MATERIAL SAFETY DATA SHEET LEVLAD GREEN FD

Version Number 1.1 Revision Date 11/06/2007

Page 1 of 6 Print Date 12/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
LEVLAD GREEN FD
CC10073701
Mixture
Mixture
Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Mica	12001-26-2	10 - 30
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure Medical Conditions	Refer to Section 11 for Toxicological Information.None known.
Aggravated by Exposure:	

PolyOne.

MATERIAL SAFETY DATA SHEET LEVLAD GREEN FD

Version Number 1.1 Revision Date 11/06/2007 Page 2 of 6 Print Date 12/2/2011

	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.	of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.	at
Skin	: Wash off with soap and plenty of water. If skin irritation persists se medical attention.	ek
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, Dry powder, Foam. 	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positiv pressure mode should be worn to prevent inhalation of airborne contaminants.	e
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	
	5. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should n be allowed to enter drains, water courses or the soil.	ot
Methods for cleaning up	: Clean up promptly by scoop or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.	13
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.	
Storage	: Keep containers dry and tightly closed to avoid moisture absorption	l

PolyOne.

MATERIAL SAFETY DATA SHEET LEVLAD GREEN FD

Version Number 1.1 Revision Date 11/06/2007 Page 3 of 6 Print Date 12/2/2011

8. EXPOSURE CONTROLS / PERSONAL PROTECTION				
Respiratory protection		To personal respiratory protecti usty conditions occur wear app		
Eye/Face Protection	: S	: Safety glasses		
Hand protection	: P	: Protective gloves		
Skin and body protection	: L	long sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations	р	Vash hands and face before bre roduct. Handle in accordance ractice for diagnostics.		
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
			2	
Exposure limit(s)			-	
Exposure limit(s) Components	Value	Exposure time		List:
-	Value 3 mg/m3	Exposure time Time Weighted Average (TWA):	Exposure type Respirable fraction.	List: ACGIH
Components		Time Weighted Average	Exposure type	
Components	3 mg/m3	Time Weighted Average (TWA): Time Weighted Average	Exposure type	ACGIH
Components Mica	3 mg/m3 3 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average	Exposure type	ACGIH MX OEL
Components Mica	3 mg/m3 3 mg/m3 10 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA):	Exposure type Respirable fraction.	ACGIH MX OEL ACGIH
Mica	3 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average	Exposure type Respirable fraction.	ACGIH MX OEL ACGIH OSHA Z1
Components Mica	3 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit	Exposure type Respirable fraction. Total dust. as Ti as Ti	ACGIH MX OEL ACGIH OSHA Z1 MX OEL

10. STABILITY AND REACTIVITY

MATERIAL SAFETY DATA SHEET LEVLAD GREEN FD

Version Number 1.1 Revision Date 11/06/2007

Page 4 of 6 Print Date 12/2/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
12001-26-2	Mica	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Not inherently biodegradable.
Additional advice	:	Chemicals are not readily available as they are bound within the

PolyOne.

MATERIAL SAFETY DATA SHEET LEVLAD GREEN FD

Version Number 1.1 Revision Date 11/06/2007 Page 5 of 6 Print Date 12/2/2011

	polymer matrix.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	us Substances (40 CFR 302)
Not applicable	
California Proposition 65	n : Not applicable
SARA Title III Section 302 E	Extremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulat
SARA Title III Section 313 T	oxic Chemicals.

PolyOne.

MATERIAL SAFETY DATA SHEET LEVLAD GREEN FD

Version Number 1.1 Revision Date 11/06/2007 Page 6 of 6 Print Date 12/2/2011

Unless specific chemicals are identified	under this section, this product is Not Applicable under this regulation
Canadian Regulations:	
National Pollutant Release Inven	tory (NPRI)
Not applicable	
WHMIS Classification : D2	A
WHMIS Ingredient Disclosure L	ist
CAS-No. 12001-26-2	
	ll components of this product are on the Canadian Domestic bstances List (DSL) or are exempt.
National Inventories:	
Australia AICS : Li	sted
China IECS : Li	sted
Europe EINECS : Li	sted
Japan ENCS : No	t determined
Korea KECI : No	t determined
Philippines PICCS : Li	sted
10	5. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.