# MATERIAL SAFETY DATA SHEET **PG 78035.00 PEARL BU PP SL**

Version Number 1.0 Revision Date 05/10/2007 Page 1 of 6 Print Date 11/28/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PG 78035.00 PEARL BU PP SL
Product code	:	CC10078035
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

## 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5
Mica	12001-26-2	5 - 10

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to avage</li> </ul>		
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		

PolyOne.

# MATERIAL SAFETY DATA SHEET PG 78035.00 PEARL BU PP SL

Version Number 1.0 Revision Date 05/10/2007 Page 2 of 6 Print Date 11/28/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not applicable
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 7 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

PolyOne.

# MATERIAL SAFETY DATA SHEET PG 78035.00 PEARL BU PP SL

Version Number 1.0 Revision Date 05/10/2007 Page 3 of 6 Print Date 11/28/2011

0 1	VDOGUDE	CONTROLS / PERSONAL	DDATECTION			
δ. Γ	LAPUSUKE	CONTROLS / FERSUNAL	TRUIEUIIUN			
Respiratory protection	: No personal respiratory protective equipment normally required.					
Eye/Face Protection	: S	: Safety glasses with side-shields				
Hand protection	: P	rotective gloves				
Skin and body protection	: L	ong sleeved clothing				
Additional Protective Measures	: S	afety shoes				
General Hygiene Considerations		Iandle in accordance with good Vash hands before breaks and a		afety practic		
Engineering measures		leat only in areas with appropri ppropriate exhaust ventilation a		Provide		
Exposure limit(s)						
Components	Value	Exposure time	Exposure type	List:		
Components Mica	Value 20 mppcf	Exposure time PEL:	Exposure type Total dust.	List: OSHA		
Components Mica	Value 20 mppcf 3 mg/m3	Ĭ	Exposure type Total dust. Respirable fraction.	List: OSHA ACGIH		
-	20 mppcf	PEL: Time Weighted Average	Total dust.	OSHA ACGIH		
-	20 mppcf 3 mg/m3	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average	Total dust.	OSHA ACGIH		
Mica	20 mppcf 3 mg/m3 3 mg/m3	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA):	Total dust.	OSHA ACGIH MX OEL ACGIH		
Mica	20 mppcf 3 mg/m3 3 mg/m3 10 mg/m3	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA):	Total dust. Respirable fraction.	OSHA ACGIH MX OEL ACGIH OSHA ZI		
Mica	20 mppcf 3 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average	Total dust. Respirable fraction. Total dust.	OSHA ACGIH MX OEL ACGIH OSHA Z1 MX OEL		
Mica	20 mppcf 3 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL):	Total dust. Respirable fraction. Total dust. as Ti as Ti	OSHA ACGIH MX OEL ACGIH OSHA Z1 MX OEL		
Mica	20 mppcf 3 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit	Total dust. Respirable fraction. Total dust. as Ti as Ti	OSHA ACGIH MX OEL ACGIH OSHA Z1 MX OEL		
Mica	20 mppcf 3 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Total dust. Respirable fraction. Total dust. as Ti as Ti PERTIES	OSHA ACGIH MX OEL ACGIH OSHA Z1 MX OEL		
Mica Titanium dioxide	20 mppcf 3 mg/m3 3 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC	PEL:         Time Weighted Average (TWA):         Time Weighted Average (TWA):         Time Weighted Average (TWA):         PEL:         Time Weighted Average (TWA):         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRO         ts       Specifi	Total dust.         Respirable fraction.         Total dust.         as Ti         as Ti         PERTIES         ation rate       : Not         c Gravity       : Not	OSHA ACGIH MX OEL ACGIH OSHA ZI MX OEL MX OEL		
Mica Titanium dioxide Form	20 mppcf 3 mg/m3 3 mg/m3 10 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : Solid : pelle : BLU	PEL:         Time Weighted Average (TWA):         Time Weighted Average (TWA):         Time Weighted Average (TWA):         PEL:         Time Weighted Average (TWA):         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRO         ts       Specifi         Te       Bulk de	Total dust. Respirable fraction. Total dust. as Ti as Ti PERTIES ration rate : Not c Gravity : Not ensity : Not	OSHA ACGIH MX OEL ACGIH OSHA ZI MX OEL MX OEL		
Mica Titanium dioxide Form Appearance Color Odour	20 mppcf 3 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : Solid : pelle : BLU : Very	PEL:         Time Weighted Average (TWA):         Time Weighted Average (TWA):         Time Weighted Average (TWA):         PEL:         Time Weighted Average (TWA):         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRO         d       Evapor         E       Bulk day         faint       Vapour	Total dust. Respirable fraction. Total dust. as Ti as Ti PERTIES ation rate : Not c Gravity : Not ensity : Not pressure : Not	OSHA ACGIH MX OEL ACGIH OSHA ZI MX OEL MX OEL MX OEL		
Mica Titanium dioxide Form Appearance Color	20 mppcf 3 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSIC : Solid : pelle : BLU : Very : Not	PEL:         Time Weighted Average (TWA):         Time Weighted Average (TWA):         Time Weighted Average (TWA):         PEL:         Time Weighted Average (TWA):         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRO         d       Evapor         E       Bulk day         faint       Vapour	Total dust. Respirable fraction. Total dust. as Ti as Ti PERTIES ation rate : Not c Gravity : Not ensity : Not pressure : Not c density : Not	OSHA ACGIH MX OEL ACGIH OSHA ZI MX OEL MX OEL applicable determined established		

## 10. STABILITY AND REACTIVITY

# MATERIAL SAFETY DATA SHEET **PG 78035.00 PEARL BU PP SL**

Version Number 1.0 Revision Date 05/10/2007 Page 4 of 6 Print Date 11/28/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
12001-26-2	Mica	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

## **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.

PolyOne.

# MATERIAL SAFETY DATA SHEET **PG 78035.00 PEARL BU PP SL**

Version Number 1.0 Revision Date 05/10/2007 Page 5 of 6 Print Date 11/28/2011

Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	as Substances (40 CFR 302)
Not applicable	
California Proposition	: Not applicable
65	
SARA Title III Section 302 E	xtremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regula

# MATERIAL SAFETY DATA SHEET **PG 78035.00 PEARL BU PP SL**

Version Number 1.0 Revision Date 05/10/2007 Page 6 of 6 Print Date 11/28/2011

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

:

Not applicable

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No. 12001-26-2

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Listed

## **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.