## MATERIAL SAFETY DATA SHEET

## Op. Coyote 451c

Version Number 1.1 Revision Date 12/01/2006 Page 1 of 6 Print Date 11/25/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	Op. Coyote 451c
Product code	:	CC10082539
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Chromium (III) oxide	1308-38-9	1 - 5
Titanium dioxide	13463-67-7	5 - 10

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	<ul><li>Resin particles, like other inert materials, can be mechanically irritating.</li><li>May be harmful if swallowed.</li></ul>
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



# MATERIAL SAFETY DATA SHEET **Op. Coyote 451c**

Version Number 1.1 Revision Date 12/01/2006 Page 2 of 6 Print Date 11/25/2011

	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all ca doubt seek medical advice.	
Ingestion	: Do not induce vomiting without medical advice. When symptometry persist or in all cases of doubt seek medical advice.	ms
Eyes	: Rinse immediately with plenty of water, also under the eyelids, least 15 minutes. If eye irritation persists, seek medical attention	
Skin	: Wash off with soap and plenty of water. If skin irritation persis medical attention.	ts seel
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
Flammable Limits		
Upper explosion limit	: Not applicable	
Lower explosion limit	: Not applicable	
Autoignition temperature	: Not applicable	
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in por pressure mode should be worn to prevent inhalation of airborne contaminants.	
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrog (NOx), other hazardous materials, and smoke are all possible.	gen
	ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product shou be allowed to enter drains, water courses or the soil.	ld not
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all materi plastic, cardboard or metal containers for disposal. Refer to Sec of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. I only in areas with appropriate exhaust ventilation.	Heat
Storage	: Keep containers dry and tightly closed to avoid moisture absorp	otion

2/6

PolyOne.

## MATERIAL SAFETY DATA SHEET Op. Coyote 451c

Version Number 1.1 Revision Date 12/01/2006 Page 3 of 6 Print Date 11/25/2011

8. I	EXPOSURE	CONTROLS / PERSON	AL PROTECTION		
Respiratory protection	: N	o personal respiratory pro	tective equipment normall	y required.	
Eye/Face Protection	: S	afety glasses with side-shi	elds.		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		andle in accordance with g	good industrial hygiene and and at the end of workday.	l safety practice	
Engineering measures		leat only in areas with app ppropriate exhaust ventilat	ropriate exhaust ventilation ion at machinery.	n. Provide	
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Chromium (III) oxide	0.5 mg/m3	Time Weighted Averag (TWA):	ge as Cr	ACGIH	
	0.5 mg/m3	PEL:	as Cr	OSHA Z1	
Titanium dioxide	10 mg/m3	Time Weighted Averag (TWA):	je	ACGIH	
	15 mg/m3	PEL:	Total dust.	OSHA Z1	
	20 mg/m3	Short Term Exposure Lin (STEL):	mit as Ti	MX OEL	
	9. PHYSIC	CAL AND CHEMICAL	PROPERTIES		
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				
Form	: Solic		aporation rate : N	ot applicable	
Appearance	: Pelle : BRO	1	2	ot determined	
Color Odor				ot established ot applicable	
Melting point/range				ot applicable	
Boiling Point:		applicable pH		ot applicable	
Water solubility	: Insoluble				
	10. 8	STABILITY AND REAC	TIVITY		
Stability	: S	table.			
Hazardous Polymerization	n : W	Vill not occur.			



# MATERIAL SAFETY DATA SHEET **Op. Coyote 451c**

Version Number 1.1 Revision Date 12/01/2006		Page 4 of 6 Print Date <i>11/25/2011</i>
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1308-38-9	Chromium (III) oxide	Irritant	Eyes, Skin.
		sensitizer	Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7 Titanium dioxide		no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:

Chromium (III) oxide 1308-38-9 The bi- and trivalent forms of chrome have a low order of acute toxicity, but may cause skin sensitization and irritation to the eyes. No effects have been reported for chromium (III) oxide. Chromium (III) compounds are not considered carcinogenic in animals or humans

### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the

**POLYONE CORPORATION** 



# MATERIAL SAFETY DATA SHEET **Op. Coyote 451c**

Version Number 1.1 Revision Date 12/01/2006

Page 5 of 6 Print Date 11/25/2011

	polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardo	is Substances (40 CFR 302)
Not applicable	
California Proposition 65	n : Not applicable
SARA Title III Section 302 F	Extremely Hazardous Substance

## MATERIAL SAFETY DATA SHEET

## Op. Coyote 451c

Version Number 1.1 Revision Date 12/01/2006 Page 6 of 6 Print Date 11/25/2011

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight %
CHROMIUM III COMPOUNDS	1308-38-9	1.00 - 5.00
ZINC COMPOUNDS	12063-19-3	1.00 - 5.00

Canadian Regulations:

CAS-No.	Weight %	NPRI ID#
1308-38-9	1.00 - 5.00	69
12063-19-3	1.00 - 5.00	231
	1308-38-9	1308-38-9 1.00 - 5.00

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

ĺ	CAS-No.
	1308-38-9

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

: Listed
: Listed
: Listed
: Not determined
: Listed
: Listed

:

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.