### MATERIAL SAFETY DATA SHEET

### Honey 4655c

Version Number 1.1 Revision Date 12/01/2006 Page 1 of 6 Print Date 11/25/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	Honey 4655c
Product code	:	CC10087550
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Iron oxide	1309-37-1	1 - 5
Titanium dioxide	13463-67-7	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to</li> </ul>
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



# MATERIAL SAFETY DATA SHEET *Honey 4655c*

Version Number 1.1 Revision Date 12/01/2006 Page 2 of 6 Print Date 11/25/2011

	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all case doubt seek medical advice.	s of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	3
Eyes	: Rinse immediately with plenty of water, also under the eyelids, fo least 15 minutes. If eye irritation persists, seek medical attention.	r at
Skin	: Wash off with soap and plenty of water. If skin irritation persists medical attention.	seel
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
Flammable Limits		
Upper explosion limit	: Not applicable	
Lower explosion limit	: Not applicable	
Autoignition temperature	: Not applicable	
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positi pressure mode should be worn to prevent inhalation of airborne contaminants.	ve
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitroger (NOx), other hazardous materials, and smoke are all possible.	l
	5. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should be allowed to enter drains, water courses or the soil.	not
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material plastic, cardboard or metal containers for disposal. Refer to Sectio of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. He only in areas with appropriate exhaust ventilation.	at
Storage	: Keep containers dry and tightly closed to avoid moisture absorption	on

2/6



# MATERIAL SAFETY DATA SHEET *Honey 4655c*

Version Number 1.1 Revision Date 12/01/2006

\_\_\_\_\_

\_\_\_\_

\_\_\_\_

Page 3 of 6 Print Date 11/25/2011

Eye/Face Protection       : Safety         Hand protection       : Protection         Skin and body protection       : Long state         Additional Protective       : Safety         Measures       : Safety         General Hygiene       : Handle         Considerations       : Heat o         Engineering measures       : Heat o         Exposure limit(s)       : Safety         Components       Value         Iron oxide       : 5 mg/m3         5 mg/m3       Ti         Titanium dioxide       10 mg/m3         15 mg/m3       : 15 mg/m3         20 mg/m3       Sho	glasses with side-sh tive gloves. eleeved clothing. shoes. e in accordance with hands before breaks	good industrial hygier and at the end of work propriate exhaust venti- tion at machinery.	ne and safety practice. kday. ilation. Provide ype List: MX OEL MX OEL
Hand protection       : Protection         Skin and body protection       : Long s         Additional Protective       : Safety         Measures       : Handle         General Hygiene       : Handle         Considerations       : Wash line         Engineering measures       : Heat o         approp       : Exposure limit(s)         Components       Value         Iron oxide       5 mg/m3         5 mg/m3       Ti         10 mg/m3       Sho         15 mg/m3       10         20 mg/m3       Sho	tive gloves. leeved clothing. shoes. e in accordance with hands before breaks nly in areas with app oriate exhaust ventila Exposure time me Weighted Avera (TWA): rt Term Exposure Li (STEL): me Weighted Avera (TWA): me Weighted Avera (TWA): me Weighted Avera (TWA): me Weighted Avera	good industrial hygier and at the end of work propriate exhaust venti- tion at machinery.	kday. ilation. Provide ype List: MX OEL MX OEL ction. ACGIH
Skin and body protection       : Long s         Additional Protective       : Safety         Measures       : Handle         General Hygiene       : Handle         Considerations       : Wash b         Engineering measures       : Heat o         approp       : Exposure limit(s)         Components       Value         Iron oxide       5 mg/m3         5 mg/m3       Ti         10 mg/m3       Sho         15 mg/m3       Ti         15 mg/m3       Sho         20 mg/m3       Sho	e in accordance with hands before breaks nly in areas with app oriate exhaust ventila Exposure time me Weighted Avera (TWA): rt Term Exposure Li (STEL): me Weighted Avera (TWA): me Weighted Avera (TWA): me Weighted Avera	and at the end of work propriate exhaust venti- ition at machinery. Exposure ty ge as Fe imit as Fe ge Respirable frac	kday. ilation. Provide ype List: MX OEL MX OEL ction. ACGIH
Additional Protective       : Safety         Measures       : Handle         General Hygiene       : Handle         Considerations       Wash         Engineering measures       : Heat o         approp         Exposure limit(s)         Components       Value         Iron oxide       5 mg/m3         5 mg/m3       Ti         10 mg/m3       Sho         5 mg/m3       Ti         15 mg/m3       20 mg/m3         20 mg/m3       Sho	shoes. e in accordance with hands before breaks nly in areas with app oriate exhaust ventila <u>Exposure time</u> me Weighted Avera (TWA): rt Term Exposure Li (STEL): me Weighted Avera (TWA): me Weighted Avera (TWA): me Weighted Avera	and at the end of work propriate exhaust venti- ition at machinery. Exposure ty ge as Fe imit as Fe ge Respirable frac	kday. ilation. Provide ype List: MX OEL MX OEL ction. ACGIH
Measures         General Hygiene       : Handle         Considerations       Wash I         Engineering measures       : Heat o         approp         Exposure limit(s)         Components       Value         Iron oxide       5 mg/m3         10 mg/m3       Sho         5 mg/m3       Ti         Titanium dioxide       10 mg/m3         15 mg/m3       Ti         20 mg/m3       Sho	e in accordance with hands before breaks nly in areas with app oriate exhaust ventila <u>Exposure time</u> me Weighted Avera (TWA): rt Term Exposure Li (STEL): me Weighted Avera (TWA): me Weighted Avera (TWA): me Weighted Avera	and at the end of work propriate exhaust venti- ition at machinery. Exposure ty ge as Fe imit as Fe ge Respirable frac	kday. ilation. Provide ype List: MX OEL MX OEL ction. ACGIH
Considerations       Wash I         Engineering measures       : Heat o         Exposure limit(s)       : Heat o         Components       Value         Iron oxide       5 mg/m3         10 mg/m3       Sho         5 mg/m3       Ti         Titanium dioxide       10 mg/m3         15 mg/m3       20 mg/m3         20 mg/m3       Sho	hands before breaks nly in areas with app oriate exhaust ventila Exposure time me Weighted Avera (TWA): rt Term Exposure Li (STEL): me Weighted Avera (TWA): me Weighted Avera (TWA): PEL:	and at the end of work propriate exhaust venti- ition at machinery. Exposure ty ge as Fe imit as Fe ge Respirable frac	kday. ilation. Provide ype List: MX OEL MX OEL ction. ACGIH
Exposure limit(s)         Components       Value         Iron oxide       5 mg/m3       Ti         10 mg/m3       Sho         5 mg/m3       Ti         Titanium dioxide       10 mg/m3       Ti         15 mg/m3       20 mg/m3       Sho	Exposure time me Weighted Avera (TWA): rt Term Exposure Li (STEL): me Weighted Avera (TWA): me Weighted Avera (TWA): PEL:	Exposure ty ge as Fe imit as Fe ge Respirable frac	ype List: MX OEL MX OEL ction. ACGIH
ComponentsValueIron oxide5 mg/m3Ti10 mg/m3Sho5 mg/m3TiTitanium dioxide10 mg/m3Ti15 mg/m320 mg/m3Sho	me Weighted Avera (TWA): rt Term Exposure Li (STEL): me Weighted Avera (TWA): me Weighted Avera (TWA): PEL:	ge as Fe imit as Fe ge Respirable frac	MX OEL MX OEL ction. ACGIH
Iron oxide5 mg/m3Ti10 mg/m3Sho5 mg/m3TiTitanium dioxide10 mg/m315 mg/m320 mg/m3Sho	me Weighted Avera (TWA): rt Term Exposure Li (STEL): me Weighted Avera (TWA): me Weighted Avera (TWA): PEL:	ge as Fe imit as Fe ge Respirable frac	MX OEL MX OEL ction. ACGIH
10 mg/m3Sho10 mg/m3Sho5 mg/m3TiTitanium dioxide10 mg/m315 mg/m320 mg/m3Sho	(TWA): rt Term Exposure Li (STEL): me Weighted Avera (TWA): me Weighted Avera (TWA): PEL:	imit as Fe ge Respirable frac	Ction. ACGIH
5 mg/m3TiTitanium dioxide10 mg/m3Ti15 mg/m320 mg/m3Sho	(STEL): me Weighted Avera (TWA): me Weighted Avera (TWA): PEL:	ge Respirable fra	ction. ACGIH
Titanium dioxide     10 mg/m3     Ti       15 mg/m3     20 mg/m3     Shote	me Weighted Avera (TWA): me Weighted Avera (TWA): PEL:	-	
15 mg/m3 20 mg/m3 Sho	me Weighted Avera (TWA): PEL:	ge	ACGIH
20 mg/m3 Sho	PEL:		neom
20 mg/m3 Sho	rt Term Exposure Li	Total dust	t. OSHA Z1
9 PHVSICAI	(STEL):	imit as Ti	MX OEL
).THISICAL	AND CHEMICAL	PROPERTIES	
Form: SolidAppearance: PelletsColor: BROWNOdor: Very faintMelting point/range: Not deternBoiling Point:: Not applidWater solubility: Insoluble	Sj B v v nined V	vaporation rate pecific Gravity: ulk density apor pressure apour density H	<ul> <li>Not applicable</li> <li>Not determined</li> <li>Not established</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> </ul>
10. STAE	BILITY AND REA	CTIVITY	
Stability : Stable			



## MATERIAL SAFETY DATA SHEET Honey 4655c

Version Number 1.1 Revision Date 12/01/2006

Page 4 of 6 Print Date 11/25/2011

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	:	No data available



# MATERIAL SAFETY DATA SHEET Honey 4655c

Version Number 1.1 Revision Date 12/01/2006 Page 5 of 6 Print Date 11/25/2011

	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	as Substances (40 CFR 302)
Not applicable	
California Propositior 65	: Not applicable
SARA Title III Section 302 E	extremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regular
SARA Title III Section 313 T	oxic Chemicals:

PolyOne.

Page 6 of 6

## POLYONE CORPORATION

Version Number 1.1

### **MATERIAL SAFETY DATA SHEET** Honey 4655c

Unless specific chemicals are id	lenti	ified under this se	ection this	s product	is Not Ar	nlicable	under this re	011
Chemical Name			Jouron, uns	CAS-N		Weight		5u
ZINC COMPOUNDS				12063-1		5.00 -		
Canadian Regulations:	ise I	nventory (NPRI)					_	_
Chemical Name			CAS-N		Weigh		NPRI ID#	
Aluminum oxide			1344-28		0.10 -		13	-
Zinc iron oxide			12063-	19-3	5.00 -	10.00	231	
WHMIS Classification	:	Not controlled. All component Substances List	ts of this p			Canadian	Domestic	
	:	All component	ts of this p			Canadian	Domestic	
DSL	:	All component	ts of this p			Canadian	n Domestic	
DSL National Inventories:	:	All component Substances List	ts of this p			Canadian	Domestic	
DSL National Inventories: Australia AICS	:	All component Substances List Listed	ts of this p			Canadian	a Domestic	
DSL National Inventories: Australia AICS China IECS	: : : : :	All component Substances List Listed Listed	ts of this p t (DSL) or			Canadian	1 Domestic	
DSL National Inventories: Australia AICS China IECS Europe EINECS	: : : : : :	All component Substances List Listed Listed Listed	ts of this p t (DSL) or			Canadian	Domestic	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.