### MATERIAL SAFETY DATA SHEET UV DARK BLUE

Version Number 1.1 Revision Date 10/26/2006 Page 1 of 6 Print Date 11/25/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	UV DARK BLUE
Product code	:	CC10088956
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous, precipitated and gel	112926-00-8	1 - 5
Titanium dioxide	13463-67-7	1 - 5

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	<ul><li>Resin particles, like other inert materials, can be mechanically irritating.</li><li>May be harmful if swallowed.</li></ul>
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



# MATERIAL SAFETY DATA SHEET **UV DARK BLUE**

Version Number 1.1 Revision Date 10/26/2006 Page 2 of 6 Print Date 11/25/2011

	4. FIRST AID MEASURES			
Inhalation	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	: Wash off with soap and plenty of water. If skin irritation persists s medical attention.	eeł		
	5. FIRE-FIGHTING MEASURES			
Flash point	: Not applicable			
Flammable Limits				
Upper explosion limit	: Not applicable			
Lower explosion limit	: Not applicable			
Autoignition temperature	: Not applicable			
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.			
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.	ve		
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.			
	5. ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	: Should not be released into the environment. The product should be allowed to enter drains, water courses or the soil.	not		
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.			
	7. HANDLING AND STORAGE			
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.	ıt		
Storage	: Keep containers dry and tightly closed to avoid moisture absorptio	n		

PolyOne.

# MATERIAL SAFETY DATA SHEET **UV DARK BLUE**

Version Number 1.1 Revision Date 10/26/2006

\_

Page 3 of 6 Print Date 11/25/2011

8. H	XPOSURE	CONTROLS / PERSONAL	PROTECTION				
Respiratory protection		No personal respiratory protect		ly required.			
Eye/Face Protection		Safety glasses with side-shields.					
Hand protection							
-		Protective gloves.					
Skin and body protection	: 1	long sleeved clothing.					
Additional Protective Measures	: 5	Safety shoes.					
General Hygiene Considerations		Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.					
Engineering measures		Heat only in areas with appropr ppropriate exhaust ventilation		on. Provide			
Exposure limit(s) Components	Value	Exposure time	Exposure type	List:			
Silica, amorphous,	5 mg/m3	PEL:	Respirable fraction				
precipitated and gel	5 mg/m5	I DL.	Respirable fraction	I. USIIA ZI			
F	15 mg/m3	PEL:	Total dust.	OSHA Z1			
	0.8 mg/m3	Time Weighted Average (TWA):		Z3			
	10 mg/m3	Time Weighted Average		MX OEL			
	10 mg/m3	(TWA):					
Titanium dioxide	10 mg/m3	(TWA): Time Weighted Average (TWA):		ACGIH			
Titanium dioxide	10 mg/m3		Total dust.	ACGIH OSHA Z1			
Titanium dioxide	-	Time Weighted Average (TWA):	Total dust. as Ti				
Titanium dioxide	10 mg/m3 15 mg/m3 20 mg/m3	Time Weighted Average (TWA): PEL: Short Term Exposure Limit	as Ti	OSHA Z1			
	10 mg/m3 15 mg/m3 20 mg/m3 9. PHYSI	Time Weighted Average (TWA): PEL: Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	as Ti DPERTIES	OSHA Z1 MX OEL			
Form	10 mg/m3 15 mg/m3 20 mg/m3 9. PHYSI : Solid	Time Weighted Average (TWA): PEL: Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR( d Evapo	as Ti DPERTIES ration rate : N	OSHA Z1 MX OEL			
Form Appearance	10 mg/m3 15 mg/m3 20 mg/m3 9. PHYSI : Soli : Pello	Time Weighted Average (TWA): PEL: Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR( d Evapo ets Specif	as Ti DPERTIES ration rate : N ic Gravity: : N	OSHA Z1 MX OEL			
Form Appearance Color	10 mg/m3 15 mg/m3 20 mg/m3 9. PHYSI : Soli : Pella : BLU	Time Weighted Average (TWA): PEL: Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo ets Specif JE Bulk of	as Ti DPERTIES ration rate : M ic Gravity: : M lensity : M	OSHA Z1 MX OEL			
Form Appearance Color Odor	10 mg/m3 15 mg/m3 20 mg/m3 9. PHYSI : Soli : Pelle : BLU : Very	Time Weighted Average (TWA): PEL: Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo ets Specif JE Bulk o y faint Vapor	as Ti DPERTIES ration rate : M ic Gravity: : M lensity : M pressure : M	OSHA Z1         MX OEL         Not applicable         Not determined         Not established         Not applicable			
Form Appearance Color Odor Melting point/range	10 mg/m3 15 mg/m3 20 mg/m3 9. PHYSI : Solic : Pello : BLU : Very : Not	Time Weighted Average (TWA):         PEL:         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRO         d       Evapo         ets       Specif         JE       Bulk of Vapor         determined       Vapor	as Ti DPERTIES ration rate : 1 Tic Gravity: : 1 lensity : 1 pressure : 1 ur density : 1	OSHA Z1 MX OEL Not applicable Not determined Not established Not applicable Not applicable			
Form Appearance Color Odor	10 mg/m3 15 mg/m3 20 mg/m3 9. PHYSI : Solic : Pello : BLU : Very : Not	Time Weighted Average (TWA):         PEL:         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRO         d       Evapoo         ets       Specif         JE       Bulk o         y faint       Vapoo         applicable       pH	as Ti DPERTIES ration rate : 1 Tic Gravity: : 1 lensity : 1 pressure : 1 ur density : 1	OSHA Z1         MX OEL         Not applicable         Not determined         Not established         Not applicable			

# MATERIAL SAFETY DATA SHEET UV DARK BLUE

Version Number 1.1 Revision Date 10/26/2006 Page 4 of 6 Print Date 11/25/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
112926-00-8	Silica, amorphous,	Irritant	Respiratory system, Eyes.
	precipitated and gel		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

#### Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.

**POLYONE CORPORATION** 



# MATERIAL SAFETY DATA SHEET **UV DARK BLUE**

Version Number 1.1 Revision Date 10/26/2006 Page 5 of 6 Print Date 11/25/2011

	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSC. Inventory.
US. EPA CERCLA Hazardo	as Substances (40 CFR 302)
Not applicable	
California Proposition 65	n : Not applicable
SARA Title III Section 302 I	Extremely Hazardous Substance
TT 1 · C 1 · 1	identified under this section, this product is Not Applicable under this regul

PolyOne

## MATERIAL SAFETY DATA SHEET UV DARK BLUE

Version Number 1.1 Revision Date 10/26/2006 Page 6 of 6 Print Date 11/25/2011

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

Chemical Name			CAS-No.	Weight %	NPRI ID#		
Phthalocyanine blue			147-14-8	1.00 - 5.00	71		
WHMIS Classificatio WHMIS Ingredient D		2-2					
CAS-No. 147-14-8							
DSL	:	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.					
ational Inventories:							
Australia AICS	:	Listed					
China IECS	:	Listed					
Europe EINECS	:	Listed					
Japan ENCS	:	Not determined	d				
Korea KECI	:	Listed					
Philippines PICCS	:	Listed					

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.