### MATERIAL SAFETY DATA SHEET COOL GRAY 10C TPE

Version Number 1.0 Revision Date 10/03/2006

Page 1 of 6 Print Date 11/24/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	COOL GRAY 10C TPE
Product code :	CC10091712
Chemical Name :	Mixture
CAS-No.	Mixture
Product Use :	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	5 - 10
Titanium dioxide	13463-67-7	5 - 10

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>
Skin Chronic exposure	<ul> <li>Experience shows no unusual dermatitis hazard from routine handling.</li> <li>Refer to Section 11 for Toxicological Information.</li> </ul>
Medical Conditions Aggravated by Exposure:	: None known.



# MATERIAL SAFETY DATA SHEET COOL GRAY 10C TPE

Version Number 1.0 Revision Date 10/03/2006 Page 2 of 6 Print Date 11/24/2011

Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists se medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foamnone.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOr), other barenders metainly and small metainly.</li> </ul>
	(NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

PolyOne.

# MATERIAL SAFETY DATA SHEET COOL GRAY 10C TPE

Version Number 1.0 Revision Date 10/03/2006

\_\_\_\_

\_

\_

Page 3 of 6 Print Date 11/24/2011

	a	nd contamination. Keep in	n a dry, cool place.		
8. I	EXPOSURE	CONTROLS / PERSON	AL PROTECTION		
Respiratory protection	: N	lo personal respiratory prot	tective equipment not	rmally r	equired.
Eye/Face Protection	: S	afety glasses with side-shi	elds.		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		landle in accordance with g Vash hands before breaks a			afety practice.
Engineering measures		leat only in areas with appr ppropriate exhaust ventilat		lation.	Provide
Exposure limit(s)					
Components	Value	Exposure time	Exposure ty	pe	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable frac	ction.	OSHA Z1
	15 mg/m3	PEL:	Total dust		OSHA Z1
	10 mg/m3	Time Weighted Averag (TWA):	ge		MX OEL
	20 mg/m3	Short Term Exposure Lir (STEL):	mit		MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Averag (TWA):	ie.		ACGIH
	15 mg/m3	PEL:	Total dust		OSHA Z1
	20 mg/m3	Short Term Exposure Lir (STEL):	mit as Ti		MX OEL
	9. PHYSIC	CAL AND CHEMICAL I	PROPERTIES		
Form Appearance	: Solic : Pelle		aporation rate ecific Gravity:		applicable determined
Color	: GRE		ilk density		established
Odor	: Very	r faint Va	apor pressure	: Not	applicable
M. 1			pour density		applicable
Melting point/range	. Not	applicable pH	I	: Not	applicable
Boiling Point/range Water solubility	: Insol				
Boiling Point:	: Insol		TIVITY		

## MATERIAL SAFETY DATA SHEET COOL GRAY 10C TPE

Version Number 1.0 Revision Date 10/03/2006 Page 4 of 6 Print Date 11/24/2011

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.



## MATERIAL SAFETY DATA SHEET COOL GRAY 10C TPE

Version Number 1.0 Revision Date 10/03/2006 Page 5 of 6 Print Date 11/24/2011

Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	us Substances (40 CFR 302)
Not applicable	
California Proposition 65	n : Not applicable
SARA Title III Section 302 E Not applicable	Extremely Hazardous Substance
SARA Title III Section 313 1	Toxic Chemicals:
Not applicable	
	5/6

PolyOne.

## MATERIAL SAFETY DATA SHEET COOL GRAY 10C TPE

Version Number 1.0 Revision Date 10/03/2006 Page 6 of 6 Print Date 11/24/2011

Canadian Regulations:

Chemical Name			CAS-No.	Weight %	NPRI ID#
Aluminum oxide			1344-28-1	0.10 - 1.00	13
Zinc ferrite brown spinel (C.I. 119)	. Piş	gment Yellow	68187-51-9	0.10 - 1.00	231
WHMIS Classification	:	Not controlled.			
DSL	:		s of this product a (DSL) or are exer	re on the Canadia mpt.	n Domestic
tional Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined			
Korea KECI	:	Listed			
Philippines PICCS		Listed			

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.