PolvOne

MATERIAL SAFETY DATA SHEET 030TN2005 SPECIALTY TAN

Version Number 1.1 Revision Date 01/26/2007

Page 1 of 7 Print Date 11/26/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	030TN2005 SPECIALTY TAN
Product code	:	CC10092290
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	•	Industrial Applications

: Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Aluminate (Al(OH)63-), (OC-6-11)-, magnesium carbonate hydroxide (2:6:1:4)	11097-59-9	1 - 5
Iron oxide	1309-37-1	5 - 10
Titanium dioxide	13463-67-7	5 - 10
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET 030TN2005 SPECIALTY TAN

Version Number 1.1 Revision Date 01/26/2007 Page 2 of 7 Print Date 11/26/2011

Medical Conditions : None known. Aggravated by Exposure:				
	4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.			
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.			
	5. FIRE-FIGHTING MEASURES			
Flash point	: Not applicable			
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive 			
Procedures Unusual Fire/Explosion Hazards	 pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. 			
	6. ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.			
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.			

PolyOne.

MATERIAL SAFETY DATA SHEET 030TN2005 SPECIALTY TAN

Version Number 1.1 Revision Date 01/26/2007 Page 3 of 7 Print Date 11/26/2011

Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 030TN2005 SPECIALTY TAN

Version Number 1.1 Revision Date 01/26/2007

Water solubility

Page 4 of 7 Print Date 11/26/2011

Components	Value	Exposure time		Exposure type	List:
Aluminate (Al(OH)63-),	2 mg/m3	Time Weighted Avera (TWA):	age	as Al	ACGIH
(OC-6-11)-,					
magnesium carbonate					
hydroxide (2:6:1:4)					
Calcium carbonate	5 mg/m3	PEL:		Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:		Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Avera (TWA):	age		MX OEL
	20 mg/m3	Short Term Exposure I (STEL):	Limit		MX OEL
Iron oxide	5 mg/m3	Time Weighted Average (TWA):		as Fe	MX OEL
	10 mg/m3	Short Term Exposure I (STEL):	Limit	as Fe	MX OEL
	5 mg/m3	Time Weighted Avera (TWA):	age	Respirable fraction.	ACGIH
Titanium dioxide	10 mg/m3	Time Weighted Avera (TWA):	age		ACGIH
	15 mg/m3	PEL:		Total dust.	OSHA Z1
	20 mg/m3	Short Term Exposure I (STEL):	Limit	as Ti	MX OEL
				DED/DIEG	
	9. PH 1510	CAL AND CHEMICAI		FERTIES	
Form	: Solic	1 I	Evapora	ation rate : Not	applicable
Appearance	: Pelle				determined
Color	: TAN		Bulk de		established
Ddor	: Very			•	applicable
Melting point/range	: Not				applicable
Boiling Point:	: Not a	applicable p	ρΗ	: Not	applicable
	. .				-

: Insoluble 10. STABILITY AND REACTIVITY

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.

MATERIAL SAFETY DATA SHEET 030TN2005 SPECIALTY TAN

Version Number 1.1 Revision Date 01/26/2007 Page 5 of 7 Print Date 11/26/2011

Hazardous decomposition products

 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
11097-59-9	Aluminate (Al(OH)63-),	Irritant	Eyes, Skin.
	(OC-6-11)-, magnesium		
	carbonate hydroxide		
	(2:6:1:4)		
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the

PolyOne.

MATERIAL SAFETY DATA SHEET 030TN2005 SPECIALTY TAN

Version Number 1.1 Revision Date 01/26/2007 Page 6 of 7 Print Date 11/26/2011

Additional advice	: No data available	
Additional advice		
	13. DISPOSAL CONSIDERATIONS	
Product	: Like most thermoplastic plastics the product can be recycled. Whe possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	re
Contaminated packaging	: Recycling is preferred when possible. The generator of waste mate has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincia and local regulations.	ı
	14. TRANSPORT INFORMATION	
U.S. DOT Classification	: Not regulated for transportation.	
ICAO/IATA (air)	: Refer to specific regulation.	
IMO / IMDG (maritime)	: Refer to specific regulation.	
	15. REGULATORY INFORMATION	
US Regulations:		
OSHA Status	: Classified as hazardous based on components.	
TSCA Status	: All components of this product are listed on or exempt from the TS Inventory.	CA
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)	
Not applicable		
California Proposition 65	n : Not applicable	
SARA Title III Section 302 B	Extremely Hazardous Substance	
Unlace encoifie chemicals and	identified under this section, this product is Not Applicable under this reg	1.

MATERIAL SAFETY DATA SHEET 030TN2005 SPECIALTY TAN

Version Number 1.1 Revision Date 01/26/2007 Page 7 of 7 Print Date 11/26/2011

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight %
ZINC COMPOUNDS	12063-19-3	10.00 - 30.00
ZINC COMPOUNDS	557-05-1	0.10 - 1.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Zinc iron oxide	12063-19-3	10.00 - 30.00	231
Zinc stearate	557-05-1	0.10 - 1.00	231

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

:

CAS-No.
11097-59-9
1309-37-1

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Listed
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Listed
Philippines PICCS	: Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.