## MATERIAL SAFETY DATA SHEET STONE BROWN

Version Number 1.2 Revision Date 11/09/2006

CAS-No.

Product Use

Page 1 of 8 Print Date 11/25/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	STONE BROWN
Product code	:	CC10092711
Chemical Name	•	Mixture

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

**Industrial Applications** 

: Mixture

:

Components	CAS-No.	Weight %
Formamide,	124172-53-8	5 - 10
N,N'-1,6-hexanediylbis[N-(2,2,6,6-tetrameth		
yl-4-piperidinyl)-		
Aluminum	7429-90-5	1 - 5
Iron oxide	1309-37-1	1 - 5
Rutile, antimony chromium buff	68186-90-3	1 - 5
Cellulose	9004-34-6	5 - 10
Titanium dioxide	13463-67-7	5 - 10

### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>



# MATERIAL SAFETY DATA SHEET **STONE BROWN**

ion Number 1.2 sion Date 11/09/2006	Page 2 Print Date 11/25/2
Skin	: Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit Autoignition temperature	<ul><li>Not applicable</li><li>Not applicable</li></ul>
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne
Unusual Fire/Explosion Hazards	<ul> <li>contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.

**POLYONE CORPORATION** 

PolyOne.

# MATERIAL SAFETY DATA SHEET **STONE BROWN**

Version Number 1.2 Revision Date 11/09/2006 Page 3 of 8 Print Date 11/25/2011

Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXF	POSUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne

## MATERIAL SAFETY DATA SHEET **STONE BROWN**

Version Number 1.2 Revision Date 11/09/2006 Page 4 of 8 Print Date 11/25/2011

Components	Value	Exposure time	Exposure type	List:
Aluminum	10 mg/m3	Time Weighted Average (TWA):	Dust.	ACGIH
	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Dust.	MX OEL
Cellulose	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Iron oxide	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Rutile, antimony chromium buff	0.5 mg/m3	Time Weighted Average (TWA):	as Cr	ACGIH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
  Pellets
  BROWN
  Very faint
  Not determined
  Not applicable
  Insoluble
- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- : Not applicable
- : Not determined
- : Not established
- : Not applicable
- : Not applicable
- : Not applicable

#### **10. STABILITY AND REACTIVITY**

Stability

: Stable.

## MATERIAL SAFETY DATA SHEET **STONE BROWN**

Version Number 1.2 Page 5 of 8 Print Date 11/25/2011 Revision Date 11/09/2006 Hazardous Polymerization : Will not occur. Conditions to avoid Keep away from oxidizing agents and open flame. To avoid thermal : decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen Hazardous decomposition : products (NOx), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
124172-53-8	Formamide,	Irritant	Eyes.
	N,N'-1,6-hexanediylbis[N-		
	(2,2,6,6-tetramethyl-4-pipe		
	ridinyl)-		
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory system.
	chromium buff		
9004-34-6	Cellulose	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
124172-53-8	Formamide,	LC50	> 5.0 mg/l	rat
	N,N'-1,6-hexanediylbis[N-	Oral LD50	> 2,000 mg/kg	rat
	(2,2,6,6-tetramethyl-4-pipe			
	ridinyl)-			
9004-34-6	Cellulose	LC50	> 5800 mg/m3	rat
		Oral LD50	> 5 gm/kg	rat
		Dermal LD50	> 2  gm/kg	rabbit

#### Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

PolyOne

## MATERIAL SAFETY DATA SHEET **STONE BROWN**

Version Number 1.2 Revision Date 11/09/2006

Page 6 of 8 Print Date 11/25/2011

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

 $2\mathbf{B}$  - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

12. ECOLOGICAL INFORMATION

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION

PolyOne.

# MATERIAL SAFETY DATA SHEET **STONE BROWN**

on Number 1.2 ion Date 11/09/2006				Prir	nt Date	11/25/
JS Regulations:						
OSHA Status : Classified as ha	azardous ba	ased on co	mponents	•		
TSCA Status : All componen Inventory.	ts of this pr	oduct are l	listed on o	r exem	pt from tl	he TSC
S. EPA CERCLA Hazardous Substances (40 CFR	302)					
Not applicable						
California Proposition : Not applicable 65						
ARA Title III Section 302 Extremely Hazardous S	ubstance					
Inless specific chemicals are identified under this s	ection, this	product is	s Not App	licable	under th	is regul
Unless specific chemicals are identified under this se	ection, this	product is	s Not App	licable	under th	is regul
Inless specific chemicals are identified under this s	ection, this	product is	s Not App	licable	under th	is regul
	ection, this	product is	s Not App	licable	under th	is regul
ARA Title III Section 313 Toxic Chemicals:		-				-
ARA Title III Section 313 Toxic Chemicals:		product is	s Not App	licable	under th	-
ARA Title III Section 313 Toxic Chemicals: Inless specific chemicals are identified under this section Chemical Name		product is CAS-No.	s Not App	<u>licable</u> Weight	under th	-
ARA Title III Section 313 Toxic Chemicals:		product is	s Not App  5	licable	under th 2 % 5.00	-
ARA Title III Section 313 Toxic Chemicals: Inless specific chemicals are identified under this section Chemical Name ALUMINUM (FUME OR DUST)		product is CAS-No. 7429-90-5	s Not App  5	licable Weight 1.00 -	under th 2 % 5.00	-
ARA Title III Section 313 Toxic Chemicals: Inless specific chemicals are identified under this section Chemical Name ALUMINUM (FUME OR DUST) CHROMIUM III COMPOUNDSANTIMONY COMPOUNDS		product is CAS-No. 7429-90-5	s Not App  5	licable Weight 1.00 -	under th 2 % 5.00	-
ARA Title III Section 313 Toxic Chemicals: Inless specific chemicals are identified under this section Chemical Name ALUMINUM (FUME OR DUST) CHROMIUM III COMPOUNDSANTIMONY COMPOUNDS		product is CAS-No. 7429-90-5	s Not App  5	licable Weight 1.00 -	under th 2 % 5.00	-
ARA Title III Section 313 Toxic Chemicals: Inless specific chemicals are identified under this section of the chemical Name ALUMINUM (FUME OR DUST) CHROMIUM III COMPOUNDSANTIMONY COMPOUNDS	ection, this	product is CAS-No. 7429-90-5	s Not App  5	licable Weight 1.00 -	under th 2 % 5.00	-
ARA Title III Section 313 Toxic Chemicals: Inless specific chemicals are identified under this section Chemical Name ALUMINUM (FUME OR DUST) CHROMIUM III COMPOUNDSANTIMONY COMPOUNDS Compounds Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name	ection, this	product is CAS-No. 7429-90-5 68186-90-	S Not App	licable Weight 1.00 - 1.00 -	<u>under th</u> 5.00 5.00	is regul
ARA Title III Section 313 Toxic Chemicals: Unless specific chemicals are identified under this section Chemical Name ALUMINUM (FUME OR DUST) CHROMIUM III COMPOUNDSANTIMONY COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name Aluminum	CAS-No 7429-90	product is CAS-No. 7429-90-5 68186-90- 68186-90- 0.	8 Not App 5 -3 Weight 1.00 - 5.	licable Weight 1.00 - 1.00 - % 00	under th 5.00 5.00 NPRI I 12	is regul
ARA Title III Section 313 Toxic Chemicals: Unless specific chemicals are identified under this section Chemical Name ALUMINUM (FUME OR DUST) CHROMIUM III COMPOUNDSANTIMONY COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name	ection, this	product is CAS-No. 7429-90-5 68186-90- 68186-90- 0.	8 Not App 5 -3 Weight 1.00 - 5. 1.00 - 5.	licable Weight 1.00 - 1.00 - % 00 00 00	under th 5.00 5.00 NPRI I 12 69	is regul
ARA Title III Section 313 Toxic Chemicals: Unless specific chemicals are identified under this section Chemical Name ALUMINUM (FUME OR DUST) CHROMIUM III COMPOUNDSANTIMONY COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name Aluminum	CAS-No 7429-90	product is CAS-No. 7429-90-5 68186-90- 68186-90- 0.	8 Not App 5 -3 Weight 1.00 - 5.	licable Weight 1.00 - 1.00 - % 00 00 00	under th 5.00 5.00 NPRI I 12	is regul
ARA Title III Section 313 Toxic Chemicals: Unless specific chemicals are identified under this section Chemical Name ALUMINUM (FUME OR DUST) CHROMIUM III COMPOUNDSANTIMONY COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name Aluminum	CAS-No 7429-90	product is CAS-No. 7429-90-5 68186-90- 68186-90- 0.	8 Not App 5 -3 Weight 1.00 - 5. 1.00 - 5.	licable Weight 1.00 - 1.00 - % 00 00 00	under th 5.00 5.00 NPRI I 12 69	is regul
ARA Title III Section 313 Toxic Chemicals: Inless specific chemicals are identified under this section of the content of the section of the	CAS-No 7429-90	product is CAS-No. 7429-90-5 68186-90- 68186-90- 0.	8 Not App 5 -3 Weight 1.00 - 5. 1.00 - 5.	licable Weight 1.00 - 1.00 - % 00 00 00	under th 5.00 5.00 NPRI I 12 69	is regul
ARA Title III Section 313 Toxic Chemicals: Inless specific chemicals are identified under this section Chemical Name ALUMINUM (FUME OR DUST) CHROMIUM III COMPOUNDSANTIMONY COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name Aluminum	CAS-No 7429-90	product is CAS-No. 7429-90-5 68186-90- 68186-90- 0.	8 Not App 5 -3 Weight 1.00 - 5. 1.00 - 5.	licable Weight 1.00 - 1.00 - % 00 00 00	under th 5.00 5.00 NPRI I 12 69	is regul
ARA Title III Section 313 Toxic Chemicals: Inless specific chemicals are identified under this section of the content of the section of the	CAS-No 7429-90	product is CAS-No. 7429-90-5 68186-90- 68186-90- 0.	8 Not App 5 -3 Weight 1.00 - 5. 1.00 - 5.	licable Weight 1.00 - 1.00 - % 00 00 00	under th 5.00 5.00 NPRI I 12 69	is regul
ARA Title III Section 313 Toxic Chemicals: Inless specific chemicals are identified under this section of the content of the	CAS-No 7429-90	product is CAS-No. 7429-90-5 68186-90- 68186-90- 0.	8 Not App 5 -3 Weight 1.00 - 5. 1.00 - 5.	licable Weight 1.00 - 1.00 - % 00 00 00	under th 5.00 5.00 NPRI I 12 69	is regul
ARA Title III Section 313 Toxic Chemicals: Jaless specific chemicals are identified under this section of the chemical Name ALUMINUM (FUME OR DUST) CHROMIUM III COMPOUNDSANTIMONY COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name Aluminum Rutile, antimony chromium buff WHMIS Classification : D2B WHMIS Ingredient Disclosure List CAS-No.	CAS-No 7429-90	product is CAS-No. 7429-90-5 68186-90- 68186-90- 0.	8 Not App 5 -3 Weight 1.00 - 5. 1.00 - 5.	licable Weight 1.00 - 1.00 - % 00 00 00	under th 5.00 5.00 NPRI I 12 69	is regul
ARA Title III Section 313 Toxic Chemicals: Inless specific chemicals are identified under this section of the content of the	CAS-No 7429-90	product is CAS-No. 7429-90-5 68186-90- 68186-90- 0.	8 Not App 5 -3 Weight 1.00 - 5. 1.00 - 5.	licable Weight 1.00 - 1.00 - % 00 00 00	under th 5.00 5.00 NPRI I 12 69	is regul

P<u>olyOne</u>

## MATERIAL SAFETY DATA SHEET STONE BROWN

Version Number 1.2 Revision Date 11/09/2006		Page 8 of 8 11/25/2011
68186-90-3 DSL	All of the components of this product are listed on the Canad Inventories or are exempt. However, at least one component of product is on the Canadian Non-Domestic Substances List (N Quantity use in Canada is restricted by regulations.	of this
National Inventories:		
Australia AICS	Listed	
China IECS	Listed	
Europe EINECS	Not determined	
Japan ENCS	Not determined	
Korea KECI	Listed	
Philippines PICCS	Listed	
16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.