MATERIAL SAFETY DATA SHEET **DARK GRAY 2**

Version Number 1.1 Revision Date 12/01/2006

Product Use

Page 1 of 7 Print Date 11/25/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DARK GRAY 2
Product code	:	CC10093342
Chemical Name	:	Mixture
CAS-No.	:	Mixture

: Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products	70624-18-9	1 - 5
Carbon black	1333-86-4	1 - 5
Iron oxide	1309-37-1	1 - 5
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to
	eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

1/7

PolyOne.

MATERIAL SAFETY DATA SHEET **DARK GRAY 2**

Version Number 1.1 Revision Date 12/01/2006 Page 2 of 7 Print Date 11/25/2011

Medical Conditions		None known.		
Aggravated by Exposure:				
		4. FIRST AID MEASURES		
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.		
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.		
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.		
		5. FIRE-FIGHTING MEASURES		
Flash point	:	Not applicable		
Flammable Limits				
Upper explosion limit	:	Not applicable		
Lower explosion limit	:	Not applicable		
Autoignition temperature Suitable extinguishing media	:	Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.		
Special Fire Fighting		Fullface self-contained breathing apparatus (SCBA) used in positive		
Procedures	•	pressure mode should be worn to prevent inhalation of airborne		
Unuquel Fire/Explasion		contaminants.		
Unusual Fire/Explosion Hazards	·	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.		
	6. A	CCIDENTAL RELEASE MEASURES		
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.		
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.		
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.		

PolyOne.

MATERIAL SAFETY DATA SHEET **DARK GRAY 2**

Version Number 1.1 Revision Date 12/01/2006 Page 3 of 7 Print Date 11/25/2011

		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXF	POSUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):	Total dust. as carbon black	ACGIH
	3.5 mg/m3	PEL:	Total dust. as carbon black	OSHA Z1
Iron oxide	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES



MATERIAL SAFETY DATA SHEET **DARK GRAY 2**

Version Number 1.1 Revision Date 12/01/2006			Page 4 of 7 Print Date 11/25/2011
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	 Solid Pellets GREY Very faint Not determined Not applicable Insoluble 	Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH	Not determinedNot establishedNot applicable
	10. STABILITY AN	D REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from o decomposition, do	xidizing agents and open fl not overheat.	ame. To avoid thermal
Incompatible Materials	: Incompatible with	strong acids and oxidizing	agents.
Hazardous decomposition products		O2), carbon monoxide (CC rdous materials, and smoke	· · · · · · · · · · · · · · · · · · ·

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine,	Irritant	Eyes, Skin, Respiratory system.
	N,N'-bis(2,2,6,6-tetrameth		
	yl-4-piperidinyl)-,polymer		
	with		
	2,4,6-trichloro-1,3,5-triazi		
	ne, reaction products		
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No. Chemical Name Route Value Species

PolvOne

MATERIAL SAFETY DATA SHEET **DARK GRAY 2**

Version Number 1.1 Revision Date 12/01/2006

Page 5 of 7 Print Date 11/25/2011

70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products	Oral LD50 Dermal LD50	> 2,000 mg/kg > 3,000 mg/kg	rat rat
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	:	No data available



MATERIAL SAFETY DATA SHEET **DARK GRAY 2**

Version Number 1.1 Revision Date 12/01/2006 Page 6 of 7 Print Date 11/25/2011

	13. DISPOSAL CONSIDERATIONS		
Product Contaminated packaging	 Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal. 		
Contaminated packaging			
	14. TRANSPORT INFORMATION		
U.S. DOT Classification	: Not regulated for transportation.		
ICAO/IATA (air)	: Refer to specific regulation.		
IMO / IMDG (maritime)	: Refer to specific regulation.		
	15. REGULATORY INFORMATION		
US Regulations:			
OSHA Status	: Classified as hazardous based on components.		
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.		
US. EPA CERCLA Hazardou	us Substances (40 CFR 302)		
Not applicable			
California Propositior 65	n : Not applicable		
SARA Title III Section 302 E	Extremely Hazardous Substance		
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulat		

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **DARK GRAY 2**

	Pri	Page 7 of nt Date 11/25/20
s product is CAS-No. 12063-19-	Weigh	
0.	Weight %	NPRI ID#
63-19-3 1.00 - 5.00 231		231
roduct are o are exempt	on the Canadian t.	1 Domestic
Listed		
Listed		
Not determined		
ļ	ATION	ATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.