PolvOne.

MATERIAL SAFETY DATA SHEET

727 Burnt Umber

Version Number 1.0 Revision Date 11/07/2006 Page 1 of 7 Print Date 11/25/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	727 Burnt Umber
Product code	:	CC10093486
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Chromium (III) oxide	1308-38-9	1 - 5
Zinc stearate	557-05-1	5 - 10
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET

727 Burnt Umber

Version Number 1.0 Revision Date 11/07/2006 Page 2 of 7 Print Date 11/25/2011

Medical Conditions Aggravated by Exposure:	: None known.	
	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.	
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.	
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.	
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. 	
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in posi pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitroge (NOx), other hazardous materials, and smoke are all possible. M emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under conditions. 	
	6. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.	
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	



MATERIAL SAFETY DATA SHEET 727 Burnt Umber

Version Number 1.0 Revision Date 11/07/2006		Page 3 of 7 Print Date 11/25/2011
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXP	OSUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Chromium (III) oxide	0.5 mg/m3	Time Weighted Average (TWA):	as Cr	ACGIH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL
Zinc stearate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	as stearates	ACGIH
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color
- : Solid : Pellets : GREY

Bulk density

Evaporation rate : Not applicable Specific Gravity: : Not determined Pully density : Not actablished : Not established

MATERIAL SAFETY DATA SHEET **727 Burnt Umber**

Version Number	er 1.0
Revision Date	11/07/2006

_

Page 4 of 7 Print Date 11/25/2011

Odor Melting point/range Boiling Point: Water solubility	: Very faint: Not determined: Not applicable: Insoluble	Vapor pressure Vapour density pH	Not applicableNot applicableNot applicable
	10. STABILITY AN	D REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from or decomposition, do	xidizing agents and open not overheat.	flame. To avoid thermal
Incompatible Materials	acetal copolymers a processing. At pro destructive and inv mechanically clean quantities of these	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.	
Hazardous decomposition products	(NOx), hydrogen c smoke are all possi or more) above 392	2 °F (200 °C) or short terr roduct decomposition and	rdous materials, and approximately 30 minutes n heating at 482 °F (250

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1308-38-9	Chromium (III) oxide	Irritant	Eyes, Skin.
		sensitizer	Skin.
557-05-1	Zinc stearate	Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
557-05-1	Zinc stearate	Oral LD50	> 10 gm/kg	rat

Carcinogenicity

MATERIAL SAFETY DATA SHEET **727 Burnt Umber**

Version Number 1.0

Revision Date 11/07/2006

Page 5 of 7 Print Date 11/25/2011

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Chromium (III) oxide 1308-38-9 The bi- and trivalent forms of chrome have a low order of acute toxicity, but may cause skin sensitization and irritation to the eyes. No effects have been reported for chromium (III) oxide. Chromium (III) compounds are not considered carcinogenic in animals or humans.

available as they are bound within the
available as they are bound within the
ATIONS
astics the product can be recycled. Where red to disposal or incineration. The l has the responsibility for proper waste on and disposal in accordance with ovincial and local regulations. n possible. The generator of waste materia roper waste classification, transportation with applicable federal, state/provincial
IATION
ation.
ort

PolyOne.

MATERIAL SAFETY DATA SHEET **727** *Burnt Umber*

ersion Number 1.0 evision Date 11/07/2006					Prir	Pa nt Date 11	ige 6 of ′ /25/201
ICAO/IATA (air) :	Refer to spec	cific regulation	on.				
IMO / IMDG (maritime) :	Refer to spec	cific regulation	on.				
1	5. REGULAT	ORY INFO	RMATION	N			
US Regulations:							
OSHA Status :	Classified as	hazardous b	ased on coi	mponent	s.		
TSCA Status :	All componers Inventory.	ents of this p	oduct are li	isted on o	or exem	pt from the '	ГSCA
US. EPA CERCLA Hazardous Su	bstances (40 CI	FR 302)					
Not applicable							
California Proposition : 65	Not applicab	le					
SARA Title III Section 302 Extrer Unless specific chemicals are iden			product is	Not App	plicable	under this r	egulation
SARA Title III Section 313 Toxic Unless specific chemicals are iden Chemical Name ZINC COMPOUNDS		s section, this	product is CAS-No. 557-05-1	Not Ap	olicable Weight 5.00 -	%	egulatio
			557-05-1		5.00 -	10.00	
Canadian Regulations: National Pollutant Release	Inventory (NPF	RI)					
Chemical Name		CAS-N		Weight		NPRI ID#	
Aluminum oxide		1344-2		0.10 - 1		13	_
Chromium (III) oxide		1308-3		0.10 - 1		69	_
Zinc stearate WHMIS Classification :	D2B	557-05	-1	5.00 - 1	0.00	231	
WHMIS Ingredient Disclos	sure List						

PolyOne.

MATERIAL SAFETY DATA SHEET **727 Burnt Umber**

Version Number 1.0 Revision Date 11/07/2006

Page 7 of 7 Print Date 11/25/2011

urope EINECS apan ENCS orea KECI hilippines PICCS	: : :	Listed Listed Listed
apan ENCS	:	Listed
-		
urope EINECS	:	Listed
Interne EINECS		
hina IECS	:	Listed
ustralia AICS	:	Listed
Inventories:		
SL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
1308-38-9 557-05-1		
CAS-No.		
I I I	1308-38-9 557-05-1 SL inventories: ustralia AICS	1308-38-9 557-05-1 SL : inventories: ustralia AICS :

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.