MATERIAL SAFETY DATA SHEET

Light Metallic Silver

Version Number 1.1 Revision Date 11/20/2006 Page 1 of 6 Print Date 11/25/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	Light Metallic Silver
Product code	:	CC10094033
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Mica	12001-26-2	5 - 10
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET Light Metallic Silver

Version Number 1.1 Revision Date 11/20/2006 Page 2 of 6 Print Date 11/25/2011

Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	4	5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit		Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	:	Not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A(CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

PolyOne.

MATERIAL SAFETY DATA SHEET Light Metallic Silver

Version Number 1.1 Revision Date 11/20/2006

Page 3 of 6 Print Date 11/25/2011

ð. f	EXPOSURE	CONTROLS / PERSONA	L PROTECTION			
Respiratory protection	: N	: No personal respiratory protective equipment normally required.				
Eye/Face Protection	: S	: Safety glasses with side-shields.				
Hand protection	: P	: Protective gloves.				
Skin and body protection	: L	: Long sleeved clothing.				
Additional Protective Measures	: S	: Safety shoes.				
General Hygiene Considerations		Iandle in accordance with go Vash hands before breaks and				
Engineering measures		Ieat only in areas with appropriate exhaust ventilatio		ion. Provide		
Exposure limit(s)						
Components	Value	Exposure time	Exposure type	List:		
Mica	20 mppcf	PEL:	Total dust.	OSHA		
	3 mg/m3	Time Weighted Average (TWA):	Respirable fraction	on. ACGIH		
	3 mg/m3	Time Weighted Average (TWA):		MX OEL		
Titanium dioxide	3 mg/m3 10 mg/m3			ACGIH		
Titanium dioxide	10 mg/m3 15 mg/m3	(TWA): Time Weighted Average	Total dust.			
Titanium dioxide	10 mg/m3	(TWA): Time Weighted Average (TWA):		ACGIH		
Titanium dioxide	10 mg/m3 15 mg/m3 20 mg/m3	(TWA): Time Weighted Average (TWA): PEL: Short Term Exposure Limi	t as Ti	ACGIH OSHA Z1		
	10 mg/m3 15 mg/m3 20 mg/m3	(TWA): Time Weighted Average (TWA): PEL: Short Term Exposure Limi (STEL): CAL AND CHEMICAL PR	t as Ti	ACGIH OSHA Z1		
Gorm	10 mg/m3 15 mg/m3 20 mg/m3 9. PHYSI	(TWA): Time Weighted Average (TWA): PEL: Short Term Exposure Limi (STEL): CAL AND CHEMICAL PR d Evap	t as Ti ROPERTIES	ACGIH OSHA Z1 MX OEL		
⁷ orm Appearance	10 mg/m3 15 mg/m3 20 mg/m3 9. PHYSIC : Solid	(TWA): Time Weighted Average (TWA): PEL: Short Term Exposure Limi (STEL): CAL AND CHEMICAL PE d Evap ets Spec	t as Ti COPERTIES Poration rate :	ACGIH OSHA Z1 MX OEL Not applicable		
Form Appearance Color Odor	10 mg/m3 15 mg/m3 20 mg/m3 9. PHYSIO : Solid : Pelle : GRE : Very	(TWA): Time Weighted Average (TWA): PEL: Short Term Exposure Limi (STEL): CAL AND CHEMICAL PE d Evap ets Spec EY Bulk / faint Vapo	t as Ti COPERTIES Poration rate : ific Gravity: : density : or pressure :	ACGIH OSHA Z1 MX OEL Not applicable Not determined Not established Not applicable		
Form Appearance Color Odor Melting point/range	10 mg/m3 15 mg/m3 20 mg/m3 9. PHYSIO : Solid : Pelld : GRE : Very : Not	(TWA): Time Weighted Average (TWA): PEL: Short Term Exposure Limi (STEL): CAL AND CHEMICAL PF d Evap ets Spec EY Bulk / faint Vapo determined Vapo	t as Ti COPERTIES Poration rate : ific Gravity: : density :	ACGIH OSHA Z1 MX OEL Not applicable Not determined Not established Not applicable Not applicable		
Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 20 mg/m3 9. PHYSIO : Solid : Pelle : GRE : Very : Not : Not	(TWA): Time Weighted Average (TWA): PEL: Short Term Exposure Limi (STEL): CAL AND CHEMICAL PF d Evap Ets Spece EY Bulk / faint Vapo determined Vapo applicable pH	t as Ti COPERTIES Poration rate : ific Gravity: : density : or pressure :	ACGIH OSHA Z1 MX OEL Not applicable Not determined Not established Not applicable		
Titanium dioxide Torm Appearance Color Odor Melting point/range Soiling Point: Water solubility	10 mg/m3 15 mg/m3 20 mg/m3 9. PHYSIO : Solid : Pelld : GRE : Very : Not	(TWA): Time Weighted Average (TWA): PEL: Short Term Exposure Limi (STEL): CAL AND CHEMICAL PF d Evap Ets Spece EY Bulk / faint Vapo determined Vapo applicable pH	t as Ti COPERTIES Poration rate : ific Gravity: : density : or pressure :	ACGIH OSHA Z1 MX OEL Not applicable Not determined Not established Not applicable Not applicable		

MATERIAL SAFETY DATA SHEET Light Metallic Silver

Version Number 1.1 Page 4 of 6 Revision Date 11/20/2006 Print Date 11/25/2011 Hazardous Polymerization : Will not occur. Conditions to avoid Keep away from oxidizing agents and open flame. To avoid thermal : decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents.

Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

products

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
12001-26-2	Mica	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available

PolyOne.

MATERIAL SAFETY DATA SHEET Light Metallic Silver

Version Number 1.1 Revision Date 11/20/2006

Page 5 of 6 Print Date 11/25/2011

	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	us Substances (40 CFR 302)
Not applicable	
California Propositior 65	n : Not applicable
SARA Title III Section 302 E	Extremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regula

MATERIAL SAFETY DATA SHEET Light Metallic Silver

Version Number 1.1 Revision Date 11/20/2006

Page 6 of 6 Print Date 11/25/2011

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation Canadian Regulations: National Pollutant Release Inventory (NPRI) NPRI ID# Chemical Name CAS-No. Weight % 7429-90-5 0.10 - 1.00 Aluminum 12 WHMIS Classification : Not controlled. DSL All components of this product are on the Canadian Domestic : Substances List (DSL) or are exempt. National Inventories: Australia AICS Listed : China IECS Listed : Europe EINECS Listed : Japan ENCS Not determined : Korea KECI Listed ÷ **Philippines PICCS** Listed :

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.