MATERIAL SAFETY DATA SHEET **BLACK 419C**

Version Number 1.0 Revision Date 11/27/2006 Page 1 of 6 Print Date 11/25/2011

1. PRODUCT AND COMPANY IDENTIFICATION POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012 Product Stewardship (770) 271-5902 Telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure **Emergency telephone** : number or accident). Product name : BLACK 419C CC10094171 Product code :

Product code:CC10094171Chemical Name:MixtureCAS-No.:MixtureProduct Use:Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

: Inhalation, Ingestion, Skin contact		
Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.		
: Resin particles, like other inert materials, are mechanically irritating to eyes.		
: Experience shows no unusual dermatitis hazard from routine handling.		
: Refer to Section 11 for Toxicological Information.		
: None known.		



MATERIAL SAFETY DATA SHEET **BLACK 419C**

Version Number 1.0 Revision Date 11/27/2006 Page 2 of 6 Print Date 11/25/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	:	Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures Unusual Fire/Explosion	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards		(NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

2/6



MATERIAL SAFETY DATA SHEET **BLACK 419C**

Version Number 1.0 Revision Date 11/27/2006 Page 3 of 6 Print Date 11/25/2011

8. H	EXPOSURE	CONTROLS / PERSONA	AL PROTECTION		
Respiratory protection	: N	o personal respiratory prot	ective equipment normally	required.	
Eye/Face Protection	: S	: Safety glasses with side-shields.			
Hand protection	: P:	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		andle in accordance with g Vash hands before breaks a	ood industrial hygiene and a at the end of workday.	safety practice.	
Engineering measures		: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):		ACGIH	
	3.5 mg/m3	PEL:	Total dust. as carbon black	OSHA Z1	
	9. PHYSIC	CAL AND CHEMICAL P	PROPERTIES		
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	: Not a : Not a : Insol	ts Spe CK Bul faint Vap determined Vap applicable pH uble	ecific Gravity: : No lk density : No por pressure : No pour density : No : No	t applicable t determined t established t applicable t applicable t applicable	
	10. S	STABILITY AND REAC	ΓΙΥΙΤΥ		
Stability	: S	table.			
Hazardous Polymerization	n : W	/ill not occur.			
Conditions to avoid		eep away from oxidizing a ecomposition, do not overh	gents and open flame. To a leat.	avoid thermal	
	-	compatible with strong aci			

MATERIAL SAFETY DATA SHEET **BLACK 419C**

Version Number 1.0 Revision Date 11/27/2006

Page 4 of 6 Print Date 11/25/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

12. ECOLOGICAL INFORMATION
: Not readily biodegradable.
: Chemicals are not readily available as they are bound within the polymer matrix.
: Chemicals are not readily available as they are bound within the polymer matrix.
: No data available
13. DISPOSAL CONSIDERATIONS
: Like most thermoplastic plastics the product can be recycled. Where



MATERIAL SAFETY DATA SHEET **BLACK 419C**

sion Number 1.0 vision Date 11/27/2006		Page 5 of 6 Print Date <i>11/25/2011</i>
Contaminated packaging	:	possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA (air)	:	Refer to specific regulation.
IMO / IMDG (maritime)	:	Refer to specific regulation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardo	us Subs	stances (40 CFR 302)
Not applicable		
California Proposition 65	n :	Not applicable
SARA Title III Section 302 I	Extreme	ely Hazardous Substance
Unless specific chemicals are	e identi	fied under this section, this product is Not Applicable under this regulation
SARA Title III Section 313	Гoxic С	Shemicals:
Unless specific chemicals are	e identi	fied under this section, this product is Not Applicable under this regulation
Canadian Regulations:		

POLYONE CORPORATION

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **BLACK 419C**

Version Number 1.0 Revision Date 11/27/2006 Page 6 of 6 Print Date 11/25/2011

National Pollutant Release I	nventory (NPRI)	
Not applicable		
WHMIS Classification :	D2A	
WHMIS Ingredient Disclose	ure List	
CAS-No. 1333-86-4		
DSL :	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National Inventories:		
Australia AICS :	Listed	
China IECS :	Listed	
Europe EINECS :	Listed	
Japan ENCS :	Not determined	
Korea KECI :	Listed	
Philippines PICCS :	Listed	
	16. OTHER INFORMATION	Π

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.