PolvOne

MATERIAL SAFETY DATA SHEET UV BLUE

Version Number 1.0 Revision Date 02/08/2007

Product Use

Page 1 of 7 Print Date 11/26/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	UV BLUE
Product code	:	CC10094706
Chemical Name	:	Mixture
CAS-No.	:	Mixture

: Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
1,6-Hexanediamine,	70624-18-9	5 - 10
N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-,		
polymer with 2,4,6-trichloro-1,3,5-triazine,		
reaction products		
Titanium dioxide	13463-67-7	0.1 - 1
Rutile (TiO2)	1317-80-2	1 - 5
Mica	12001-26-2	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to
	eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

1/7

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET UV BLUE

Version Number 1.0 Revision Date 02/08/2007 Page 2 of 7 Print Date 11/26/2011

Medical Conditions : None known.					
Aggravated by Exposure:					
		4. FIRST AID MEASURES			
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.			
		5. FIRE-FIGHTING MEASURES			
Flash point	:	Not applicable			
Flammable Limits					
Upper explosion limit	:	Not applicable			
Lower explosion limit	:	Not applicable			
Autoignition temperature Suitable extinguishing media	:	Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.			
Suitable extinguishing media	•	Carbon dioxide blanket, water spray, dry powder, toannione.			
Special Fire Fighting	:	Fullface self-contained breathing apparatus (SCBA) used in positive			
Procedures		pressure mode should be worn to prevent inhalation of airborne			
		contaminants.			
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.			
	6. A	CCIDENTAL RELEASE MEASURES			
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.			
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.			

PolyOne

MATERIAL SAFETY DATA SHEET UV BLUE

Version Number 1.0 Revision Date 02/08/2007

Page 3 of 7 Print Date 11/26/2011

		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXF	OSUI	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Mica	20 mppcf	PEL:	Total dust.	OSHA
	3 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	3 mg/m3	Time Weighted Average (TWA):		MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range
- : Solid
 : Pellets
 : BLUE
 : Very faint
 : Not determined
- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density
- Not applicableNot determinedNot establishedNot applicableNot applicable





MATERIAL SAFETY DATA SHEET UV BLUE

Version Number 1.0 Revision Date 02/08/2007

_

_

Page 4 of 7 Print Date 11/26/2011

Boiling Point: Water solubility	: Not applicable : Insoluble	рН	: Not applicable
	10. STABILITY A	ND REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from decomposition, d	00	open flame. To avoid thermal
Incompatible Materials	: Incompatible wit	h strong acids and oxi	dizing agents.
Hazardous decomposition products			de (CO), oxides of nitrogen smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products	Irritant	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
12001-26-2	Mica	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products	Oral LD50 Dermal LD50	> 2,000 mg/kg > 3,000 mg/kg	rat rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

PolyOne

MATERIAL SAFETY DATA SHEET UV BLUE

Version Number 1.0

Revision Date 02/08/2007

Page 5 of 7 Print Date 11/26/2011

13463-67-7 Titanium dioxide no 2B no	CAS-No.	Chemical Name	OSHA	IARC	NTP
1317-80-2 Rutile (TiO2) no 2B no	13463-67-7		no	2B	no
	1317-80-2	Rutile (TiO2)	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

t readily biodegradable. emicals are not readily available as they are bound within the lymer matrix. emicals are not readily available as they are bound within the lymer matrix. data available ISPOSAL CONSIDERATIONS the most thermoplastic plastics the product can be recycled. Where essible recycling is preferred to disposal or incineration. The herator of waste material has the responsibility for proper waste ssification, transportation and disposal in accordance with plicable federal, state/provincial and local regulations. cycling is preferred when possible. The generator of waste material
lymer matrix. emicals are not readily available as they are bound within the lymer matrix. data available ISPOSAL CONSIDERATIONS the most thermoplastic plastics the product can be recycled. Where essible recycling is preferred to disposal or incineration. The merator of waste material has the responsibility for proper waste ssification, transportation and disposal in accordance with policable federal, state/provincial and local regulations.
ymer matrix. data available ISPOSAL CONSIDERATIONS The most thermoplastic plastics the product can be recycled. Where ssible recycling is preferred to disposal or incineration. The merator of waste material has the responsibility for proper waste ssification, transportation and disposal in accordance with blicable federal, state/provincial and local regulations.
ISPOSAL CONSIDERATIONS the most thermoplastic plastics the product can be recycled. Where ssible recycling is preferred to disposal or incineration. The merator of waste material has the responsibility for proper waste ssification, transportation and disposal in accordance with plicable federal, state/provincial and local regulations.
the most thermoplastic plastics the product can be recycled. Where essible recycling is preferred to disposal or incineration. The herator of waste material has the responsibility for proper waste ssification, transportation and disposal in accordance with plicable federal, state/provincial and local regulations.
ssible recycling is preferred to disposal or incineration. The herator of waste material has the responsibility for proper waste ssification, transportation and disposal in accordance with blicable federal, state/provincial and local regulations.
cycling is preferred when possible. The generator of waste material
the responsibility for proper waste classification, transportation disposal in accordance with applicable federal, state/provincial local regulations.
RANSPORT INFORMATION
t regulated for transportation.
fer to specific regulation.
fer to specific regulation.
EGULATORY INFORMATION
1 1 1

PolyOne.

MATERIAL SAFETY DATA SHEET **UV BLUE**

/ersion Number 1.0 Revision Date 02/08/2007			Pri	Page 6 of 7 int Date 11/26/2011
OSHA Status	: Classified as h	azardous based oi	n components.	
TSCA Status	: All componen Inventory.	ts of this product a	are listed on or exen	npt from the TSCA
US. EPA CERCLA Hazardous	Substances (40 CFR	302)		
Not applicable				
California Proposition 65	: Not applicable			
05				
SARA Title III Section 302 Ex	tremely Hazardous S	Substance		
Unless specific chemicals are i	dentified under this s	ection this produ	ct is Not Applicable	e under this regulation
		eenon, uns produ		
SARA Title III Section 313 To	xic Chemicals:			
Unless specific chemicals are id	dentified under this s	ection, this produ	ct is Not Applicable	e under this regulation
Canadian Regulations:				
National Pollutant Relea	asa Invantory (NDRT)		
Chemical Name		CAS-No.	Weight %	NPRI ID#
Phthalocyanine blue		147-14-8	0.10 - 1.00	71
WHMIS Classification	: D2B			
WHMIS Ingredient Disc	closure List			
CAS-No. 12001-26-2				
DSL		tts of this product st (DSL) or are exe	are on the Canadiar empt.	n Domestic
National Inventories:				
Australia AICS	: Listed			
China IECS	: Listed			
		6/7		

PolyOne

MATERIAL SAFETY DATA SHEET UV BLUE

Version Number 1.0 Revision Date 02/08/2007 Page 7 of 7 Print Date 11/26/2011

Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.