MATERIAL SAFETY DATA SHEET 30297 YELLOW K532

Version Number 1.1 Revision Date 02/22/2007

Page 1 of 6 Print Date 11/26/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	30297 YELLOW K532
Product code	:	CC10096341
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Aluminate (Al(OH)63-), (OC-6-11)-, magnesium carbonate hydroxide (2:6:1:4)	11097-59-9	1 - 5
Calcium carbonate	1317-65-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET 30297 YELLOW K532

Version Number 1.1 Revision Date 02/22/2007 Page 2 of 6 Print Date 11/26/2011

Aggravated by Exposure:	4. FIRST AID MEASURES			
	4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.			
	5. FIRE-FIGHTING MEASURES			
Flash point	: Not applicable			
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature	 Not applicable Not applicable Not applicable 			
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.			
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.			
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.			
	6. ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.			
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.			
	7. HANDLING AND STORAGE			

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 30297 YELLOW K532

/ersion Number 1.1 Revision Date 02/22/2007		Page 3 of 6 Print Date 11/26/2011
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSUE	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Aluminate	2 mg/m3	Time Weighted Average	as Al	ACGIH
(Al(OH)63-),		(TWA):		
(OC-6-11)-,				
magnesium carbonate				
hydroxide (2:6:1:4)				
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit		MX OEL
		(STEL):		

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
 Pellets
 YELLOW
 Very faint
 Not determined
 Not applicable
 Insoluble
- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 Not applicable
 Not applicable
 Not applicable

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 30297 YELLOW K532

Version Number 1.1 Revision Date 02/22/2007

_

Page 4 of 6 Print Date 11/26/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
11097-59-9	Aluminate (Al(OH)63-), (OC-6-11)-, magnesium carbonate hydroxide	Irritant	Eyes, Skin.
1317-65-3	(2:6:1:4) Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.

PolyOne.

MATERIAL SAFETY DATA SHEET 30297 YELLOW K532

Version Number 1.1 Revision Date 02/22/2007 Page 5 of 6 Print Date 11/26/2011

Additional advice	: No data available		
	13. DISPOSAL CONSIDERATIONS		
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
	14. TRANSPORT INFORMATION		
U.S. DOT Classification	: Not regulated for transportation.		
ICAO/IATA (air)	: Refer to specific regulation.		
IMO / IMDG (maritime)	: Refer to specific regulation.		
	15. REGULATORY INFORMATION		
US Regulations:			
OSHA Status	: Classified as hazardous based on components.		
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.		
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)		
Not applicable			
California Proposition 65	: Not applicable		
	xtremely Hazardous Substance		
SARA Title III Section 302 E			

PolyOne

MATERIAL SAFETY DATA SHEET 30297 YELLOW K532

Version Number 1.1 Revision Date 02/22/2007 Page 6 of 6 Print Date 11/26/2011

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

Chemical Name			CAS-No.	Weight %	NPRI ID#	
Zinc stearate			557-05-1	0.10 - 1.00	231	
WHMIS Classification WHMIS Ingredient Dis		D2B re List				
CAS-No. 11097-59-9						
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.				
tional Inventories:						
Australia AICS	:	Listed				
China IECS	:	Listed				
Europe EINECS	:	Listed				
Japan ENCS	:	Not determine	ed			
Korea KECI	:	Listed				
Philippines PICCS	:	Listed				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.