PolvOne

MATERIAL SAFETY DATA SHEET

Metallic Pyrite

Product Use

Version Number 1.0 Revision Date 02/07/2007 Page 1 of 8 Print Date 11/26/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	Metallic Pyrite
Product code	:	CC10096527
Chemical Name	:	Mixture
CAS-No.	:	Mixture

: Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	1 - 5
Rutile, antimony chromium buff	68186-90-3	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Aluminum	7429-90-5	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

MATERIAL SAFETY DATA SHEET *Metallic Pyrite*

Version Number 1.0 Revision Date 02/07/2007 Page 2 of 8 Print Date 11/26/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures Unusual Fire/Explosion Hazards	 rainage sent containing opplatuus (SODIT) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as
Environmental precautions	impervious gloves, boots and coveralls.Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat

<u>PolyOne</u>.



MATERIAL SAFETY DATA SHEET *Metallic Pyrite*

Version Number 1.0 Revision Date 02/07/2007	Page Print Date 11/26	3 of 8 2011
Storage :	only in areas with appropriate exhaust ventilation. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.	1
8. EXPOSU	E CONTROLS / PERSONAL PROTECTION	
Respiratory protection :	No personal respiratory protective equipment normally required.	
Eye/Face Protection :	Safety glasses with side-shields.	
Hand protection :	Protective gloves.	
Skin and body protection :	Long sleeved clothing.	
Additional Protective : Measures	Safety shoes.	
General Hygiene : Considerations	Handle in accordance with good industrial hygiene and safety practic Wash hands before breaks and at the end of workday.	ce.
Engineering measures :	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.	
Exposure limit(s)		

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET *Metallic Pyrite*

Version Number 1.0 Revision Date 02/07/2007 Page 4 of 8 Print Date 11/26/2011

Components	Value	Exposure time	Exposure type	List:
Aluminum	10 mg/m3	Time Weighted Average (TWA):	Dust.	ACGIH
	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Dust.	MX OEL
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):	Total dust. as carbon black	ACGIH
	3.5 mg/m3	PEL:	Total dust. as carbon black	OSHA Z1
Rutile, antimony chromium buff	0.5 mg/m3	Time Weighted Average (TWA):	as Cr	ACGIH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility

:	Solid
:	Pellets
:	GREY
:	Very faint
:	Not determined
:	Not applicable
:	Insoluble

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH

- Not applicableNot determinedNot establishedNot applicableNot applicable
- : Not applicable

10. STABILITY AND REACTIVITY	
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

MATERIAL SAFETY DATA SHEET *Metallic Pyrite*

Version Number 1.0

Revision Date 02/07/2007

Page 5 of 8 Print Date 11/26/2011

products

(NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory system.
	chromium buff		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

MATERIAL SAFETY DATA SHEET

Metallic Pyrite

Version Number 1.0 Revision Date 02/07/2007 Page 6 of 8 Print Date 11/26/2011

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Wher possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste mater has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.

PolyOne

MATERIAL SAFETY DATA SHEET *Metallic Pyrite*

Version Number 1.0 Revision Date 02/07/2007 Page 7 of 8 Print Date 11/26/2011

	15. REGUL	LATORY INFO	RMATIO	ON		
US Regulations:						
OSHA Status	: Classifie	ed as hazardous t	based on c	components		
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.					
US. EPA CERCLA Hazardo	ous Substances (4	0 CFR 302)				
Not applicable						
California Propositio 65	on : Not appl	licable				
Unless specific chemicals and	e identified under	r this section, thi	s product	is Not App	licable	under this regu
	.					
SARA Title III Section 313						
Unless specific chemicals a						
Unless specific chemicals an Chemical Name	re identified under		CAS-N	0.	Weight	t %
Unless specific chemicals a	re identified under R DUST)	r this section, thi		o. -5		10.00
Unless specific chemicals an Chemical Name ALUMINUM (FUME OF CHROMIUM III COMPO	re identified under R DUST)	r this section, thi	CAS-N 7429-90	o. -5	Weight 5.00 -	10.00
Unless specific chemicals an Chemical Name ALUMINUM (FUME OF CHROMIUM III COMPO COMPOUNDS Canadian Regulations: National Pollutant Ref	re identified under R DUST) DUNDSANTIMO	r this section, thi	CAS-N 7429-90 68186-9	0. 0-5 0-3	Weight 5.00 - 1.00 -	<u>10.00</u> 5.00
Unless specific chemicals an Chemical Name ALUMINUM (FUME OF CHROMIUM III COMPO COMPOUNDS Canadian Regulations: National Pollutant Re Chemical Name	re identified under R DUST) DUNDSANTIMO	n this section, thi NY NPRI)	CAS-N 7429-90 68186-9	0. 0-3 Weight	Weight 5.00 - 1.00 - %	× % 10.00 5.00 NPRI ID#
Unless specific chemicals an Chemical Name ALUMINUM (FUME OF CHROMIUM III COMPO COMPOUNDS Canadian Regulations: National Pollutant Re Chemical Name Aluminum	re identified under R DUST) DUNDSANTIMO elease Inventory (n this section, thi NY NPRI) CAS-N 7429-9	CAS-N 7429-90 68186-9 00-5	0. -5 0-3 Weight 5.00 - 1	Weight 5.00 - 1.00 - % % 0.00	 <u>%</u> 10.00 <u>5.00</u> <u>NPRI ID#</u> 12
Unless specific chemicals an Chemical Name ALUMINUM (FUME OF CHROMIUM III COMPO COMPOUNDS Canadian Regulations: National Pollutant Re Chemical Name	re identified under R DUST) DUNDSANTIMO elease Inventory (n this section, thi NY NPRI)	CAS-N 7429-90 68186-9 00-5	0. 0-3 Weight	Weight 5.00 - 1.00 - % 0.00 -	× % 10.00 5.00 NPRI ID#

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.

PolyOne.

MATERIAL SAFETY DATA SHEET *Metallic Pyrite*

Version Number 1.0 Revision Date 02/07/2007

_

Page 8 of 8 Print Date 11/26/2011

7429-90-5			
1333-86-4 68186-90-3			
00100-90-3			
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National Inventories:			
Australia AICS	:	Listed	
China IECS	:	Listed	
Europe EINECS	:	Listed	
Japan ENCS	:	Not determined	
Korea KECI	:	Listed	
Philippines PICCS	:	Listed	
		16. OTHER INFORMATION	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.