MATERIAL SAFETY DATA SHEET COLOR PLUS BEIGE 2

Version Number 1.0 Revision Date 02/28/2007

Page 1 of 7 Print Date 11/26/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	COLOR PLUS BEIGE 2
Product code	:	CC10096929
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Rutile, antimony chromium buff	68186-90-3	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.
Eyes Skin	 Resin particles, like other inert materials, are mechanically irritating to eyes. Experience shows no unusual dermatitis bezord from routing handling
SKII	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET COLOR PLUS BEIGE 2

Version Number 1.0 Revision Date 02/28/2007 Page 2 of 7 Print Date 11/26/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists se medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not applicable
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

PolyOne

MATERIAL SAFETY DATA SHEET COLOR PLUS BEIGE 2

Version Number 1.0 Revision Date 02/28/2007

_

Page 3 of 7 Print Date 11/26/2011

and contamination. Keep in a dry, cool place.				
8. H	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection : No personal respiratory protective equipment normally required.				
Eye/Face Protection	: \$	afety glasses with side-shields.		
Hand protection	: F	Protective gloves.		
Skin and body protection	: I	long sleeved clothing.		
Additional Protective : Safety shoes. Measures				
General Hygiene: Handle in accordance with good industrial hygiene and safety practice.ConsiderationsWash hands before breaks and at the end of workday.				
Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Rutile, antimony chromium buff	0.5 mg/m3	Time Weighted Average (TWA):	as Cr	ACGIH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1

	0.5 mg/m3	Time Weighted Average	as Sb	ACGIH
		(TWA):		
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average	as Sb	MX OEL
		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
		(STEL):		

Time Weighted Average

(TWA):

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
 Pellets
 TAN
 Very faint
 Not determined
 Not applicable
 Insoluble

0.5 mg/m3

- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 Not applicable
 Not applicable
 Not applicable

MX OEL

MATERIAL SAFETY DATA SHEET COLOR PLUS BEIGE 2

Version Number 1.0 Revision Date 02/28/2007

Page 4 of 7 Print Date 11/26/2011

		10	. STABILITY AND REACTIVITY	t
S	tability	:	Stable.	
ŀ	Hazardous Polymerization	:	Will not occur.	
C	Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.	
I	ncompatible Materials	:	Incompatible with strong acids and oxidizing agents.	
	Hazardous decomposition roducts	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory system.
	chromium buff		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

12. ECOLOGICAL INFORMATION

PolyOne.

MATERIAL SAFETY DATA SHEET COLOR PLUS BEIGE 2

Version Number 1.0 Revision Date 02/28/2007 Page 5 of 7 Print Date 11/26/2011

Dergistance and degradability	Not readily biodegradelle
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Wher possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste mater has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSC Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition	: Not applicable

PolvOne

MATERIAL SAFETY DATA SHEET COLOR PLUS BEIGE 2

Version Number 1.0 Revision Date 02/28/2007 Page 6 of 7 Print Date 11/26/2011

65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight %	
CHROMIUM III COMPOUNDSANTIMONY	68186-90-3	1.00 - 5.00	
COMPOUNDS			

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Aluminum oxide	1344-28-1	0.10 - 1.00	13
Rutile, antimony chromium buff	68186-90-3	1.00 - 5.00	69
		1.00 - 5.00	17

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.
68186-90-3

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Listed
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Listed
Philippines PICCS	: Listed

:

PolyOne

MATERIAL SAFETY DATA SHEET COLOR PLUS BEIGE 2

Version Number 1.0 Revision Date 02/28/2007

Page 7 of 7 Print Date 11/26/2011

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.