PolvOne

### MATERIAL SAFETY DATA SHEET

#### **PVC Smooth Silver**

Version Number 1.0 Revision Date 02/22/2007

Product Use

Page 1 of 8 Print Date 11/26/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PVC Smooth Silver
Product code	:	CC10097273
Chemical Name	:	Mixture
CAS-No.	:	Mixture

: Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Aluminum	7429-90-5	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Mica	12001-26-2	5 - 10
Calcium carbonate	1317-65-3	10 - 30

#### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion Eyes	<ul><li>May be harmful if swallowed.</li><li>Particulates, like other inert materials can be mechanically irritating.</li></ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

# MATERIAL SAFETY DATA SHEET PVC Smooth Silver

Version Number 1.0 Revision Date 02/22/2007 Page 2 of 8 Print Date 11/26/2011

Medical Conditions       : None known.         Aggravated by Exposure:					
	4. FIRST AID MEASURES				
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.				
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.				
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.				
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.				
	5. FIRE-FIGHTING MEASURES				
Flash point	: Not applicable				
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foamnone.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne</li> </ul>				
Unusual Fire/Explosion Hazards	<ul> <li>contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.</li> </ul>				
	6. ACCIDENTAL RELEASE MEASURES				
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.				
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.				
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.				

**POLYONE CORPORATION** 

PolyOne.

# MATERIAL SAFETY DATA SHEET PVC Smooth Silver

Version Number 1.0 Revision Date 02/22/2007 Page 3 of 8 Print Date 11/26/2011

Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.			
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.			
8. EXF	POSUF	RE CONTROLS / PERSONAL PROTECTION			
Respiratory protection	:	No personal respiratory protective equipment normally required.			
Eye/Face Protection	:	Safety glasses with side-shields.			
Hand protection	:	Protective gloves.			
Skin and body protection	:	Long sleeved clothing.			
Additional Protective Measures	:	Safety shoes.			
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.			
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)					

PolyOne

### **MATERIAL SAFETY DATA SHEET PVC Smooth Silver**

Version Number 1.0 Revision Date 02/22/2007 Page 4 of 8 Print Date 11/26/2011

Components	Value	Exposure time		Exposure type	List:
Aluminum	10 mg/m3	Time Weighted Average (TWA):		Dust.	ACGIH
	15 mg/m3	PEL:		Total dust. as Al	OSHA Z1
	5 mg/m3	PEL:		Respirable dust. as Al	OSHA Z1
	10 mg/m3	Time Weighted Avera (TWA):	ige	Dust.	MX OEL
Calcium carbonate	5 mg/m3	PEL:		Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:		Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Avera (TWA):	ge		MX OEL
	20 mg/m3	Short Term Exposure L (STEL):	imit		MX OEL
Mica	20 mppcf	PEL:		Total dust.	OSHA
	3 mg/m3	Time Weighted Average (TWA):		Respirable fraction.	ACGIH
	3 mg/m3	Time Weighted Avera (TWA):	ge		MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):			ACGIH
	15 mg/m3	PEL:		Total dust.	OSHA Z1
	20 mg/m3	Short Term Exposure Limit (STEL):		as Ti	MX OEL
	9. PHYSIC	CAL AND CHEMICAL	PRO	PERTIES	
Form Appearance	: Pelle	: Pellets Specific		c Gravity: : No	t applicable t determined
Color	: GREY		ulk de	•	t established
Odor	: Very faint				applicable
Melting point/range					applicable
Boiling Point: Water solubility	: Not : : Insol	applicable pH luble		: No	applicable
	10. 8	STABILITY AND REA	CTIV	ITY	

Stability

Hazardous Polymerization

: Stable.

: Will not occur.

Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during

## MATERIAL SAFETY DATA SHEET **PVC Smooth Silver**

Version Number 1.0 Revision Date 02/22/2007

Page 5 of 8 Print Date 11/26/2011

Prevent cross contamination of feedstocks.

Hazardous decomposition<br/>products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen<br/>(NOx), hydrogen chloride (HCl), other hazardous materials, and<br/>smoke are all possible. Prolonged heating (approximately 30 minutes<br/>or more) above 392 °F (200 °C) or short term heating at 482 °F (250<br/>°C) may result in product decomposition and evolution of carbon<br/>monoxide and hydrogen chloride.

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
12001-26-2	Mica	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.

**POLYONE CORPORATION** 



# MATERIAL SAFETY DATA SHEET PVC Smooth Silver

Version Number 1.0 Revision Date 02/22/2007

Page 6 of 8 Print Date 11/26/2011

	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
Not applicable	
California Proposition 65	n : Not applicable
SARA Title III Section 302 H	Extremely Hazardous Substance
	identified under this section, this product is Not Applicable under this regula

## MATERIAL SAFETY DATA SHEET

### **PVC Smooth Silver**

Version Number 1.0 Revision Date 02/22/2007 Page 7 of 8 Print Date 11/26/2011

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulationChemical NameCAS-No.Weight %ALUMINUM (FUME OR DUST)7429-90-51.00 - 5.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)								
Chemical Name	CAS-No.	Weight %	NPRI ID#					
Aluminum	7429-90-5	1.00 - 5.00	12					
Manganese antimony titanium brown rutile (C.I.	68412-38-4	0.10 - 1.00	147					
Pigment Yellow 164)								
		0.10 - 1.00	17					
Rutile, antimony chromium buff	68186-90-3	0.10 - 1.00	69					
		0.10 - 1.00	17					

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.	
7429-90-5	
12001-26-2	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Listed

÷

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The

PolyOne.

## MATERIAL SAFETY DATA SHEET **PVC Smooth Silver**

Version Number 1.0 Revision Date 02/22/2007 Page 8 of 8 Print Date 11/26/2011

information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.