PolvOne

MATERIAL SAFETY DATA SHEET SILVER B V3

Version Number 1.0 Revision Date 03/08/2007

Page 1 of 7 Print Date 11/26/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number		Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	SILVER B V3
Product code	:	CC10097572
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	•	Industrial Applications

: Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	0.1 - 1
Calcium carbonate	1317-65-3	1 - 5
Mica	12001-26-2	1 - 5
Aluminum	7429-90-5	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact			
Acute exposure				
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eves. 			
Skin	: Experience shows no unusual dermatitis hazard from routine handling.			
Chronic exposure	: Refer to Section 11 for Toxicological Information.			

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET SILVER B V3

Version Number 1.0 Revision Date 03/08/2007 Page 2 of 7 Print Date 11/26/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists se medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat



MATERIAL SAFETY DATA SHEET SILVER B V3

Version Number 1.0 Revision Date 03/08/2007	Page 3 of 7 Print Date 11/26/2011
Storage :	only in areas with appropriate exhaust ventilation. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXPOSU	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection :	No personal respiratory protective equipment normally required.
Eye/Face Protection :	Safety glasses with side-shields.
Hand protection :	Protective gloves.
Skin and body protection :	Long sleeved clothing.
Additional Protective : Measures	Safety shoes.
General Hygiene : Considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures :	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)	

PolyOne.

MATERIAL SAFETY DATA SHEET SILVER B V3

Version Number 1.0 Revision Date 03/08/2007

Page 4 of 7 Print Date 11/26/2011

Appearance : Pellets Specific Gravity: : Not determined Color : GREY Bulk density : Not established Odor : Very faint Vapor pressure : Not applicable Melting point/range : Not determined Vapour density : Not applicable Boiling Point: : Not applicable pH : Not applicable Water solubility : Insoluble Insoluble Insoluble Very faint Vapour density : Not applicable Boiling Point: : Not applicable pH : Not applicable Water solubility : Insoluble Insoluble Insoluble Very faint Vapour density : Not applicable Water solubility : Insoluble Insoluble Insoluble Very faint Very faint : Stable. Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.	Components	Value	Exposure time	Exposure type	List:	
5 mg/m3 PEL: Respirable dust. as Al OSHA Z1 10 mg/m3 Time Weighted Average (TWA): Dust. MX OEL Calcium carbonate 5 mg/m3 PEL: Respirable fraction. OSHA Z1 10 mg/m3 PEL: Total dust. OSHA Z1 10 mg/m3 Short Term Exposure Limit (STEL): MX OEL Mica 20 mp/cf PEL: Total dust. OSHA 3 mg/m3 Time Weighted Average (TWA): MX OEL OSHA 21 fanium dioxide 10 mg/m3 Time Weighted Average (TWA): MX OEL 22 mg/m3 Time Weighted Average (TWA): MX OEL OSHA Z1 20 mg/m3 Time Weighted Average (TWA): MX OEL OSHA 21 fanium dioxide 10 mg/m3 Time Weighted Average (TWA): MX OEL 22 mg/m3 Short Term Exposure Limit (STEL): MX OEL OSHA Z1 20 mg/m3 Short Term Exposure Limit (STEL): Not applicable Not applicable 9. PHYSICAL AND CHEMICAL PROPERTIES Not appl	Aluminum	10 mg/m3		Dust.		
I0 mg/m3 Time Weighted Average (TWA): Dust. MX OEL (TWA): Calcium carbonate 5 mg/m3 PEL: Respirable fraction. OSHA ZI OSHA ZI 10 mg/m3 Time Weighted Average (TWA): MX OEL OSHA ZI 20 mg/m3 Short Term Exposure Limit (STEL): MX OEL OSHA Mica 20 mpc/f PEL: Total dust. OSHA 3 mg/m3 Time Weighted Average (TWA): MX OEL OSHA 3 mg/m3 Time Weighted Average (TWA): MX OEL OSHA 3 mg/m3 Time Weighted Average (TWA): MX OEL OSHA 15 mg/m3 PEL: Total dust. OSHA ZI 20 mg/m3 Short Term Exposure Limit (STEL): MX OEL OSHA ZI 20 mg/m3 Short Term Exposure Limit (STEL): MX OEL OSHA ZI 20 mg/m3 Short Term Exposure Limit (STEL): Ostal dust. OSHA ZI 20 mg/m3 Short Term Exposure Limit (STEL): MX OEL OSHA ZI 20 mg/m3 Short Term Exposure Limit (STEL): Not applicable OSHA ZI 9. PHYSICAL AND CHEMICAL PROPERTIES Solid Evaporation rate : Not applicable Not		15 mg/m3	PEL:	Total dust. as Al	OSHA Z1	
Calcium carbonate 5 mg/m3 PEL: Respirable fraction. OSHA ZI 15 mg/m3 PEL: Total dust. OSHA ZI 10 mg/m3 Time Weighted Average (TWA): MX OEL 20 mg/m3 Short Term Exposure Limit (STEL): MX OEL Mica 20 mppcf PEL: Total dust. OSHA 3 mg/m3 Time Weighted Average (TWA): Respirable fraction. ACGIH 3 mg/m3 Time Weighted Average (TWA): MX OEL ACGIH 115 mg/m3 Time Weighted Average (TWA): MX OEL OSHA ZI 20 mg/m3 Time Weighted Average (TWA): MX OEL ACGIH 115 mg/m3 PEL: Total dust. OSHA ZI 20 mg/m3 Short Term Exposure Limit (STEL): as Ti MX OEL OSHA ZI Otal dust. OSHA ZI 20 mg/m3 Time Weighted Average (TWA): MX OEL Otal dust. OSHA ZI 20 mg/m3 Short Term Exposure Limit (STEL): MX OEL OPHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not a		5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1	
15 mg/m3 PEL: Total dust. OSHA Z1 10 mg/m3 Time Weighted Average (TWA); MX OEL 20 mg/m3 Short Term Exposure Limit (STEL); MX OEL Mica 20 mpprf PEL: Total dust. OSHA 3 mg/m3 Time Weighted Average (TWA); MX OEL OSHA 3 mg/m3 Time Weighted Average (TWA); MX OEL ACGIH 1tanium dioxide 10 mg/m3 Time Weighted Average (TWA); MX OEL OSHA Z1 20 mg/m3 Time Weighted Average (TWA); ACGIH OSHA Z1 20 mg/m3 Short Term Exposure Limit (STEL); MX OEL OSHA Z1 20 mg/m3 Short Term Exposure Limit (STEL); as Ti MX OEL 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable Appearance : Pellets Specific Gravity: : Not applicable Color : GREY Bulk density : Not applicable Not applicable Odor : Very faint Vapor pressure : Not applicable Not applicable Mater solubility : Insoluble Insoluble Not applicable IO. STABILITY AND REACTIVITY Stability : Stable. </td <td></td> <td>10 mg/m3</td> <td></td> <td>Dust.</td> <td>MX OEL</td>		10 mg/m3		Dust.	MX OEL	
10 mg/m3 Time Weighted Average (TWA): MX OEL 20 mg/m3 Short Term Exposure Limit (STEL): MX OEL Mica 20 mppcf PEL: Total dust. OSHA 3 mg/m3 Time Weighted Average (TWA): Respirable fraction. ACGIH 3 mg/m3 Time Weighted Average (TWA): MX OEL ACGIH 11 mg/m3 Time Weighted Average (TWA): MX OEL ACGIH 11 mg/m3 Time Weighted Average (TWA): MX OEL ACGIH 11 mg/m3 Time Weighted Average (TWA): MX OEL OEL 15 mg/m3 PEL: Total dust. OSHA ZI 20 mg/m3 Short Term Exposure Limit (STEL): as Ti MX OEL 9. PHYSICAL AND CHEMICAL PROPERTIES OEL Otal dust. OSHA ZI 04 mg/m3 Short Term Exposure Limit (STEL): as Ti MX OEL 9. PHYSICAL AND CHEMICAL PROPERTIES Social Exporation rate Not applicable Appearance : Pellets Specific Gravity: Not applicable 20 or : GREY Bulk density : Not applicable 20 or : Very faint	Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1	
Image: Construct of the stress of the str				Total dust.		
Mica 20 mppcf PEL: Total dust. OSHA 3 mg/m3 Time Weighted Average (TWA): Respirable fraction. ACGIH 3 mg/m3 Time Weighted Average (TWA): MX OEL Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): MX OEL Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): ACGIH 115 mg/m3 PEL: Total dust. OSHAZI 20 mg/m3 Short Term Exposure Limit (STEL): as Ti MX OEL 20 mg/m3 Short Term Exposure Limit (STEL): as Ti MX OEL 9. PHYSICAL AND CHEMICAL PROPERTIES Form Solid Evaporation rate : Not applicable Appearance : Pellets Specific Gravity: : Not applicable Odor : GREY Bulk density : Not applicable Meting point/range : Not determined Vapour density : Not applicable Boiling Point: : Not applicable pH : Not applicable Mater solubility : Insoluble : Stable. Insoluble <		0	(TWA):			
3 mg/m3 Time Weighted Average (TWA): Respirable fraction. ACGIH 3 mg/m3 Time Weighted Average (TWA): MX OEL Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): MX OEL 15 mg/m3 PEL: Total dust. OSHA ZI 20 mg/m3 Short Term Exposure Limit (STEL): as Ti MX OEL 9. PHYSICAL AND CHEMICAL PROPERTIES Form Solid Evaporation rate : Not applicable Appearance : Pellets Specific Gravity: : Not determined Color : GREY Bulk density : Not applicable Melting point/range : Not determined Vapour pressure : Not applicable Boiling Point: : Not applicable pH : Not applicable Water solubility : Insoluble Insoluble Not applicable IO. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur. : Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materia		20 mg/m3			MX OEL	
Image: Constraint of the standard stress of the standard stress of the standard stress of the standard stress of the stress o	Mica	20 mppcf	PEL:	Total dust.	OSHA	
Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): ACGIH 15 mg/m3 PEL: Total dust. OSHA Z1 20 mg/m3 Short Term Exposure Limit (STEL): as Ti MX OEL 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable Appearance Color GREY Bulk density : Not determined Old of the termined Vapor pressure : Not applicable Melting point/range : Not determined Vapour density : Not established Old STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible with strong acids and oxidizing agents.		3 mg/m3		Respirable fraction.	ACGIH	
Image: Constraint of the strong acids and oxidizing agents. Image: Constraint of the strong acids and oxidizing agents. Image: Constraint of the strong acids and oxidizing agents. Image: Constraint of the strong acids and oxidizing agents.		3 mg/m3	(TWA):		MX OEL	
20 mg/m3 Short Term Exposure Limit (STEL): as Ti MX OEL 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable Appearance : Pellets Specific Gravity: Not determined Color : GREY Bulk density : Not determined Odor : Very faint Vapor pressure : Not applicable Melting point/range : Not determined Vapour density : Not applicable Boiling Point: : Not applicable pH : Not applicable Built density : Not applicable Water solubility : Insoluble IO. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents. Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen	Titanium dioxide	10 mg/m3	6 6		ACGIH	
(STEL): 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable Appearance : Pellets Specific Gravity: : Not determined Color : GREY Bulk density : Not determined Odor : Very faint Vapor pressure : Not applicable Melting point/range : Not determined Vapour density : Not applicable Boiling Point: : Not applicable pH : Not applicable Water solubility : Insoluble Insoluble Insoluble Insoluble Stability : Stable. Hazardous Polymerization : Will not occur. : Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents. Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen <td></td> <td>•</td> <td></td> <td></td> <td></td>		•				
Form : Solid Evaporation rate : Not applicable Appearance : Pellets Specific Gravity: : Not determined Color : GREY Bulk density : Not established Odor : Very faint Vapor pressure : Not applicable Melting point/range : Not determined Vapour density : Not applicable Boiling Point: : Not applicable pH : Not applicable Boiling Point: : Not applicable pH : Not applicable Water solubility : Insoluble Insoluble Insoluble IO. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents. Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen		20 mg/m3	-	as Ti	MX OEL	
Appearance:PelletsSpecific Gravity::Not determinedColor:GREYBulk density:Not establishedOdor:Very faintVapor pressure:Not applicableMelting point/range:Not determinedVapour density:Not applicableBoiling Point::Not applicablepH:Not applicableBoiling Point::Not applicablepH:Not applicableWater solubility:InsolubleConditions to avoid:Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.Conditions to avoid:Incompatible with strong acids and oxidizing agents.Hazardous decomposition:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen		9. PHYSIC	CAL AND CHEMICAL PRO	DPERTIES		
Color: GREYBulk density: Not establishedOdor: Very faintVapor pressure: Not applicableMelting point/range: Not determinedVapour density: Not applicableBoiling Point:: Not applicablepH: Not applicableWater solubility: InsolubleInsoluble	Form	: Solic			applicable	
Odor: Very faintVapor pressure: Not applicableMelting point/range: Not determinedVapour density: Not applicableBoiling Point:: Not applicablepH: Not applicableWater solubility: InsolubleInsolubleInsolubleIO. STABILITY AND REACTIVITYStability: Stable.: Will not occur.Conditions to avoid:Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.Incompatible Materials: Incompatible with strong acids and oxidizing agents.Hazardous decomposition: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen	Appearance					
Melting point/range : Not determined Vapour density : Not applicable Boiling Point: : Not applicable pH : Not applicable Water solubility : Insoluble 10. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents. Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen						
Boiling Point: : Not applicable pH : Not applicable Water solubility : Insoluble 10. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents. Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen						
Water solubility : Insoluble Insoluble 10. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents. Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen						
10. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents. Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen						
Stability : Stable. Hazardous Polymerization : Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents. Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen	Water solubility	: Insol	luble			
 Hazardous Polymerization : Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents. Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen 		10. 5	STABILITY AND REACTIV	VITY		
Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents. Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen	Stability	: S	table.			
decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents. Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen	Hazardous Polymerizatio	n : W	Vill not occur.			
Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen						
	Incompatible Materials : Incompatible with strong acids and oxidizing agents.					

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET SILVER B V3

Version Number 1.0 Revision Date 03/08/2007 Page 5 of 7 Print Date 11/26/2011

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
12001-26-2	Mica	Systemic effects	Respiratory system.
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.



MATERIAL SAFETY DATA SHEET SILVER B V3

ersion Number 1.0 evision Date 03/08/2007			Page 6 of 7 Print Date 11/26/2011		
Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.					
	1	4. TRANSPORT INFOR	MATION		
U.S. DOT Classification	:	Not regulated for transpo	rtation.		
ICAO/IATA (air)	:	Refer to specific regulation	on.		
IMO / IMDG (maritime)	:	Refer to specific regulation	on.		
	15	. REGULATORY INFO	RMATION		
US Regulations:					
OSHA Status	:	Classified as hazardous b	ased on componen	nts.	
TSCA Status	TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.				
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)			
Not applicable					
California Proposition 65	:	Not applicable			
SARA Title III Section 302 Ex	trem	ely Hazardous Substance			
Unless specific chemicals are in	lenti	fied under this section, this	s product is Not A _l	pplicable under this regulation	
SARA Title III Section 313 To					
Unless specific chemicals are id Chemical Name ALUMINUM (FUME OR D			CAS-No. 7429-90-5	Weight % 10.00 - 30.00	
Canadian Regulations:					
National Pollutant Relea	ise Ii	nventory (NPRI)			

PolyOne

MATERIAL SAFETY DATA SHEET SILVER B V3

Version Number 1.0 Revision Date 03/08/2007

Page 7 of 7 Print Date 11/26/2011

Chemical Name CAS	S-No. Wei	ght % N	PRI ID#
Aluminum 7429	9-90-5 10.0	0 - 30.00 12	2

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.	
7429-90-5	
12001-26-2	

:

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Listed
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Listed
Philippines PICCS	: Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.