PolvOne.

### **MATERIAL SAFETY DATA SHEET** WHITE ETCH

Version Number 1.0 Revision Date 03/13/2007

Page 1 of 7 Print Date 11/26/2011

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	WHITE ETCH
Product code	:	CC10097765
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

: Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Antimony trioxide	1309-64-4	0.1 - 1
Titanium dioxide	13463-67-7	1 - 5
Tin oxide	1332-29-2	1 - 5

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	<ul><li>Resin particles, like other inert materials, can be mechanically irritating.</li><li>May be harmful if swallowed.</li></ul>
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

# MATERIAL SAFETY DATA SHEET WHITE ETCH

Version Number 1.0 Revision Date 03/13/2007 Page 2 of 7 Print Date 11/26/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foamnone.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



## MATERIAL SAFETY DATA SHEET WHITE ETCH

Version Numb	er 1.0
<b>Revision Date</b>	03/13/2007

Storage

Page 3 of 7 Print Date 11/26/2011

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	: No j	personal respiratory protective equipment normally required.
Eye/Face Protection	: Safe	ty glasses with side-shields.
Hand protection	: Prot	ective gloves.
Skin and body protection	: Lon	g sleeved clothing.
Additional Protective Measures	: Safe	ty shoes.
General Hygiene Considerations		dle in accordance with good industrial hygiene and safety practice. h hands before breaks and at the end of workday.
Engineering measures		t only in areas with appropriate exhaust ventilation. Provide opriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Antimony trioxide	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average	as Sb	ACGIH
		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
		(STEL):		
Tin oxide	2 mg/m3	Time Weighted Average	as Sn	ACGIH
		(TWA):		
	2 mg/m3	Time Weighted Average	as Sn	MX OEL
		(TWA):		
	4 mg/m3	Short Term Exposure Limit	as Sn	MX OEL
		(STEL):		

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range Boiling Point: Solid
Pellets
ORANGE
Very faint
Not determined
Not applicable

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH Not applicable
Not determined
Not established
Not applicable
Not applicable
Not applicable

## **MATERIAL SAFETY DATA SHEET** WHITE ETCH

Version Number 1.0 Revision Date 03/13/2007

Page 4 of 7 Print Date 11/26/2011

Water solubility	Insoluble	
	10. STABILITY AND REACTIVITY	]
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.	
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.	
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

PolyOne

## MATERIAL SAFETY DATA SHEET WHITE ETCH

Version Number 1.0 Revision Date 03/13/2007 Page 5 of 7 Print Date 11/26/2011

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

<ul> <li>biodegradable.</li> <li>re not readily available as they are bound within the rix.</li> <li>re not readily available as they are bound within the rix.</li> <li>lable</li> <li>CONSIDERATIONS</li> <li>ermoplastic plastics the product can be recycled. Where cling is preferred to disposal or incineration. The waste material has the responsibility for proper waste a, transportation and disposal in accordance with deral, state/provincial and local regulations.</li> <li>preferred when possible. The generator of waste material nsibility for proper waste classification, transportation in accordance with applicable federal, state/provincial ulations.</li> </ul>
rix. The not readily available as they are bound within the rix. Table
rix. lable <b>CONSIDERATIONS</b> ermoplastic plastics the product can be recycled. Where cling is preferred to disposal or incineration. The waste material has the responsibility for proper waste a, transportation and disposal in accordance with deral, state/provincial and local regulations. preferred when possible. The generator of waste material nsibility for proper waste classification, transportation in accordance with applicable federal, state/provincial ulations.
ermoplastic plastics the product can be recycled. Where cling is preferred to disposal or incineration. The waste material has the responsibility for proper waste a, transportation and disposal in accordance with deral, state/provincial and local regulations. preferred when possible. The generator of waste material nsibility for proper waste classification, transportation in accordance with applicable federal, state/provincial ulations.
ermoplastic plastics the product can be recycled. Where rcling is preferred to disposal or incineration. The waste material has the responsibility for proper waste a, transportation and disposal in accordance with deral, state/provincial and local regulations. preferred when possible. The generator of waste material nsibility for proper waste classification, transportation in accordance with applicable federal, state/provincial ulations.
cling is preferred to disposal or incineration. The waste material has the responsibility for proper waste a, transportation and disposal in accordance with deral, state/provincial and local regulations. preferred when possible. The generator of waste material nsibility for proper waste classification, transportation in accordance with applicable federal, state/provincial ulations.
nsibility for proper waste classification, transportation in accordance with applicable federal, state/provincial ulations.
PRT INFORMATION
for transportation.
ific regulation.
ific regulation.
ORY INFORMATION
hazardous based on components.
ents of this product are listed on or exempt from the TSCA



## MATERIAL SAFETY DATA SHEET WHITE ETCH

Version Number 1.0 Revision Date 03/13/2007 Page 6 of 7 Print Date 11/26/2011

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition : WARNING! This product contains a chemical known to the State of California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Antimony trioxide	1309-64-4	0.10 - 1.00	17

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
1332-29-2	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Not determined
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed

:

# MATERIAL SAFETY DATA SHEET WHITE ETCH

POLYONE CORPORATION

Version Number 1.0 Revision Date 03/13/2007

Page 7 of 7 Print Date 11/26/2011

Philippines PICCS : Listed

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.