PolvOne

MATERIAL SAFETY DATA SHEET 97910 BL PE MASTERBATCH

Version Number 1.0 Revision Date 03/26/2007 Page 1 of 8 Print Date 11/27/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	97910 BL PE MASTERBATCH
Product code	:	CC10098395
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Quartz	14808-60-7	0.1 - 1
Carbon black	1333-86-4	1 - 5
Calcium carbonate	1317-65-3	10 - 30
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET 97910 BL PE MASTERBATCH

Version Number 1.0 Revision Date 03/26/2007 Page 2 of 8 Print Date 11/27/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists se medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should n be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material ir plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat

PolyOne.

MATERIAL SAFETY DATA SHEET 97910 BL PE MASTERBATCH

Version Number 1.0 Revision Date 03/26/2007 Page 3 of 8 Print Date 11/27/2011

Storage	:	only in areas with appropriate exhaust ventilation. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXF	OSUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practic Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 97910 BL PE MASTERBATCH

Version Number 1.0 Revision Date 03/26/2007 Page 4 of 8 Print Date 11/27/2011

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):	Total dust. as carbon black	ACGIH
	3.5 mg/m3	PEL:	Total dust. as carbon black	OSHA Z1
Quartz	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	0.1 mg/m3	Time Weighted Average (TWA):	Respirable.	Z3
	0.3 mg/m3	Time Weighted Average (TWA):	Total dust.	Z3
	0.1 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.025 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odour Melting point/range Boiling Point: Water solubility

	Solid pellets BLUE Very faint Not determined Not applicable
:	Not applicable
:	Insoluble

Evaporation rate Specific Gravity: Bulk density Vapour pressure Vapour density pH

- Not applicableNot determinedNot establishedNot applicableNot applicable
- : Not applicable

10. STABILITY AND REACTIVITY	
: Stable.	
: Will not occur.	
: Keep away from oxidizing agents and open flame. To avoid therm decomposition, do not overheat.	al
: Incompatible with strong acids and oxidizing agents.	
: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen	
:	 Stable. Will not occur. Keep away from oxidizing agents and open flame. To avoid therm decomposition, do not overheat. Incompatible with strong acids and oxidizing agents.

MATERIAL SAFETY DATA SHEET 97910 BL PE MASTERBATCH

Version Number 1.0 Revision Date 03/26/2007

Page 5 of 8 Print Date 11/27/2011

products

(NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Chemical Name Effect Target Organ	
14808-60-7	Quartz Systemic effects Eyes, Respiratory system		Eyes, Respiratory system.
1333-86-4	Carbon black	Systemic effects Eyes, Respiratory system.	
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14808-60-7	Quartz	no	1	no
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation. Long-term exposure may cause coughing, chest pain, diminished chest expansion and possibly silicosis, which is a scarring of the lungs.

Additional Health Hazard Information:

PolvOne

MATERIAL SAFETY DATA SHEET 97910 BL PE MASTERBATCH

Version Number 1.0 Revision Date 03/26/2007 Page 6 of 8 Print Date 11/27/2011

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

12. ECOLOGICAL INFORMATION

Environmental Toxicity	: Chemicals are not readily available as they are bound within the		
	polymer matrix.		
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.		
Additional advice	: no data available		
	13. DISPOSAL CONSIDERATIONS		
Product	: Like most thermoplastic plastics the product can be recycled. Wher possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
	14. TRANSPORT INFORMATION		
U.S. DOT Classification	: Not regulated for transportation.		
ICAO/IATA (air)	: Refer to specific regulation.		
IMO / IMDG (maritime)	: Refer to specific regulation.		
	15. REGULATORY INFORMATION		
US Regulations:			

PolyOne.

MATERIAL SAFETY DATA SHEET 97910 BL PE MASTERBATCH

sion Number 1.0 sion Date 03/26/2007			Pr	Page int Date 11/27/
OSHA Status	Classic	fied as horsedays hased on	acronomete	
OSHA Status	: Classi	fied as hazardous based on	components.	
TSCA Status		All components of this product are listed on or exempt from the TSCA Inventory.		
US. EPA CERCLA Hazardous	Substances	(40 CFR 302)		
Not applicable				
California Proposition 65	: Not ap	plicable		
SARA Title III Section 302 Ex	tremely Haz	ardous Substance		
Unless specific chemicals are id	dontified und	lar this social this produc	at is Not Applicabl	a under this requi
Oness spectric chemicars are fo	uentineu uno	ier uns section, uns produc	et is Not Applicabl	e under uns regu
SARA Title III Section 313 To			et is Not Applicabl	e under this regu
Unless specific chemicals are id Canadian Regulations:	dentified und	ler this section, this produc	ct is Not Applicabl	e under this regu
Unless specific chemicals are id Canadian Regulations: National Pollutant Relea	dentified und	ler this section, this produc		
Unless specific chemicals are id Canadian Regulations: <u>National Pollutant Relea</u> Chemical Name	dentified und	ler this section, this produc y (NPRI) CAS-No.	Weight %	NPRI ID#
Unless specific chemicals are id Canadian Regulations: National Pollutant Relea Chemical Name Aluminum oxide	dentified und	ler this section, this product (NPRI) CAS-No. 1344-28-1	Weight % 0.10 - 1.00	NPRI ID# 13
Unless specific chemicals are id Canadian Regulations: <u>National Pollutant Relea</u> Chemical Name	dentified und	ler this section, this produc y (NPRI) CAS-No.	Weight %	NPRI ID#
Unless specific chemicals are id Canadian Regulations: National Pollutant Relea Chemical Name Aluminum oxide Phthalocyanine blue Phthalocyanine green WHMIS Classification WHMIS Ingredient Diso CAS-No. 1333-86-4 147-14-8 1328-53-6	dentified und ase Inventory	ler this section, this product (NPRI) CAS-No. 1344-28-1 147-14-8	Weight % 0.10 - 1.00 1.00 - 5.00	NPRI ID# 13 71
Unless specific chemicals are id Canadian Regulations: National Pollutant Relea Chemical Name Aluminum oxide Phthalocyanine blue Phthalocyanine green WHMIS Classification WHMIS Ingredient Disc CAS-No. 1333-86-4 147-14-8	dentified und ase Inventory : D2A closure List	ler this section, this product (NPRI) CAS-No. 1344-28-1 147-14-8	Weight % 0.10 - 1.00 1.00 - 5.00 1.00 - 5.00	NPRI ID# 13 71 71 71

7/8

PolyOne

MATERIAL SAFETY DATA SHEET 97910 BL PE MASTERBATCH

Version Number 1.0 Revision Date 03/26/2007 Page 8 of 8 Print Date *11/27/2011*

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Listed
Korea KECI	:	Listed
Philippines PICCS	:	Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.