## MATERIAL SAFETY DATA SHEET 030UV2000 PVC

Version Number 1.0 Revision Date 03/27/2007

CAS-No.

Product Use

Page 1 of 8 Print Date 11/27/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	030UV2000 PVC
Product code	:	CC10098474
Chemical Name	:	Mixture

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS
7 COMPOSITION/INFORMATION ON REGULATED INCREDIENTS
2, COMI OSITION/INFORMATION ON REGULATED INGREDIENTS

Mixture

: Industrial Applications

:

Components	CAS-No.	Weight %
Aluminate (Al(OH)63-), (OC-6-11)-,	11097-59-9	1 - 5
magnesium carbonate hydroxide (2:6:1:4)		
1,6-Hexanediamine,	70624-18-9	5 - 10
N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-,		
polymer with 2,4,6-trichloro-1,3,5-triazine,		
reaction products		
Phenol,	25973-55-1	10 - 30
2-(2H-benzotriazol-2-yl)-4,6-bis(1,1-dimeth		
ylpropyl)-		
Quartz	14808-60-7	0.1 - 1
Calcium carbonate	1317-65-3	30 - 60

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Ingestion, Skin contact	
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating.



# MATERIAL SAFETY DATA SHEET 030UV2000 PVC

sion Number 1.0 ision Date 03/27/2007	Page 2 Print Date 11/27/2
Ingestion Eyes Skin	<ul> <li>Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.</li> <li>May be harmful if swallowed.</li> <li>Particulates, like other inert materials can be mechanically irritating.</li> <li>Experience shows no unusual dermatitis hazard from routine handling.</li> </ul>
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foamnone.</li> </ul>
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.



# MATERIAL SAFETY DATA SHEET 030UV2000 PVC

Version Number 1.0 Revision Date 03/27/2007		Page 3 of 8 Print Date 11/27/2011
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXPO	SUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne

### MATERIAL SAFETY DATA SHEET 030UV2000 PVC

Version Number 1.0 Revision Date 03/27/2007 Page 4 of 8 Print Date 11/27/2011

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Quartz	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	0.1 mg/m3	Time Weighted Average (TWA):	Respirable.	Z3
	0.3 mg/m3	Time Weighted Average (TWA):	Total dust.	Z3
	0.1 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.025 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odour Melting point/range Boiling Point: Water solubility

Solid
pellets
NO PIGMENT
Very faint
Not determined
Not applicable
Insoluble

#### Evaporation rate Specific Gravity: Bulk density Vapour pressure Vapour density pH

Not applicable
Not determined
Not established
Not applicable
Not applicable
Not applicable

### **10. STABILITY AND REACTIVITY**

Stability Hazardous Polymerization	:	Stable. Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon

PolyOne

## MATERIAL SAFETY DATA SHEET 030UV2000 PVC

Version Number 1.0 Revision Date 03/27/2007

Page 5 of 8 Print Date 11/27/2011

monoxide and hydrogen chloride.

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
11097-59-9	Aluminate (Al(OH)63-),	Irritant	Eyes, Skin.
	(OC-6-11)-, magnesium		
	carbonate hydroxide		
	(2:6:1:4)		
70624-18-9	1,6-Hexanediamine,	Irritant	Eyes, Skin, Respiratory system.
	N,N'-bis(2,2,6,6-tetrameth		
	yl-4-piperidinyl)-,polymer		
	with		
	2,4,6-trichloro-1,3,5-triazi		
	ne, reaction products		
25973-55-1	Phenol,	Systemic effects	Kidney, Liver, reproductive
	2-(2H-benzotriazol-2-yl)-4		system.
	,6-bis(1,1-dimethylpropyl)		
	-		
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine,	Oral LD50	> 2,000 mg/kg	rat
	N,N'-bis(2,2,6,6-tetrameth	Dermal LD50	> 3,000 mg/kg	rat
	yl-4-piperidinyl)-,polymer			
	with			
	2,4,6-trichloro-1,3,5-triazi			
	ne, reaction products			

#### Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14808-60-7	Quartz	no	1	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

## MATERIAL SAFETY DATA SHEET 030UV2000 PVC

Version Number 1.0 Revision Date 03/27/2007 Page 6 of 8 Print Date 11/27/2011

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### **Additional Health Hazard Information:**

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation. Long-term exposure may cause coughing, chest pain, diminished chest expansion and possibly silicosis, which is a scarring of the lungs.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.

### MATERIAL SAFETY DATA SHEET 030UV2000 PVC

Version Number 1.0						
Revision Date	03/27/2007					

Page 7 of 8 Print Date 11/27/2011

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Zinc stearate	557-05-1	0.10 - 1.00	231

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
11097-59-9	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed

:



# MATERIAL SAFETY DATA SHEET 030UV2000 PVC

Version Number 1.0 Revision Date 03/27/2007 Page 8 of 8 Print Date 11/27/2011

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.