### MATERIAL SAFETY DATA SHEET

### Keltec Grey

Version Number 1.0 Revision Date 03/28/2007 Page 1 of 6 Print Date 11/27/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	Keltec Grey
Product code	:	CC10098484
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	5 - 10
Titanium dioxide	13463-67-7	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to</li> </ul>
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



# MATERIAL SAFETY DATA SHEET *Keltec Grey*

Version Number 1.0 Revision Date 03/28/2007 Page 2 of 6 Print Date 11/27/2011

Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
<b>F</b> 1		
Flammable Limits Upper explosion limit		Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	:	Not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foamnone.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

2/6



# MATERIAL SAFETY DATA SHEET Keltec Grey

### Version Number 1.0 Revision Date 03/28/2007

Page 3 of 6 Print Date 11/27/2011

8. H	EXPOSURE	CONTROLS / PERSON	AL PROTECTION	
Respiratory protection	: N	lo personal respiratory pro	tective equipment normally	required.
Eye/Face Protection	: S	afety glasses with side-shi	elds	
Hand protection	: P	rotective gloves		
Skin and body protection	: L	ong sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations			good industrial hygiene and and at the end of workday.	safety practic
Engineering measures		leat only in areas with app ppropriate exhaust ventilat	ropriate exhaust ventilation tion at machinery.	. Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z
	15 mg/m3	PEL:	Total dust.	OSHA Z
	10 mg/m3	Time Weighted Averag (TWA):	ge	MX OEL
	20 mg/m3	Short Term Exposure Lin (STEL):	mit	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Averag (TWA):	ge	ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z
	20 mg/m3	Short Term Exposure Lin (STEL):	mit as Ti	MX OEL
	9. PHYSIC	CAL AND CHEMICAL	PROPERTIES	
Form	: Solic	l Ev	vaporation rate : No	ot applicable
Appearance	: pelle	ts Sp	ecific Gravity: : No	ot determined
Color	: GRE	Y Bi	ilk density : No	ot established
Odour			apour pressure : No	ot applicable
Melting point/range				ot applicable
Boiling Point:		applicable pH	I : No	ot applicable
Water solubility	: Insol	uble		
	10. 5	STABILITY AND REAC	CTIVITY	



### MATERIAL SAFETY DATA SHEET *Keltec Grey*

Version Number 1.0 Revision Date 03/28/2007

Page 4 of 6 Print Date 11/27/2011

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.



### MATERIAL SAFETY DATA SHEET *Keltec Grey*

Version Number 1.0 Page 5 of 6 Print Date 11/27/2011 Revision Date 03/28/2007 Additional advice : no data available 13. DISPOSAL CONSIDERATIONS Product : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material Contaminated packaging : has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. **14. TRANSPORT INFORMATION** U.S. DOT Classification : Not regulated for transportation. Refer to specific regulation. ICAO/IATA (air) : IMO / IMDG (maritime) : Refer to specific regulation. **15. REGULATORY INFORMATION US Regulations: OSHA Status** Classified as hazardous based on components. **TSCA Status** All components of this product are listed on or exempt from the TSCA : Inventory. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable California Proposition : Not applicable 65 SARA Title III Section 302 Extremely Hazardous Substance Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

PolyOne

# MATERIAL SAFETY DATA SHEET *Keltec Grey*

Version Number 1.0 Revision Date 03/28/2007

Page 6 of 6 Print Date 11/27/2011

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

Chemical Name			CAS-No.	Weight %	NPRI ID#
Aluminum oxide			1344-28-1	0.10 - 1.00	13
WHMIS Classification	:	D2A			
DSL	:		s of this product a (DSL) or are exe	are on the Canadia empt.	n Domestic
ational Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Listed			
Korea KECI	:	Listed			
Philippines PICCS	:	Listed			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.