MATERIAL SAFETY DATA SHEET

Magohany Pearl 160c

Version Number 1.0 Revision Date 04/03/2007 Page 1 of 6 Print Date 11/27/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	Magohany Pearl 160c
Product code	:	CC10098651
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Aluminum	7429-90-5	5 - 10
Iron oxide	1309-37-1	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET Magohany Pearl 160c

Version Number 1.0 Revision Date 04/03/2007 Page 2 of 6 Print Date 11/27/2011

Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
F 1		
Flammable Limits		Not applicable
Upper explosion limit Lower explosion limit	:	Not applicable Not applicable
Autoignition temperature	·	Not applicable
0 1	•	
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foamnone.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne
		contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

2/6

PolyOne.

MATERIAL SAFETY DATA SHEET Magohany Pearl 160c

Version Number 1.0 Revision Date 04/03/2007

_

Page 3 of 6 Print Date 11/27/2011

8. EXPOSURE CONTROLS / PERSONAL PROTECTION					
Respiratory protection	: N	lo personal respiratory protecti	ve equipment normally re	equired.	
Eye/Face Protection	: S	afety glasses with side-shields			
Hand protection	: P	rotective gloves			
Skin and body protection	: L	ong sleeved clothing			
Additional Protective Measures	: S	afety shoes			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)	Value	England time	European form	I inte	
Components Aluminum	Value	Exposure time	Exposure type	List:	
Aluminum	10 mg/m3	Time Weighted Average (TWA):	Dust.	ACGIH	
	15 mg/m3	PEL:	Total dust. as Al	0.0114 71	
				OSHA ZI	
				OSHA Z1 OSHA Z1	
	5 mg/m3 10 mg/m3	PEL: Time Weighted Average	Respirable dust. as Al Dust.	OSHA ZI OSHA ZI MX OEL	
Iron oxide	5 mg/m3	PEL: Time Weighted Average (TWA): Time Weighted Average	Respirable dust. as Al	OSHA Z1	
Iron oxide	5 mg/m3 10 mg/m3	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Limit	Respirable dust. as Al Dust.	OSHA Z1 MX OEL	
Iron oxide	5 mg/m3 10 mg/m3 5 mg/m3	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA):	Respirable dust. as Al Dust. as Fe	OSHA Z1 MX OEL MX OEL	
Iron oxide	5 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3 5 mg/m3	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): Time Weighted Average	Respirable dust. as Al Dust. as Fe as Fe Respirable fraction.	OSHA Z1 MX OEL MX OEL MX OEL	
	5 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3 5 mg/m3 9. PHYSIC	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): CAL AND CHEMICAL PRO	Respirable dust. as Al Dust. as Fe as Fe Respirable fraction.	OSHA Z1 MX OEL MX OEL MX OEL ACGIH	
Form	5 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3 5 mg/m3 9. PHYSIC : Solid	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): CAL AND CHEMICAL PRO	Respirable dust. as Al Dust. as Fe as Fe Respirable fraction. OPERTIES ration rate : Not a	OSHA Z1 MX OEL MX OEL MX OEL ACGIH	
Form Appearance	5 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3 5 mg/m3 9. PHYSIO : Solid : pelle	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO th Evapor ets Specific	Respirable dust. as Al Dust. as Fe as Fe Respirable fraction. OPERTIES ration rate : Not all ic Gravity: : Not all	OSHA Z1 MX OEL MX OEL MX OEL ACGIH applicable determined	
Form Appearance Color	5 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3 5 mg/m3 9. PHYSIO : Solid : pelle : BRC	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO the sets Specific OWN	Respirable dust. as Al Dust. as Fe as Fe Respirable fraction. DPERTIES ration rate : Not a size of a siz	OSHA Z1 MX OEL MX OEL MX OEL ACGIH applicable determined established	
Form Appearance Color Odour	5 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3 5 mg/m3 5 mg/m3 9. PHYSIO : Solid : pelle : BRC : Very	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): Time Weighted Average (TWA): Example CAL AND CHEMICAL PROPERTY ets Specific DWN Bulk d / faint Vapou	Respirable dust. as Al Dust. as Fe as Fe Respirable fraction. DPERTIES ration rate : Not a side of a sid	OSHA Z1 MX OEL MX OEL MX OEL ACGIH applicable determined	
Form Appearance Color	5 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3 5 mg/m3 5 mg/m3 9. PHYSIO : Solid : pelle : BRC : Very : Not	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): Time Weighted Average (TWA): Example CAL AND CHEMICAL PROPERTY ets Specific DWN Bulk d / faint Vapou	Respirable dust. as Al Dust. as Fe as Fe Respirable fraction. OPERTIES ration rate : Not and	OSHA Z1 MX OEL MX OEL MX OEL ACGIH applicable determined established applicable	

PolyOne

MATERIAL SAFETY DATA SHEET Magohany Pearl 160c

Version Number 1.0 Revision Date 04/03/2007 Page 4 of 6 Print Date 11/27/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	C	hemical Name	Effect	Target Organ	
7429-90-5	Alumir	num	Irritant	Skin, Respiratory system.	
			Systemic effects	Eyes, Skin, Respiratory system	
1309-37-1	Iron ox	ide	Systemic effects	Respiratory system.	
		12. ECOLOGIO	CAL INFORMATION	1	
Persistence and degradability :		: Not readily bi	iodegradable.		
Environmental Toxicity :			Chemicals are not readily available as they are bound within the polymer matrix.		
Bioaccumulation Potential :			Chemicals are not readily available as they are bound within the polymer matrix.		
Additional advice :		: no data availa	no data available		
		13. DISPOSAL	CONSIDERATIONS	6	
Product :		possible recyc generator of v classification,	cling is preferred to dis waste material has the r	product can be recycled. Where posal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations.	
Contaminated packaging :		has the respon	nsibility for proper was in accordance with app	e. The generator of waste material te classification, transportation licable federal, state/provincial	

PolyOne.

MATERIAL SAFETY DATA SHEET

Magohany Pearl 160c

Version Number 1.0 Revision Date 04/03/2007

Page 5 of 6 Print Date 11/27/2011

nents.
l on or exempt from the TSCA
t Applicable under this regulati
t Applicable under this regulati
t Applicable under this regulati

rutional i onatant recrease inventory (i (i ru))			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Aluminum	7429-90-5	5.00 - 10.00	12
Zinc ferrite brown spinel (C.I. Pigment Yellow	68187-51-9	5.00 - 10.00	231
119)			

PolyOne

MATERIAL SAFETY DATA SHEET

Magohany Pearl 160c

Version Number 1.0 Revision Date 04/03/2007 Page 6 of 6 Print Date 11/27/2011

	WHMIS Classification	:	D2B
	WHMIS Ingredient Disc	losu	re List
	CAS-No. 7429-90-5 1309-37-1		
	DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
Natio	nal Inventories:		
	Australia AICS	:	Listed
	China IECS	:	Listed
	Europe EINECS	:	Listed
	Japan ENCS	:	Not determined
	Korea KECI	:	Listed
	Philippines PICCS	:	Listed
			14 OTHED INFORMATION

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.