PolvOne

MATERIAL SAFETY DATA SHEET DK GRAY 520576

Version Number 1.1 Revision Date 04/13/2007

Page 1 of 7 Print Date 11/27/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DK GRAY 520576
Product code	:	CC10098728
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

: Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
1,6-Hexanediamine,	70624-18-9	5 - 10
N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-,		
polymer with 2,4,6-trichloro-1,3,5-triazine,		
reaction products		
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET **DK GRAY 520576**

Version Number 1.1 Revision Date 04/13/2007 Page 2 of 7 Print Date 11/27/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET **DK GRAY 520576**

Version Number 1.1 Revision Date 04/13/2007	Page 3 of 7 Print Date 11/27/2011
Handling :	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage :	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXPOSU	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection :	No personal respiratory protective equipment normally required.
Eye/Face Protection :	Safety glasses with side-shields
Hand protection :	Protective gloves
Skin and body protection :	Long sleeved clothing
Additional Protective : Measures	Safety shoes
General Hygiene : Considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures :	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous, fumed, crystal-free	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range Boiling Point:
- Solid
 pellets
 GREY
 Very faint
 Not determined
 Not applicable
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 Not applicable
 Not applicable
 Not applicable

P<u>olyOne</u>

MATERIAL SAFETY DATA SHEET DK GRAY 520576

Version Number 1.1 Revision Date 04/13/2007

_

Page 4 of 7 Print Date 11/27/2011

Water solubility	Insoluble	
	10. STABILITY AND REACTIVITY	
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.	
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.	
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products	Irritant	Eyes, Skin, Respiratory system.
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine,	Oral LD50	> 2,000 mg/kg	rat
	N,N'-bis(2,2,6,6-tetrameth	Dermal LD50	> 3,000 mg/kg	rat
	yl-4-piperidinyl)-,polymer			
	with			
	2,4,6-trichloro-1,3,5-triazi			
	ne, reaction products			
112945-52-5	Silica, amorphous, fumed,	Oral LD50	3,160 mg/kg	rat
	crystal-free			

Carcinogenicity

P<u>olyOne</u>

MATERIAL SAFETY DATA SHEET **DK GRAY 520576**

Version Number 1.1 Revision Date 04/13/2007

Page 5 of 7 Print Date 11/27/2011

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Persistence and degradability	: Not readily biodegradable.
reisistence and degradability	. Not readily blodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION

PolyOne.

MATERIAL SAFETY DATA SHEET **DK GRAY 520576**

sion Number 1.1 sion Date 04/13/2007				Pr	Page int Date 11/2	
US Regulations:						
OSHA Status	: Clas	ssified as ha	azardous based on	components.		
TSCA Status		component entory.	s of this product a	re listed on or exen	npt from the TS	SCA
US. EPA CERCLA Hazardous	Substance	es (40 CFR	302)			
Not applicable						
California Proposition 65	: Not	applicable				
SARA Title III Section 302 Ex	tremely H	lazardous Si	ubstance			
	-					
TT.1						1.
Unless specific chemicals are id SARA Title III Section 313 To			ection, this produc	t is Not Applicabl	e under this reg	gula
-	xic Chemi dentified ι	icals: under this se	-		-	
SARA Title III Section 313 To Unless specific chemicals are id Canadian Regulations: <u>National Pollutant Relea</u> Chemical Name	xic Chemi dentified u ase Invent	icals: under this se	ection, this produc	t is Not Applicabl	e under this reg	
SARA Title III Section 313 To Unless specific chemicals are in Canadian Regulations: National Pollutant Relea	xic Chemi dentified u ase Invent	icals: under this se	ection, this produc	t is Not Applicable Weight % 0.10 - 1.00	e under this reg NPRI ID# 69	
SARA Title III Section 313 To Unless specific chemicals are id Canadian Regulations: <u>National Pollutant Relea</u> Chemical Name	xic Chemi dentified u ase Invent	icals: under this se	ection, this produc	t is Not Applicabl	e under this reg	
SARA Title III Section 313 To Unless specific chemicals are id Canadian Regulations: <u>National Pollutant Relea</u> Chemical Name	xic Chemi dentified u ase Invent	icals: under this se ory (NPRI)	ection, this produc	t is Not Applicable Weight % 0.10 - 1.00	e under this reg NPRI ID# 69	
SARA Title III Section 313 To Unless specific chemicals are in Canadian Regulations: <u>National Pollutant Relea</u> <u>Chemical Name</u> <u>Rutile, antimony chromium b</u>	xic Chemi dentified u ase Invent buff : D24	icals: under this se ory (NPRI)	ection, this produc	t is Not Applicable Weight % 0.10 - 1.00	e under this reg NPRI ID# 69	
SARA Title III Section 313 To Unless specific chemicals are id Canadian Regulations: <u>National Pollutant Relea</u> <u>Chemical Name</u> <u>Rutile, antimony chromium b</u>	xic Chemi dentified u ase Invent buff : D24	icals: under this se ory (NPRI)	ection, this produc	t is Not Applicable Weight % 0.10 - 1.00	e under this reg NPRI ID# 69	
SARA Title III Section 313 To Unless specific chemicals are id Canadian Regulations: National Pollutant Relea Chemical Name Rutile, antimony chromium to WHMIS Classification WHMIS Ingredient Disc	xic Chemi dentified u ase Invente buff : D24 closure Li closure Li closure Li	icals: under this se ory (NPRI) A st of the com entories or a duct is on th	CAS-No. 68186-90-3 ponents of this pro re exempt. Howe the Canadian Non-J	t is Not Applicable Weight % 0.10 - 1.00	e under this reg	gulat
SARA Title III Section 313 To Unless specific chemicals are in Canadian Regulations: <u>National Pollutant Relea</u> <u>Chemical Name</u> <u>Rutile, antimony chromium b</u> WHMIS Classification WHMIS Ingredient Disc <u>CAS-No.</u> <u>112945-52-5</u>	xic Chemi dentified u ase Invente buff : D24 closure Li closure Li closure Li	icals: under this se ory (NPRI) A st of the com entories or a duct is on th	CAS-No. 68186-90-3 ponents of this pro re exempt. Howe the Canadian Non-J	t is Not Applicable Weight % 0.10 - 1.00 0.10 - 1.00 0.10 - 1.00	e under this reg	gula

PolyOne

MATERIAL SAFETY DATA SHEET **DK GRAY 520576**

Version Number 1.1 Revision Date 04/13/2007 Page 7 of 7 Print Date 11/27/2011

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.