PolvOne.

MATERIAL SAFETY DATA SHEET VC-22798 GOLD 125

Version Number 1.0 Revision Date 04/17/2007

Page 1 of 7 Print Date 11/27/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	VC-22798 GOLD 125
Product code	:	CC10099004
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

: Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Mica	12001-26-2	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.		
Ingestion	: May be harmful if swallowed.		
Eyes	: Particulates, like other inert materials can be mechanically irritating.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		

PolyOne.

MATERIAL SAFETY DATA SHEET VC-22798 GOLD 125

Version Number 1.0 Revision Date 04/17/2007 Page 2 of 7 Print Date 11/27/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May
Trazards	emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET VC-22798 GOLD 125

Version Number 1.0 Revision Date 04/17/2007		Page 3 of 7 Print Date <i>11/27/2011</i>			
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.			
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.			
8. EXP(OSUF	RE CONTROLS / PERSONAL PROTECTION			
Respiratory protection	:	No personal respiratory protective equipment normally required.			
Eye/Face Protection	:	Safety glasses with side-shields			
Hand protection	:	Protective gloves			
Skin and body protection	:	Long sleeved clothing			
Additional Protective Measures	:	Safety shoes			
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit		MX OEL
		(STEL):		
Mica	20 mppcf	PEL:	Total dust.	OSHA
	3 mg/m3	Time Weighted Average	Respirable fraction.	ACGIH
		(TWA):		
	3 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
		(STEL):		

9. PHYSICAL AND CHEMICAL PROPERTIES

PolvOne

MATERIAL SAFETY DATA SHEET VC-22798 GOLD 125

Version Number 1.0 Revision Date 04/17/2007 Page 4 of 7 Print Date 11/27/2011

Form	: Solid	Evaporation rate	:	Not applicable
Appearance	: pellets	Specific Gravity	:	Not determined
Color	: TAN	Bulk density	:	Not established
Odour	: Very faint	Vapour pressure	:	Not applicable
Melting point/range	: Not determined	Vapour density	:	
Boiling Point:	: Not applicable	pH	:	Not applicable
Water solubility	: Insoluble			
-				
	10. STABILITY AN	D REACTIVITY		

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
12001-26-2	Mica	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

PolyOne.

MATERIAL SAFETY DATA SHEET VC-22798 GOLD 125

Version Number 1.0 Revision Date 04/17/2007 Page 5 of 7 Print Date 11/27/2011

13463-67-7TitaniumIARC Carcinogen Classifications1 - The component is carcinogeni2A - The component is probably of2B - The component is possibly ofNTP Carcinogen Classifications:1 - The component is known to be2 - The component is reasonablyPersistence and degradability	: c to humans. carcinogenic to huma arcinogenic to huma e a human carcinogen anticipated to be a hu	ns. 1.	2B	no
 The component is carcinogeni 2A - The component is probably 2B - The component is possibly c NTP Carcinogen Classifications: 1 - The component is known to be 2 - The component is reasonably 	c to humans. carcinogenic to huma arcinogenic to huma e a human carcinogen anticipated to be a hu	ns. 1.		
Persistence and degradability		0		
Persistence and degradability	12. ECOLOGICAL	INFORMATION		
r ersistence und degradubility	: Not readily biode	egradable.		
Environmental Toxicity	: Chemicals are no polymer matrix.	t readily available as	they are bound w	vithin the
Bioaccumulation Potential	: Chemicals are no polymer matrix.	t readily available as	they are bound w	vithin the
Additional advice	: No data available			
	13. DISPOSAL CO	NSIDERATIONS		
Product	possible recyclin generator of was classification, tra	pplastic plastics the p g is preferred to disp e material has the re nsportation and disp l, state/provincial an	osal or incinerations sponsibility for prosal in accordance	on. The oper waste with
Contaminated packaging	has the responsib	erred when possible. ility for proper waste ccordance with appli ons.	e classification, tra	ansportation
	14. TRANSPORT	INFORMATION		
U.S. DOT Classification	: Not regulated for	transportation.		
ICAO/IATA (air)	: Refer to specific	regulation.		
IMO / IMDG (maritime)	: Refer to specific	regulation.		
	15. REGULATORY	INFORMATION		
US Regulations:				

PolyOne.

MATERIAL SAFETY DATA SHEET VC-22798 GOLD 125

rsion Number 1.0 vision Date 04/17/2007		Pr	Page 6 of 7 int Date 11/27/2011
OSHA Status : Classified as ha	zardous based on	components.	
TSCA Status : All component Inventory.	s of this product a	re listed on or exen	npt from the TSCA
US. EPA CERCLA Hazardous Substances (40 CFR	302)		
Not applicable			
California Proposition : Not applicable 65			
SARA Title III Section 302 Extremely Hazardous Su	ubstance		
Unless specific chemicals are identified under this se	ection, this produc	ct is Not Applicabl	e under this regulation
SARA Title III Section 313 Toxic Chemicals: Unless specific chemicals are identified under this se Canadian Regulations: National Pollutant Release Inventory (NPRI)	ection, this produc	ct is Not Applicabl	e under this regulatior
Chemical Name	CAS-No.	Weight %	NPRI ID#
Aluminum	7429-90-5	0.10 - 1.00	12
Inventories or a product is on th Quantity use in	re exempt. Howe e Canadian Non-	oduct are listed on ver, at least one co Domestic Substand ted by regulations.	omponent of this ces List (NDSL).
WHMIS Ingredient Disclosure List CAS-No. 12001-26-2 DSL : All of the complexity inventories or a product is on the Quantity use in t	re exempt. Howe e Canadian Non-	ver, at least one co Domestic Substanc	omponent of this ces List (NDSL).
WHMIS Ingredient Disclosure List CAS-No. 12001-26-2 DSL : All of the complexity inventories or a product is on the Quantity use in the the quantity of the quantity use in the qua	re exempt. Howe e Canadian Non-	ver, at least one co Domestic Substanc	omponent of this ces List (NDSL).
WHMIS Ingredient Disclosure List CAS-No. 12001-26-2 DSL : All of the complexity inventories or a product is on the Quantity use in the Statement of	re exempt. Howe e Canadian Non-	ver, at least one co Domestic Substanc	omponent of this ces List (NDSL).

PolyOne

MATERIAL SAFETY DATA SHEET VC-22798 GOLD 125

Version Number 1.0 Revision Date 04/17/2007 Page 7 of 7 Print Date *11/27/2011*

China IECS	:	Listed
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.