PolvOne

MATERIAL SAFETY DATA SHEET 030GN2018 TEAL

Version Number 1.0 Revision Date 04/18/2007

Page 1 of 8 Print Date 11/27/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| Telephone Emergency telephone number | : | Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|--|---|---|
| Product name | : | 030GN2018 TEAL |
| Product code | : | CC10099139 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |

CAS-No.:MixtureProduct Use:Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components | CAS-No. | Weight % |
|---|------------|----------|
| Aluminate (Al(OH)63-), (OC-6-11)-, magnesium carbonate hydroxide (2:6:1:4) | 11097-59-9 | 1 - 5 |
| Quartz | 14808-60-7 | 0.1 - 1 |
| Titanium dioxide | 13463-67-7 | 10 - 30 |
| Calcium carbonate | 1317-65-3 | 30 - 60 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Ingestion, Skin contact |
|---------------------|--|
| Acute exposure | |
| Inhalation | : Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system. |
| Ingestion | : May be harmful if swallowed. |
| Eyes | : Particulates, like other inert materials can be mechanically irritating. |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. |

PolyOne.

MATERIAL SAFETY DATA SHEET 030GN2018 TEAL

Version Number 1.0 Revision Date 04/18/2007 Page 2 of 8 Print Date 11/27/2011

| Medical Conditions : None known. Aggravated by Exposure: : | | | | |
|--|--|--|--|--|
| | 4. FIRST AID MEASURES | | | |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice. | | | |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. | | | |
| Eyes | : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention. | | | |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists see medical attention. | | | |
| | 5. FIRE-FIGHTING MEASURES | | | |
| Flash point | : Not applicable | | | |
| Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards | Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May | | | |
| | emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. | | | |
| | 6. ACCIDENTAL RELEASE MEASURES | | | |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. | | | |
| Environmental precautions | : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil. | | | |
| Methods for cleaning up | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods. | | | |

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET 030GN2018 TEAL

Version Number 1.0 Revision Date 04/18/2007 Page 3 of 8 Print Date 11/27/2011

| Handling | : | Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. |
|-----------------------------------|-------|--|
| Storage | : | Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. |
| 8. EXI | POSUF | RE CONTROLS / PERSONAL PROTECTION |
| Respiratory protection | : | No personal respiratory protective equipment normally required. |
| Eye/Face Protection | : | Safety glasses with side-shields |
| Hand protection | : | Protective gloves |
| Skin and body protection | : | Long sleeved clothing |
| Additional Protective Measures | : | Safety shoes |
| General Hygiene Considerations | : | Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday. |
| Engineering measures | : | Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. |
| Exposure limit(s) | | |

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 030GN2018 TEAL

Version Number 1.0 Revision Date 04/18/2007 Page 4 of 8 Print Date *11/27/2011*

| Components | Value | Exposure time | Exposure type | List: |
|-------------------|----------------|-----------------------------------|----------------------|---------|
| Calcium carbonate | 5 mg/m3 | PEL: | Respirable fraction. | OSHA Z1 |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 10 mg/m3 | Time Weighted Average (TWA): | | MX OEL |
| | 20 mg/m3 | Short Term Exposure Limit (STEL): | | MX OEL |
| Quartz | 5 mg/m3 | PEL: | Respirable fraction. | OSHA Z1 |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 0.1 mg/m3 | Time Weighted Average (TWA): | Respirable. | Z3 |
| | 0.3 mg/m3 | Time Weighted Average (TWA): | Total dust. | Z3 |
| | 0.1 mg/m3 | Time Weighted Average (TWA): | | MX OEL |
| | 0.025 mg/m3 | Time Weighted Average (TWA): | Respirable fraction. | ACGIH |
| Titanium dioxide | 10 mg/m3 | Time Weighted Average (TWA): | | ACGIH |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 10 mg/m3 | Time Weighted Average (TWA): | as Ti | MX OEL |
| | 20 mg/m3 | Short Term Exposure Limit (STEL): | as Ti | MX OEL |

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odour Melting point/range **Boiling Point:** Water solubility

: Solid pellets : GREEN

Very faint : : Not determined : Not applicable : Insoluble

:

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pН

- : Not applicable : Not determined Not established :
- Not applicable :
- : Not applicable
- : Not applicable

10. STABILITY AND REACTIVITY

| Stability | : | Stable. |
|--------------------------|---|---|
| Hazardous Polymerization | : | Will not occur. |
| Conditions to avoid | : | Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. |
| Incompatible Materials | : | Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace |

MATERIAL SAFETY DATA SHEET 030GN2018 TEAL

| Version Number 1.0 | Page 5 of 8 |
|--------------------------|---|
| Revision Date 04/18/2007 | Print Date <i>11/27/2011</i> |
| | quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks. |

Hazardous decomposition
products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
(NOx), hydrogen chloride (HCl), other hazardous materials, and
smoke are all possible. Prolonged heating (approximately 30 minutes
or more) above 392 °F (200 °C) or short term heating at 482 °F (250
°C) may result in product decomposition and evolution of carbon
monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|------------------------|------------------|---------------------------------|
| 11097-59-9 | Aluminate (Al(OH)63-), | Irritant | Eyes, Skin. |
| | (OC-6-11)-, magnesium | | |
| | carbonate hydroxide | | |
| | (2:6:1:4) | | |
| 14808-60-7 | Quartz | Systemic effects | Eyes, Respiratory system. |
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |
| 1317-65-3 | Calcium carbonate | Irritant | Eyes, Skin. |
| | | Systemic effects | Eyes, Skin, Respiratory system. |

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|------------|------------------|------|------|-----|
| 14808-60-7 | Quartz | no | 1 | no |
| 13463-67-7 | Titanium dioxide | no | 2B | no |

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation. Long-term exposure may cause coughing, chest pain, diminished chest expansion and possibly silicosis, which is a scarring of the lungs.

PolyOne.

MATERIAL SAFETY DATA SHEET 030GN2018 TEAL

Version Number 1.0 Revision Date 04/18/2007 Page 6 of 8 Print Date 11/27/2011

| Persistence and degradability | : Not readily biodegradable. |
|-------------------------------|---|
| Environmental Toxicity | : Chemicals are not readily available as they are bound within the polymer matrix. |
| Bioaccumulation Potential | : Chemicals are not readily available as they are bound within the polymer matrix. |
| Additional advice | : No data available |
| | 13. DISPOSAL CONSIDERATIONS |
| Product | : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| Contaminated packaging | : Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| | 14. TRANSPORT INFORMATION |
| U.S. DOT Classification | : Not regulated for transportation. |
| ICAO/IATA (air) | : Refer to specific regulation. |
| IMO / IMDG (maritime) | : Refer to specific regulation. |
| | 15. REGULATORY INFORMATION |
| US Regulations: | |
| OSHA Status | : Classified as hazardous based on components. |
| TSCA Status | : All components of this product are listed on or exempt from the TSCA Inventory. |
| US. EPA CERCLA Hazardous | Substances (40 CFR 302) |
| Not applicable | |
| | |

PolvOne

MATERIAL SAFETY DATA SHEET 030GN2018 TEAL

Version Number 1.0 Revision Date 04/18/2007 Page 7 of 8 Print Date 11/27/2011

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name | CAS-No. | Weight % | NPRI ID# |
|----------------------|------------|-------------|----------|
| Aluminum oxide | 1344-28-1 | 0.10 - 1.00 | 13 |
| Phthalocyanine blue | 147-14-8 | 1.00 - 5.00 | 71 |
| Phthalocyanine green | 1328-53-6 | 1.00 - 5.00 | 71 |
| Zinc iron oxide | 12063-19-3 | 0.10 - 1.00 | 231 |
| Zinc stearate | 557-05-1 | 0.10 - 1.00 | 231 |

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

| CAS-No. | |
|------------|--|
| 11097-59-9 | |
| 147-14-8 | |
| 1328-53-6 | |

:

DSL

All of the components of this product are listed on the Canadian Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations.

National Inventories:

| Australia AICS | : | Listed |
|----------------|---|----------------|
| China IECS | : | Listed |
| Europe EINECS | : | Listed |
| Japan ENCS | : | Not determined |

| P | bly | <i>O</i> t | ne. |
|---|-----|------------|-----|
| | | | |

MATERIAL SAFETY DATA SHEET 030GN2018 TEAL

Version Number 1.0 Revision Date 04/18/2007 Page 8 of 8 Print Date 11/27/2011

Korea KECI : Listed

Philippines PICCS : Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.