MATERIAL SAFETY DATA SHEET **PG 99892.00 OR PP**

Version Number 1.0 Revision Date 05/08/2007

Page 1 of 6 Print Date 11/28/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| Telephone Emergency telephone | : | Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|----------------------------------|---|---|
| Product name | : | PG 99892.00 OR PP |
| Product code | : | CC10099892 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |
| Product Use | : | Industrial Applications |

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components | CAS-No. | Weight % |
|-------------------|------------|----------|
| Titanium dioxide | 13463-67-7 | 1 - 5 |
| Calcium carbonate | 1317-65-3 | 10 - 30 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Ingestion, Skin contact | | |
|---|---|--|--|
| Acute exposure | | | |
| Inhalation Ingestion Eyes | Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to | | |
| Skin | eyes.Experience shows no unusual dermatitis hazard from routine handling. | | |
| Chronic exposure | : Refer to Section 11 for Toxicological Information. | | |
| Medical Conditions Aggravated by Exposure: | : None known. | | |

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 99892.00 OR PP**

Version Number 1.0 Revision Date 05/08/2007 Page 2 of 6 Print Date 11/28/2011

| | 4. FIRST AID MEASURES |
|---|--|
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists see medical attention. |
| | 5. FIRE-FIGHTING MEASURES |
| Flash point | : Not applicable |
| Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion | Not applicable Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen |
| Hazards | (NOx), other hazardous materials, and smoke are all possible. |
| | 6. ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil. |
| Methods for cleaning up | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods. |
| | 7. HANDLING AND STORAGE |
| Handling | : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. |
| Storage | : Keep containers dry and tightly closed to avoid moisture absorption |

2/6

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 99892.00 OR PP**

Version Number 1.0 Revision Date 05/08/2007 Page 3 of 6 Print Date 11/28/2011

| 8. E | XPOSURE | CONTROLS / PERSONAL | PROTECTION | | | |
|--------------------------------------|--|---|---|--|--|--|
| Respiratory protection | : N | : No personal respiratory protective equipment normally required. | | | | |
| Eye/Face Protection | : S | : Safety glasses with side-shields | | | | |
| Hand protection | : P | rotective gloves | | | | |
| Skin and body protection | : L | ong sleeved clothing | | | | |
| Additional Protective Measures | : S | afety shoes | | | | |
| General Hygiene Considerations | | landle in accordance with good Vash hands before breaks and a | | safety practic | | |
| Engineering measures | | leat only in areas with appropri ppropriate exhaust ventilation a | | Provide | | |
| Exposure limit(s) | | | | | | |
| Components | Value | Exposure time | Exposure type | List: | | |
| Calcium carbonate | 5 mg/m3 | PEL: | Respirable fraction. | OSHA Z | | |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z | | |
| | 10 mg/m3 | Time Weighted Average | | MX OEL | | |
| | 10 mg/m3 | (TWA): | | WIX OLL | | |
| | 20 mg/m3 | | | | | |
| Titanium dioxide | | (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): | | MX OEL | | |
| Titanium dioxide | 20 mg/m3 | (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: | Total dust. | MX OEL | | |
| Titanium dioxide | 20 mg/m3 10 mg/m3 | (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): | as Ti | ACGIH | | |
| Titanium dioxide | 20 mg/m3 10 mg/m3 15 mg/m3 | (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average | | ACGIH | | |
| Titanium dioxide | 20 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 | (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): | as Ti as Ti | MX OEL ACGIH OSHA Z MX OEL | | |
| Titanium dioxide | 20 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 | (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit | as Ti as Ti | MX OEL ACGIH OSHA Z MX OEL | | |
| Titanium dioxide | 20 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 | (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO | as Ti as Ti PERTIES | MX OEL ACGIH OSHA Z MX OEL MX OEL | | |
| Form | 20 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : Solic | (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO | as Ti as Ti DPERTIES ration rate : Not | MX OEL ACGIH OSHA Z MX OEL | | |
| | 20 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : Solic : pelle | (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO I Evapor Specifi | as Ti as Ti PPERTIES ration rate : Not ic Gravity : Not | MX OEL ACGIH OSHA Z MX OEL MX OEL | | |
| Form Appearance | 20 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSIC : Solic : pelle : ORA | (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO I Evapor ts Specifi NGE Bulk de | as Ti as Ti PPERTIES ration rate : Noi ic Gravity : Noi ensity : Noi | MX OEL ACGIH OSHA Z MX OEL MX OEL t applicable t determined t established | | |
| Form Appearance Color Odour | 20 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSIC : Solid : pelle : ORA : Very | (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO I Evapor ts Specifi NGE Bulk de faint | as Ti as Ti PPERTIES ration rate : Not ic Gravity : Not ensity : Not r pressure : Not | MX OEL ACGIH OSHA Z: MX OEL MX OEL MX OEL | | |
| Form Appearance Color | 20 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSIC : Solic : pelle : ORA : Very : Not of | (TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO I Evapor ts Specifi NGE Bulk de faint | as Ti as Ti PPERTIES ration rate : Not c Gravity : Not ensity : Not r pressure : Not r density : Not | MX OEL ACGIH OSHA Z MX OEL MX OEL t applicable t determined t established | | |

blvUn<u>e</u>

MATERIAL SAFETY DATA SHEET **PG 99892.00 OR PP**

Version Number 1.0 Revision Date 05/08/2007

Page 4 of 6 Print Date 11/28/2011

| Stability | : | Stable. |
|----------------------------------|---|--|
| Hazardous Polymerization | : | Will not occur. |
| Conditions to avoid | : | Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. |
| Incompatible Materials | : | Incompatible with strong acids and oxidizing agents. |
| Hazardous decomposition products | : | Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. |

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|-------------------|------------------|---------------------------------|
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |
| 1317-65-3 | Calcium carbonate | Irritant | Eyes, Skin. |
| | | Systemic effects | Eyes, Skin, Respiratory system. |

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|------------|------------------|------|------|-----|
| 13463-67-7 | Titanium dioxide | no | 2B | no |

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

| Persistence and degradability | : | Not readily biodegradable. |
|-------------------------------|---|--|
| Environmental Toxicity | : | Chemicals are not readily available as they are bound within the polymer matrix. |
| Bioaccumulation Potential | : | Chemicals are not readily available as they are bound within the |

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 99892.00 OR PP**

Version Number 1.0 Revision Date 05/08/2007 Page 5 of 6 Print Date 11/28/2011

| | polymer matrix. |
|--|---|
| Additional advice | : No data available |
| | 13. DISPOSAL CONSIDERATIONS |
| Product | Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| Contaminated packaging | : Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| | 14. TRANSPORT INFORMATION |
| | |
| U.S. DOT Classification | : Not regulated for transportation. |
| ICAO/IATA (air) | : Refer to specific regulation. |
| IMO / IMDG (maritime) | : Refer to specific regulation. |
| | 15. REGULATORY INFORMATION |
| US Regulations: | |
| OSHA Status | : Classified as hazardous based on components. |
| TSCA Status | : All components of this product are listed on or exempt from the TSCA Inventory. |
| US. EPA CERCLA Hazardo | us Substances (40 CFR 302) |
| Not applicable | |
| California Proposition 65 | n : Not applicable |
| SARA Title III Section 302 H | Extremely Hazardous Substance |
| TT 1 · · · · · · · · · · · · · · · · · · | identified under this section, this product is Not Applicable under this regula |

MATERIAL SAFETY DATA SHEET **PG 99892.00 OR PP**

Version Number 1.0 Revision Date 05/08/2007 Page 6 of 6 Print Date 11/28/2011

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

| CAS-No. | |
|----------|--|
| 150-13-0 | |

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

| Australia AICS | : | Listed |
|-------------------|---|----------------|
| China IECS | : | Listed |
| Europe EINECS | : | Not determined |
| Japan ENCS | : | Not determined |
| Korea KECI | : | Listed |
| Philippines PICCS | : | Listed |
| | | |

:

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.