### MATERIAL SAFETY DATA SHEET PINK 243C PET

Version Number 1.0 Revision Date 05/16/2007 Page 1 of 6 Print Date 11/28/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PINK 243C PET
Product code	:	CC10100075
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	30 - 60

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes Skin	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Particulates, like other inert materials can be mechanically irritating.</li> <li>Experience shows no unusual dermatitis hazard from routine handling.</li> </ul>		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		



# MATERIAL SAFETY DATA SHEET *PINK 243C PET*

Version Number 1.0 Revision Date 05/16/2007 Page 2 of 6 Print Date 11/28/2011

		4. FIRST AID MEASURES
Inhalation	(	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion		Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes		Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin		Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5.	FIRE-FIGHTING MEASURES
Flash point	: ]	Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	: 1 : 1	Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	1	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards		Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. AC	CIDENTAL RELEASE MEASURES
Personal precautions		Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions		Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	1	Clean up promptly by scoop or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7	. HANDLING AND STORAGE
Handling		Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	• 1	Keep containers dry and tightly closed to avoid moisture absorption

2/6

**POLYONE CORPORATION** 

PolyOne.

# MATERIAL SAFETY DATA SHEET **PINK 243C PET**

Version Number 1.0 Revision Date 05/16/2007 Page 3 of 6 Print Date 11/28/2011

8. ]	EXPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection		Vo personal respiratory protect usty conditions occur wear app		
Eye/Face Protection	: S	afety glasses		
Hand protection	: P	Protective gloves		
Skin and body protection	: L	long sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations	р	Vash hands and face before bre roduct. Handle in accordance ractice for diagnostics.		
Engineering measures		Heat only in areas with appropr ppropriate exhaust ventilation		Provide
Exposure limit(s)				
<u>Exposure mini(s)</u>				
0	X7 1			<b>T</b> • .
Components	Value	Exposure time	Exposure type	List:
Components Silica, amorphous	Value 0.8 mg/m3	Time Weighted Average	Exposure type	List: Z3
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
		Time Weighted Average (TWA): Time Weighted Average	Exposure type Inhalable particulate.	
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	0.8 mg/m3 10 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average	Inhalable particulate.	Z3 MX OEL
Silica, amorphous	0.8 mg/m3 10 mg/m3 3 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA):	Inhalable particulate.	Z3 MX OEL MX OEL
Silica, amorphous	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average	Inhalable particulate. Respirable dust.	Z3 MX OEL MX OEL ACGIH
Silica, amorphous	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL:	Inhalable particulate. Respirable dust. Total dust.	Z3 MX OEL MX OEL ACGIH OSHA Z1
Silica, amorphous	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit	Inhalable particulate. Respirable dust. Total dust. as Ti as Ti	Z3 MX OEL MX OEL ACGIH OSHA Z1 MX OEL
Silica, amorphous Titanium dioxide	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 <b>9. PHYSI</b> 0	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL):	Inhalable particulate. Respirable dust. Total dust. as Ti as Ti DPERTIES	Z3 MX OEL MX OEL ACGIH OSHA Z1 MX OEL MX OEL
Silica, amorphous Titanium dioxide Form	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 . Solid . Solid	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Inhalable particulate.         Respirable dust.         Total dust.         as Ti         as Ti         DPERTIES         ration rate       : Not	Z3 MX OEL MX OEL ACGIH OSHA Z1 MX OEL MX OEL applicable
Silica, amorphous Titanium dioxide Form Appearance	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSI0 : Solid : flake	Time Weighted Average (TWA):         Time Weighted Average (TWA):         Time Weighted Average (TWA):         Time Weighted Average (TWA):         PEL:         Time Weighted Average (TWA):         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRO         d       Evapo Specifi	Inhalable particulate.         Respirable dust.         Total dust.         as Ti         DPERTIES         ration rate       : Not         ic Gravity       : Not	Z3 MX OEL MX OEL ACGIH OSHA Z1 MX OEL MX OEL applicable determined
Silica, amorphous Titanium dioxide Form Appearance Color	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 <b>9. PHYSI</b> : Solic : flake : PIN	Time Weighted Average (TWA):         Time Weighted Average (TWA):         Time Weighted Average (TWA):         Time Weighted Average (TWA):         PEL:         Time Weighted Average (TWA):         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRO         d       Evapo         es       Specifik	Inhalable particulate.         Respirable dust.         Total dust.         as Ti         as Ti         OPERTIES         ration rate       : Not         ic Gravity       : Not         lensity       : Not	Z3 MX OEL MX OEL ACGIH OSHA Z1 MX OEL MX OEL MX OEL
Silica, amorphous Titanium dioxide Form Appearance Color Odour	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIO : Solia : flake : PIN : Very	Time Weighted Average (TWA):         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRO         d       Evapo         es       Specifik         K       Bulk of Vapor	Inhalable particulate.         Respirable dust.         Total dust.         as Ti         as Ti         OPERTIES         ration rate       : Not         Ic Gravity       : Not         lensity       : Not         respirable       : Not         respirable       : Not         ass Ti       : Not         ic Gravity       : Not         ic pressure       : Not	Z3 MX OEL MX OEL ACGIH OSHA Z1 MX OEL MX OEL MX OEL
Silica, amorphous	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSIO : Solio : flake : PINI : Very : Grea	Time Weighted Average (TWA):         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRO         d       Evapo         es       Specifik         K       Bulk of Vapor	Inhalable particulate.         Respirable dust.         Total dust.         as Ti         as Ti         OPERTIES         ration rate       : Not         ric Gravity       : Not         lensity       : Not         r pressure       : Not         r density       : Not	Z3 MX OEL MX OEL ACGIH OSHA Z1 MX OEL MX OEL MX OEL

# MATERIAL SAFETY DATA SHEET **PINK 243C PET**

Version Number 1.0 Revision Date 05/16/2007

Page 4 of 6 Print Date 11/28/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
7631-86-9	Silica, amorphous	Oral LD50Oral LD50	15,000 mg/kg22,500 mg/kg	mouserat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

PolyOne.

# MATERIAL SAFETY DATA SHEET **PINK 243C PET**

Version Number 1.0 Revision Date 05/16/2007 Page 5 of 6 Print Date 11/28/2011

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
<b>Bioaccumulation Potential</b>	: Not inherently biodegradable.
Additional advice	: Chemicals are not readily available as they are bound within the polymer matrix.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	

# MATERIAL SAFETY DATA SHEET **PINK 243C PET**

Version Number 1.0 Revision Date 05/16/2007

Page 6 of 6 Print Date 11/28/2011

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
7631-86-9	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Listed
Korea KECI	:	Listed
Philippines PICCS	:	Listed

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.