# MATERIAL SAFETY DATA SHEET **ROJO**

Version Number 1.0 Revision Date 08/01/2007 Page 1 of 6 Print Date 11/30/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| Telephone:Emergency telephone: |   | Product Stewardship (770) 271-5902<br>CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure<br>or accident). |
|--------------------------------|---|---|
| Product name                   | : | ROJO  |
| Product code                   | : | CC10100962  |
| Chemical Name                  | : | Mixture   |
| CAS-No.                        | : | Mixture   |
| Product Use                    | : | Industrial Applications   |

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components                              | CAS-No.    | Weight % |
|---|------------|----------|
| Aluminate (Al(OH)63-), (OC-6-11)-,      | 11097-59-9 | 1 - 5    |
| magnesium carbonate hydroxide (2:6:1:4) |            |          |
| Calcium carbonate                       | 1317-65-3  | 10 - 30  |

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | osure: : Inhalation, Ingestion, Skin contact   |  |  |
|---------------------|--|--|--|
| Acute exposure      |  |  |  |
| Inhalation          | : Particulates, like other inert materials can be mechanically irritating.<br>Excessive inhalation of product vapors, especially during heating or<br>processing, may be irritating to respiratory system. |  |  |
| Ingestion           | : May be harmful if swallowed.   |  |  |
| Eyes                | : Particulates, like other inert materials can be mechanically irritating.   |  |  |
| Skin                | : Experience shows no unusual dermatitis hazard from routine handling.   |  |  |
| Chronic exposure    | : Refer to Section 11 for Toxicological Information.   |  |  |



# MATERIAL SAFETY DATA SHEET **ROJO**

Version Number 1.0 Revision Date 08/01/2007 Page 2 of 6 Print Date 11/30/2011

| Aggravated by Exposure:  | 4. FIRST AID MEASURES  |
|--|--|
| Inhalation   | <ul> <li>Move to fresh air in case of accidental inhalation of fumes from<br/>overheating or combustion. When symptoms persist or in all cases of<br/>doubt seek medical advice.</li> </ul>  |
| Ingestion  | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.   |
| Eyes   | : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.   |
| Skin   | : Wash off with soap and plenty of water. If skin irritation persists see medical attention.   |
|  | 5. FIRE-FIGHTING MEASURES  |
| Flash point  | : Not applicable   |
| Flammable Limits<br>Upper explosion limit<br>Lower explosion limit<br>Autoignition temperature<br>Suitable extinguishing media<br>Special Fire Fighting<br>Procedures<br>Unusual Fire/Explosion<br>Hazards | <ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.</li> </ul> |
|  | 6. ACCIDENTAL RELEASE MEASURES   |
| Personal precautions   | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.   |
| Environmental precautions  | : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.   |
| Methods for cleaning up  | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.   |
|  | 7. HANDLING AND STORAGE  |



# MATERIAL SAFETY DATA SHEET **ROJO**

| ion Number 1.0<br>sion Date 08/01/2007  |   |   | Print D  | Page<br>ate 11/30/                                    |  |  |
|---|---|---|--|---|--|--|
| Handling  | : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. |   |  |   |  |  |
| Storage   | : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.       |   |  |   |  |  |
| 8. H  | EXPOSURE  | CONTROLS / PERSONA  | L PROTECTION   |   |  |  |
| Respiratory protection  | : N   | lo personal respiratory prote   | ective equipment normally  | required.   |  |  |
| Eye/Face Protection   | : S   | afety glasses with side-shiel   | ds   |   |  |  |
| Hand protection   | : P   | rotective gloves  |  |   |  |  |
| Skin and body protection  | : L   | ong sleeved clothing  |  |   |  |  |
| Additional Protective<br>Measures   | : S   | afety shoes   |  |   |  |  |
| General Hygiene<br>Considerations   |   | landle in accordance with go<br>Vash hands before breaks an             |  | afety practic   |  |  |
| Engineering measures  | : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.          |   |  |   |  |  |
| Exposure limit(s)   |   |   |  |   |  |  |
| Components  | Value   | Exposure time   | Exposure type  | List:   |  |  |
| Calcium carbonate   | 5 mg/m3   | PEL:  | Respirable fraction.   | OSHA Z  |  |  |
|   | 15 mg/m3  | PEL:  | Total dust.  | OSHA Z  |  |  |
|   | 10 mg/m3  | Time Weighted Average<br>(TWA):   |  | MX OEI  |  |  |
|   | 20 mg/m3  | Short Term Exposure Lim<br>(STEL):                                      | it   | MX OEI  |  |  |
|   | 9. PHYSIC   | CAL AND CHEMICAL P  | ROPERTIES  |   |  |  |
|   |   |   |  |   |  |  |
| Form  | : Solic   | i Eva   | poration rate : Not  | applicable  |  |  |
|   | : Solic<br>: pelle  |   | -  | applicable determined                                 |  |  |
| Appearance  |   | ts Spe  | cific Gravity : Not  | determined  |  |  |
| Appearance<br>Color   | : pelle<br>: RED<br>: Very  | ts Spe<br>9 Bul<br>9 faint Vap  | cific Gravity : Not<br>k density : Not<br>our pressure : Not                               | determined  |  |  |
| Appearance<br>Color<br>Odour<br>Melting point/range                           | : pelle<br>: RED<br>: Very<br>: Not o   | ts Spe<br>Bull<br>faint Vap<br>determined Vap                           | cific Gravity : Not<br>k density : Not<br>our pressure : Not<br>our density : Not          | determined<br>established<br>applicable<br>applicable |  |  |
| Form<br>Appearance<br>Color<br>Odour<br>Melting point/range<br>Boiling Point: | : pelle<br>: RED<br>: Very<br>: Not o<br>: Not o  | ts Spe<br>Bull<br>faint Vap<br>determined Vap<br>applicable pH          | cific Gravity : Not<br>k density : Not<br>our pressure : Not<br>our density : Not          | determined<br>established<br>applicable               |  |  |
| Appearance<br>Color<br>Odour<br>Melting point/range<br>Boiling Point:         | : pelle<br>: RED<br>: Very<br>: Not o   | ts Spe<br>Bull<br>faint Vap<br>determined Vap<br>applicable pH          | cific Gravity : Not<br>k density : Not<br>our pressure : Not<br>our density : Not          | determined<br>established<br>applicable<br>applicable |  |  |
| Appearance<br>Color<br>Odour<br>Melting point/range<br>Boiling Point:         | : pelle<br>: RED<br>: Very<br>: Not o<br>: Not o<br>: Insol   | ts Spe<br>Bull<br>faint Vap<br>determined Vap<br>applicable pH          | cific Gravity : Not<br>k density : Not<br>our pressure : Not<br>our density : Not<br>: Not | determined<br>established<br>applicable<br>applicable |  |  |
| Appearance<br>Color<br>Odour<br>Melting point/range                           | : pelle<br>: RED<br>: Very<br>: Not o<br>: Not a<br>: Insol   | ts Spe<br>Bull<br>faint Vap<br>determined Vap<br>applicable pH<br>luble | cific Gravity : Not<br>k density : Not<br>our pressure : Not<br>our density : Not<br>: Not | determined<br>established<br>applicable<br>applicable |  |  |

<u>PolyOne</u>

## **MATERIAL SAFETY DATA SHEET** ROJO

| Version Number 1.0<br>Revision Date 08/01/2007 |   | Page 4 of 6<br>Print Date 11/30/2011   |
|--|---|--|
|  |   |  |
| Hazardous Polymerization                       | : | Will not occur.  |
| Conditions to avoid                            | : | Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.   |
| Incompatible Materials                         | : | Avoid contact with strong oxidizers. Also, avoid contact with acetal or<br>acetal copolymers and with amine containing materials during<br>processing. At processing conditions, these materials are mutually<br>destructive and involve rapid degradation. Thoroughly purge and<br>mechanically clean processing equipment to avoid even trace<br>quantities of these materials from coming in contact with each other.<br>Prevent cross contamination of feedstocks. |
| Hazardous decomposition products               | : | Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.  |

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

| CAS-No.    | Chemical Name                             | Effect           | Target Organ                    |  |
|------------|---|------------------|---------------------------------|--|
| 11097-59-9 | Aluminate (Al(OH)63-),                    | Irritant         | Eyes, Skin.                     |  |
|            | (OC-6-11)-, magnesium carbonate hydroxide |                  |                                 |  |
|            | (2:6:1:4)                                 |                  |                                 |  |
| 1317-65-3  | Calcium carbonate                         | Irritant         | Eyes, Skin.                     |  |
|            |   | Systemic effects | Eyes, Skin, Respiratory system. |  |

|             |                     | 12 | 2. ECOLOGICAL INFORMATION  |  |
|-------------|---------------------|----|--|--|
| Persistence | e and degradability | :  | Not readily biodegradable.   |  |
| Environme   | ental Toxicity      | :  | Chemicals are not readily available as they are bound within the polymer matrix. |  |
| Bioaccum    | ulation Potential   | :  | Chemicals are not readily available as they are bound within the polymer matrix. |  |
| Additional  | l advice            | :  | No data available  |  |
|             |                     | 1. | 3. DISPOSAL CONSIDERATIONS   |  |



# MATERIAL SAFETY DATA SHEET **ROJO**

|                               | Page 5 c<br>Print Date 11/30/20   |
|-------------------------------|---|
|                               |   |
| Product                       | : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| Contaminated packaging        | : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.  |
|                               | 14. TRANSPORT INFORMATION   |
|                               |   |
| U.S. DOT Classification       | : Not regulated for transportation.   |
| ICAO/IATA (air)               | : Refer to specific regulation.   |
| IMO / IMDG (maritime)         | : Refer to specific regulation.   |
|                               | 15. REGULATORY INFORMATION  |
| US Regulations:               |   |
| OSHA Status                   | : Classified as hazardous based on components.  |
| TSCA Status                   | : All components of this product are listed on or exempt from the TSCA Inventory.   |
| US. EPA CERCLA Hazardou       | us Substances (40 CFR 302)  |
| Not applicable                |   |
|                               |   |
| California Propositior<br>65  | n : Not applicable  |
| SARA Title III Section 302 F  | Extremely Hazardous Substance   |
| Unless specific chemicals are | e identified under this section, this product is Not Applicable under this regulat  |
|                               | Covic Chamicale:  |
| SARA Title III Section 313 T  | oxic Chemicals.   |

<u>PolyOne</u>

# MATERIAL SAFETY DATA SHEET **ROJO**

| Version Number 1.0<br>Revision Date 08/01/2007              |   | Print D                             | Page 6 of 6<br>ate 11/30/2011 |  |  |  |  |
|---|---|-------------------------------------|-------------------------------|--|--|--|--|
| Canadian Regulations:                                       |   |                                     |                               |  |  |  |  |
| National Pollutant Release Inventory (NPRI<br>Chemical Name | CAS-No.                                   | Weight % N                          | PRI ID#                       |  |  |  |  |
| Zinc stearate   | 557-05-1                                  | 0.10 - 1.00 23                      |                               |  |  |  |  |
|   | nts of this product<br>st (DSL) or are ex | t are on the Canadian Doc<br>kempt. | mestic                        |  |  |  |  |
| National Inventories:                                       |   |                                     |                               |  |  |  |  |
| Australia AICS : Listed                                     |   |                                     |                               |  |  |  |  |
| China IECS : Listed   |   |                                     |                               |  |  |  |  |
| Europe EINECS : Not determine                               | ed  |                                     |                               |  |  |  |  |
| Japan ENCS : Not determine                                  | ed  |                                     |                               |  |  |  |  |
| Korea KECI : Listed   |   |                                     |                               |  |  |  |  |
| Philippines PICCS : Listed                                  |   |                                     |                               |  |  |  |  |
| 16. OTHER   | INFORMATIO                                | N                                   |                               |  |  |  |  |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.