## MATERIAL SAFETY DATA SHEET

## Salmon Pink #2

Version Number 1.0 Revision Date 06/14/2007 Page 1 of 6 Print Date 11/29/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	Salmon Pink #2
Product code :	CC10101158
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

## 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	10 - 30
Titanium dioxide	13463-67-7	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to</li> </ul>		
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		



# MATERIAL SAFETY DATA SHEET

# Salmon Pink #2

Version Number 1.0 Revision Date 06/14/2007 Page 2 of 6 Print Date 11/29/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards Personal precautions	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> <li>ACCIDENTAL RELEASE MEASURES</li> <li>Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.</li> </ul>
Environmental precautions	<ul> <li>Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.</li> </ul>
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
	: Keep containers dry and tightly closed to avoid moisture absorption

2/6



# MATERIAL SAFETY DATA SHEET Salmon Pink #2

Version Number 1.0 Revision Date 06/14/2007

\_\_\_\_

\_\_\_\_

Page 3 of 6 Print Date 11/29/2011

Considerations       Wash hands before breaks and at the end of workday.         Engineering measures       : Heat only in areas with appropriate exhaust ventilation. appropriate exhaust ventilation at machinery.         Exposure limit(s) <ul> <li>Components</li> <li>Value</li> <li>Exposure time</li> <li>Exposure type</li> <li>Calcium carbonate</li> <li>5 mg/m3</li> <li>PEL:</li> <li>Respirable fraction.</li> <li>15 mg/m3</li> <li>PEL:</li> <li>Total dust.</li> <li>10 mg/m3</li> <li>Time Weighted Average (TWA):</li> <li>20 mg/m3</li> <li>Short Term Exposure Limit (STEL):</li> <li>Titanium dioxide</li> <li>10 mg/m3</li> <li>Time Weighted Average (TWA):</li> <li>15 mg/m3</li> <li>PEL:</li> <li>Total dust.</li> </ul> 10 mg/m3           Time Weighted Average (TWA):           15 mg/m3         PEL:           Titanium dioxide         10 mg/m3           10 mg/m3         Time Weighted Average as Ti (TWA):           20 mg/m3         Short Term Exposure Limit as Ti (STEL):           9. PHYSICAL AND CHEMICAL PROPERTIES           Form         : Solid         Evaporation rate         : Not a specific Gravity         : Not a specific Gravity           Appearance         : pellets         Specific Gravity         : Not a specific Gravity         : Not a spe	and contamination. Keep in a dry, cool place.				
Eye/Face Protection       :       Safety glasses with side-shields         Hand protection       :       Protective gloves         Skin and body protection       :       Long sleeved clothing         Additional Protective       :       Safety shoes         Measures       :       Handle in accordance with good industrial hygiene and sa Wash hands before breaks and at the end of workday.         Engineering measures       :       Heat only in areas with appropriate exhaust ventilation. : appropriate exhaust ventilation at machinery.         Exposure limit(s)       :       Respirable fraction. : appropriate exhaust ventilation at machinery.         Exposure limit(s)       :       Respirable fraction. : (TWA): : Total dust. : 10 mg/m3         Pittanium dioxide       10 mg/m3       Short Term Exposure Limit (STEL): : Total dust. : 11 mg/m3         Titanium dioxide       10 mg/m3       Time Weighted Average (TWA): : (STEL): : (Total dust. : 10 mg/m3         Short Term Exposure Limit (STEL):       : 20 mg/m3       Short Term Exposure Limit (STEL): : (STE					
Hand protection       :       Protective gloves         Skin and body protection       :       Long sleeved clothing         Additional Protective       :       Safety shoes         Measures       :       Safety shoes         General Hygiene       :       Handle in accordance with good industrial hygiene and sa Considerations         Considerations       :       Heat only in areas with appropriate exhaust ventilation. appropriate exhaust ventilation at machinery.         Engineering measures       :       Heat only in areas with appropriate exhaust ventilation. appropriate exhaust ventilation at machinery.         Exposure limit(s)       :       Respirable fraction.         Components       Value       Exposure time       Exposure type         Calcium carbonate       5 mg/m3       PEL:       Total dust.         10 mg/m3       Time Weighted Average (TWA):	ive equipment normally required.				
Skin and body protection       :       Long sleeved clothing         Additional Protective       :       Safety shoes         Measures       :       Handle in accordance with good industrial hygiene and sa         Considerations       :       Heat only in areas with appropriate exhaust ventilation. : appropriate exhaust ventilation at machinery.         Engineering measures       :       Heat only in areas with appropriate exhaust ventilation. : appropriate exhaust ventilation at machinery.         Exposure limit(s)       :       Respirable fraction.         Components       Value       Exposure time       Exposure type         Calcium carbonate       5 mg/m3       PEL:       Total dust.         10 mg/m3       Time Weighted Average (TWA):					
Additional Protective Measures       : Safety shoes         General Hygiene Considerations       : Handle in accordance with good industrial hygiene and sa Wash hands before breaks and at the end of workday.         Engineering measures       : Heat only in areas with appropriate exhaust ventilation. : appropriate exhaust ventilation at machinery.         Exposure limit(s)       : Heat only in areas with appropriate exhaust ventilation. : appropriate exhaust ventilation at machinery.         Exposure limit(s)       : Respirable fraction.         Components       Value       Exposure time       Exposure type         Calcium carbonate       5 mg/m3       PEL:       Total dust.         10 mg/m3       Time Weighted Average (TWA):       :       :         20 mg/m3       Short Term Exposure Limit (STEL):       :       :         Titanium dioxide       10 mg/m3       Time Weighted Average (TWA):       :       :         20 mg/m3       Short Term Exposure Limit (STEL):       :       :       :         10 mg/m3       Time Weighted Average (TWA):       :       :       :         20 mg/m3       Short Term Exposure Limit (STEL):       :       :       :         9. PHYSICAL AND CHEMICAL PROPERTIES       :       :       :       :         6. Ordor       :       PINK       Bulk density					
Measures					
Considerations       Wash hands before breaks and at the end of workday.         Engineering measures       : Heat only in areas with appropriate exhaust ventilation. appropriate exhaust ventilation at machinery.         Exposure limit(s)         Components       Value         Exposure limit(s)         Components       Value         Exposure limit(s)         Components       Value         Exposure time       Exposure type         Calcium carbonate       5 mg/m3         PEL:       Respirable fraction.         15 mg/m3       PEL:         10 mg/m3       Time Weighted Average (TWA):         20 mg/m3       Short Term Exposure Limit (STEL):         Titanium dioxide       10 mg/m3         15 mg/m3       PEL:         Total dust.       10 mg/m3         Time Weighted Average (TWA):       Total dust.         10 mg/m3       Time Weighted Average (TWA):         20 mg/m3       Short Term Exposure Limit (STEL):         20 mg/m3       Short Term Exposure Limit (STEL):         9. PHYSICAL AND CHEMICAL PROPERTIES         Form       : Solid       Evaporation rate       : Not a (Stell         Appearance       : pellets       Specific Gravity       : Not of Odour         Odour<					
appropriate exhaust ventilation at machinery.         Exposure limit(s)         Components       Value       Exposure time       Exposure type         Calcium carbonate       5 mg/m3       PEL:       Respirable fraction.         15 mg/m3       PEL:       Total dust.         10 mg/m3       Time Weighted Average (TWA):       Image: Component of the second of the seco	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Components         Value         Exposure time         Exposure type           Calcium carbonate         5 mg/m3         PEL:         Respirable fraction.           15 mg/m3         PEL:         Total dust.           10 mg/m3         Time Weighted Average (TWA):         Total dust.           20 mg/m3         Short Term Exposure Limit (STEL):         Image: Component State St					
Calcium carbonate       5 mg/m3       PEL:       Respirable fraction.         15 mg/m3       PEL:       Total dust.       10 mg/m3         10 mg/m3       Time Weighted Average (TWA):       10 mg/m3       10 mg/m3         20 mg/m3       Short Term Exposure Limit (STEL):       10 mg/m3       10 mg/m3         Titanium dioxide       10 mg/m3       Time Weighted Average (TWA):       15 mg/m3         15 mg/m3       PEL:       Total dust.         10 mg/m3       Time Weighted Average (TWA):       10 mg/m3         10 mg/m3       Time Weighted Average (TWA):       10 mg/m3         10 mg/m3       Short Term Exposure Limit (STEL):       as Ti         10 mg/m3       Short Term Exposure Limit (STEL):       as Ti         20 mg/m3       Short Term Exposure Limit (STEL):       as Ti         20 mg/m3       Short Term Exposure Limit (STEL):       as Ti         9. PHYSICAL AND CHEMICAL PROPERTIES       Form       : Solid       Evaporation rate       : Not at the properties of the properime of the properties of the properties of the properimore of the					
Calcium carbonate       5 mg/m3       PEL:       Respirable fraction.         15 mg/m3       PEL:       Total dust.       10 mg/m3         10 mg/m3       Time Weighted Average (TWA):       10 mg/m3       10 mg/m3         20 mg/m3       Short Term Exposure Limit (STEL):       10 mg/m3       10 mg/m3         Titanium dioxide       10 mg/m3       Time Weighted Average (TWA):       15 mg/m3         15 mg/m3       PEL:       Total dust.         10 mg/m3       Time Weighted Average (TWA):       10 mg/m3         10 mg/m3       Time Weighted Average (TWA):       10 mg/m3         10 mg/m3       Short Term Exposure Limit (STEL):       as Ti         10 mg/m3       Short Term Exposure Limit (STEL):       as Ti         20 mg/m3       Short Term Exposure Limit (STEL):       as Ti         20 mg/m3       Short Term Exposure Limit (STEL):       as Ti         9. PHYSICAL AND CHEMICAL PROPERTIES       Form       : Solid       Evaporation rate : Not at the second se	List:				
15 mg/m3       PEL:       Total dust.         10 mg/m3       Time Weighted Average (TWA):       Item Weighted Average (TWA):         20 mg/m3       Short Term Exposure Limit (STEL):       Item Weighted Average (TWA):         Titanium dioxide       10 mg/m3       Time Weighted Average (TWA):         15 mg/m3       PEL:       Total dust.         10 mg/m3       Time Weighted Average (TWA):       as Ti         10 mg/m3       Time Weighted Average (TWA):       as Ti         20 mg/m3       Short Term Exposure Limit (STEL):       as Ti         20 mg/m3       Short Term Exposure Limit (STEL):       as Ti         PHYSICAL AND CHEMICAL PROPERTIES         Form       : Solid         Evaporation rate       : Not at the properties         Form       : Solid         Evaporation rate       : Not at the properties         Form       : Solid       Evaporation rate       : Not at the properties         Form       : Solid       Evaporation rate       : Not at the properties         Color       : PINK       Bulk density       : Not at the properties         Color       : Very faint       Vapour pressure       : Not at the properties <td>OSHA Z1</td>	OSHA Z1				
10 mg/m3       Time Weighted Average (TWA):         20 mg/m3       Short Term Exposure Limit (STEL):         Titanium dioxide       10 mg/m3         15 mg/m3       PEL:         15 mg/m3       PEL:         Time Weighted Average (TWA):         10 mg/m3       Time Weighted Average (TWA):         10 mg/m3       Time Weighted Average (TWA):         20 mg/m3       Short Term Exposure Limit (STEL):         20 mg/m3       Short Term Exposure Limit (STEL):         9. PHYSICAL AND CHEMICAL PROPERTIES         Form       : Solid         Evaporation rate       : Not a Color         : PINK       Bulk density       : Not a Short         Odour       : Very faint       Vapour pressure	OSHA Z1				
20 mg/m3       Short Term Exposure Limit (STEL):         Titanium dioxide       10 mg/m3         Time Weighted Average (TWA):         15 mg/m3       PEL:         Total dust.         10 mg/m3       Time Weighted Average (TWA):         10 mg/m3       Time Weighted Average (TWA):         20 mg/m3       Short Term Exposure Limit (STEL):         20 mg/m3       Short Term Exposure Limit (STEL):         9. PHYSICAL AND CHEMICAL PROPERTIES         Form       : Solid         Evaporation rate       : Not a Appearance         : pellets       Specific Gravity         : PINK       Bulk density       : Not a Not a         Odour       : Very faint       Vapour pressure	MX OEL				
Titanium dioxide       10 mg/m3       Time Weighted Average (TWA):         15 mg/m3       PEL:       Total dust.         10 mg/m3       Time Weighted Average as Ti (TWA):       as Ti         20 mg/m3       Short Term Exposure Limit (STEL):       as Ti         9. PHYSICAL AND CHEMICAL PROPERTIES         Form : Solid       Evaporation rate : Not a Appearance : pellets         20 or : PINK       Bulk density : Not of Odour         Odour       : Very faint       Vapour pressure : Not a State	MX OEL				
15 mg/m3       PEL:       Total dust.         10 mg/m3       Time Weighted Average (TWA):       as Ti         20 mg/m3       Short Term Exposure Limit (STEL):       as Ti         9. PHYSICAL AND CHEMICAL PROPERTIES         Form       :       Solid       Evaporation rate       :       Not at a strict of the strict	ACGIH				
10 mg/m3       Time Weighted Average (TWA):       as Ti         20 mg/m3       Short Term Exposure Limit (STEL):       as Ti         9. PHYSICAL AND CHEMICAL PROPERTIES         Form : Solid Evaporation rate : Not a Appearance : pellets Specific Gravity : Not a Color : PINK Bulk density : Not a Odour : Very faint Vapour pressure : Not a					
Image: constraint of the system of the sy	OSHA Z1				
(STEL):         9. PHYSICAL AND CHEMICAL PROPERTIES         Form       :       Solid       Evaporation rate       :       Not and a colspan="2">Not a colspan="2"         Form       :       Solid       Evaporation rate       :       Not a colspan="2">Not a colspan="2"         Form       :       Solid       Evaporation rate       :       Not a colspan="2">Not a colspan="2"         Form       :       Solid       Evaporation rate       :       Not a colspan="2">Not a colspan="2"         Color       :       PINK       Bulk density       :       Not a colspan="2">Not a colspan="2"         Odour       :       Very faint       Vapour pressure       :       Not a colspan="2">Not a colspan="2"	MX OEL				
Form: SolidEvaporation rate: Not aAppearance: pelletsSpecific Gravity: Not aColor: PINKBulk density: Not aOdour: Very faintVapour pressure: Not a	MX OEL				
Appearance: pelletsSpecific Gravity: Not ofColor: PINKBulk density: Not ofOdour: Very faintVapour pressure: Not of					
Appearance: pelletsSpecific Gravity: Not ofColor: PINKBulk density: Not ofOdour: Very faintVapour pressure: Not of					
Color: PINKBulk density: Not ofOdour: Very faintVapour pressure: Not a	applicable determined				
Odour : Very faint Vapour pressure : Not a	established				
Malting point/range · Not determined Vapour density · Not	applicable applicable				
	applicable				
Water solubility : Insoluble	applicable				

## **10. STABILITY AND REACTIVITY**

'olyOne

# MATERIAL SAFETY DATA SHEET

# Salmon Pink #2

Version Number 1.0 Revision Date 06/14/2007	Page 4 of 6 Print Date 11/29/2011
Stability	Stable.
Hazardous Polymerization :	Will not occur.
Conditions to avoid :	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials :	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition : products	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

## 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the



# MATERIAL SAFETY DATA SHEET

## Salmon Pink #2

Version Number 1.0 Revision Date 06/14/2007 Page 5 of 6 Print Date 11/29/2011

	polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Wher possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSC Inventory.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
Not applicable	
California Proposition 65	n : Not applicable
SARA Title III Section 302 I	Extremely Hazardous Substance
Unless specific chemicals are	

POLYONE CORPORATION

*PolyOne* 

# MATERIAL SAFETY DATA SHEET Salmon Pink #2

Version Number 1.0	Page 6 of 6
Revision Date 06/14/2007	Print Date 11/29/2011
SARA Title III Section 313 Toxic Chemicals:	
Unless specific chemicals are identified under this sectio	on, this product is Not Applicable under this regulation
Canadian Regulations:	
National Pollutant Release Inventory (NPRI)	
Not applicable	

WHMIS Classification	:	D2A
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

		· · · ·
Philippines PICCS	: Listed	
Korea KECI	: Listed	
Japan ENCS	: Not determined	
Europe EINECS	: Not determined	
China IECS	: Listed	
Australia AICS	: Listed	

## **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.