# MATERIAL SAFETY DATA SHEET **PG 101502.00 IY APET**

Version Number 1.0 Revision Date 06/22/2007

Page 1 of 7 Print Date 11/29/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	PG 101502.00 IY APET
Product code :	CC10101502
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	<ul><li>Resin particles, like other inert materials, can be mechanically irritating.</li><li>May be harmful if swallowed.</li></ul>
Eyes Skin	<ul> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> <li>Experience shows no unusual dermatitis bezord from routing handling</li> </ul>
SKII	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

# MATERIAL SAFETY DATA SHEET **PG 101502.00 IY APET**

Version Number 1.0 Revision Date 06/22/2007 Page 2 of 7 Print Date 11/29/2011

	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all case doubt seek medical advice.	s of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	;
Eyes	: Rinse immediately with plenty of water, also under the eyelids, fo least 15 minutes. If eye irritation persists, seek medical attention.	r at
Skin	: Wash off with soap and plenty of water. If skin irritation persists medical attention.	seek
	5. FIRE-FIGHTING MEASURES	_
Flash point	: Not applicable	
Flammable Limits		
Upper explosion limit	: Not applicable	
Lower explosion limit	: Not applicable	
Autoignition temperature	: Not applicable	
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positi pressure mode should be worn to prevent inhalation of airborne contaminants.	ve
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	
	5. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should be allowed to enter drains, water courses or the soil.	not
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material plastic, cardboard or metal containers for disposal. Refer to Sectio of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. Here only in areas with appropriate exhaust ventilation.	ıt
Storage	: Keep containers dry and tightly closed to avoid moisture absorption	n

PolyOne.

## MATERIAL SAFETY DATA SHEET PG 101502.00 IY APET

Version Number 1.0 Revision Date 06/22/2007 Page 3 of 7 Print Date 11/29/2011

<u> </u>	EXPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	o personal respiratory protecti	ve equipment normally r	equired.
Eye/Face Protection		afety glasses with side-shields		1
Hand protection	: P	rotective gloves		
Skin and body protection	: L	ong sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations		landle in accordance with good Vash hands before breaks and a		afety practice
Engineering measures		leat only in areas with appropri ppropriate exhaust ventilation a		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Silica, amorphous	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
Titanium dioxide	10 mg/m3 15 mg/m3	Time Weighted Average (TWA): PEL:	Total dust.	
Titanium dioxide		(TWA):	Total dust. as Ti	OSHA Z1
Titanium dioxide	15 mg/m3	(TWA): PEL: Time Weighted Average		ACGIH OSHA Z1 MX OEL MX OEL
Titanium dioxide	15 mg/m3 10 mg/m3 20 mg/m3	(TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit	as Ti as Ti	OSHA Z1 MX OEL
Titanium dioxide	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : Solic	(TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	as Ti as Ti PERTIES ration rate : Not	OSHA Z1 MX OEL MX OEL applicable
Form Appearance	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : Solic : pelle	(TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO Evapor ts Specifi	as Ti as Ti PERTIES ration rate : Not c Gravity : Not	OSHA Z1 MX OEL MX OEL applicable determined
Form Appearance Color	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : Solic : pelle : WHI	(TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO I Evapor ts Specifi TE Bulk d	as Ti as Ti PERTIES ration rate : Not c Gravity : Not ensity : Not	OSHA Z1 MX OEL MX OEL applicable determined established
Form Appearance Color Odour	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : Solic : pelle : WHI : Very	(TWA):         PEL:         Time Weighted Average (TWA):         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRO         I       Evapor         ts       Specifi         TE       Bulk d         faint       Vapour	as Ti as Ti PERTIES ration rate : Not c Gravity : Not ensity : Not r pressure : Not	OSHA Z1 MX OEL MX OEL applicable determined established applicable
Form Appearance Color	15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : Solic : pelle : WHI : Very : Not of	(TWA):         PEL:         Time Weighted Average (TWA):         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRO         I       Evapor         ts       Specifi         TE       Bulk d         faint       Vapour	as Ti as Ti PERTIES ration rate : Not c Gravity : Not ensity : Not r pressure : Not r density : Not	OSHA Z1 MX OEL MX OEL applicable determined established

# MATERIAL SAFETY DATA SHEET **PG 101502.00 IY APET**

Version Number 1.0 Revision Date 06/22/2007

Page 4 of 7 Print Date 11/29/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
7631-86-9	Silica, amorphous	Oral LD50Oral LD50	15,000 mg/kg22,500 mg/kg	mouserat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

### **12. ECOLOGICAL INFORMATION**

PolyOne.

# MATERIAL SAFETY DATA SHEET **PG 101502.00 IY APET**

Version Number 1.0 Revision Date 06/22/2007 Page 5 of 7 Print Date 11/29/2011

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materi has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSC Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition	: Not applicable

# MATERIAL SAFETY DATA SHEET **PG 101502.00 IY APET**

Version Number 1.0 Revision Date 06/22/2007

Page 6 of 7 Print Date 11/29/2011

65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Zinc iron oxide	12063-19-3	0.10 - 1.00	231

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
7631-86-9	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Not determined
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Listed
Philippines PICCS	: Not determined

:

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The

PolyOne.

# MATERIAL SAFETY DATA SHEET **PG 101502.00 IY APET**

Version Number 1.0 Revision Date 06/22/2007 Page 7 of 7 Print Date 11/29/2011

information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.