PolvOne

MATERIAL SAFETY DATA SHEET #297 BLUE PEARL

Version Number 1.0 Revision Date 06/29/2007

Page 1 of 8 Print Date 11/29/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	#297 BLUE PEARL
Product code	:	CC10101744
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
8-Oxa-3,5-dithia-4-stannatetradecanoic acid, 10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl	57583-35-4	1 - 5
ester		
Glyceryl monostearate	31566-31-1	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Dioctyltin bis(2-ethylhexylmercaptoacetate)	15571-58-1	1 - 5
Mica	12001-26-2	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion Eyes	May be harmful if swallowed.Particulates, like other inert materials can be mechanically irritating.

PolyOne.

MATERIAL SAFETY DATA SHEET **#297 BLUE PEARL**

Version Number 1.0 Revision Date 06/29/2007 Page 2 of 8 Print Date 11/29/2011

Skin	: Experience shows no unusual dermatitis hazard from routine handling	
Chronic exposure	: Refer to Section 11 for Toxicological Information.	
Medical Conditions Aggravated by Exposure:	: None known.	
	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.	
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.	
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.	
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. 	
	6. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.	



Page 3 of 8

Print Date 11/29/2011

MATERIAL SAFETY DATA SHEET #297 BLUE PEARL

Version Number 1.0 Revision Date 06/29/2007	Page 3 of Print Date 11/29/20
	plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling :	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage :	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXPOSU	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection :	No personal respiratory protective equipment normally required.

Eye/Face Protection : Safety glasses with side-shields Hand protection Protective gloves : Skin and body protection : Long sleeved clothing Additional Protective : Safety shoes Measures General Hygiene : Handle in accordance with good industrial hygiene and safety practice. Considerations Wash hands before breaks and at the end of workday. : Heat only in areas with appropriate exhaust ventilation. Provide Engineering measures appropriate exhaust ventilation at machinery.

Exposure limit(s)

PolyOne

MATERIAL SAFETY DATA SHEET #297 BLUE PEARL

Version Number 1.0 Revision Date 06/29/2007 Page 4 of 8 Print Date 11/29/2011

Components	Value	Exposure time	Exposure type	List:
8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl ester	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	ACGIH
	0.2 mg/m3	Short Term Exposure Limit (STEL):	as Sn	ACGIH
	0.1 mg/m3	PEL:	as Sn	OSHA Z1
	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	MX OEL
	0.2 mg/m3	Short Term Exposure Limit (STEL):	as Sn	MX OEL
Glyceryl monostearate	10 mg/m3	Time Weighted Average (TWA):		ACGIH
Mica	3 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	3 mg/m3	Time Weighted Average (TWA):		MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL
Dioctyltin bis(2-ethylhexylmerca ptoacetate)	0.1 mg/m3	PEL:	as Sn	OSHA Z1
• /	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	ACGIH
	0.2 mg/m3	Short Term Exposure Limit (STEL):	as Sn	ACGIH

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range Boiling Point: Water solubility
- Solid
 pellets
 BLUE
 Very faint
 Not determined
 Not applicable
 Insoluble
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicableNot determinedNot establishedNot applicableNot applicable
- : Not applicable

10. STABILITY AND REACTIVITY

Stability

: Stable.

Hazardous Polymerization

: Will not occur.

4/8

PolyOne.

MATERIAL SAFETY DATA SHEET #297 BLUE PEARL

Version Number 1.0 Revision Date 06/29/2007	Page 5 of 8 Print Date 11/29/2011
Conditions to avoid :	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials :	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition : products	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
57583-35-4	8-Oxa-3,5-dithia-4-stannat etradecanoic acid, 10-ethyl-4,4-dimethyl-7-o xo-, 2-ethylhexyl ester	Irritant	Eyes, Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
15571-58-1	Dioctyltin bis(2-ethylhexylmercaptoa cetate)	Systemic effects	Respiratory system, central nervous system (CNS).
12001-26-2	Mica	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
15571-58-1	Dioctyltin bis(2-ethylhexylmercaptoa cetate)	Oral LD50	2,100 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

PolyOne.

MATERIAL SAFETY DATA SHEET #297 BLUE PEARL

Version Number 1.0 Revision Date 06/29/2007 Page 6 of 8 Print Date 11/29/2011

CAS-No.		mical Name	OSHA	IARC	NTP
13463-67-7	Titanium d	ioxide	no	2B	no
IARC Carcinogen Cla 1 - The component is a 2A - The component is 2B - The component is NTP Carcinogen Class 1 - The component is b 2 - The component is b	carcinogenic s probably ca s possibly car sifications: known to be a	rcinogenic to huma cinogenic to human a human carcinoger	ns. 1.		
	12	2. ECOLOGICAL	INFORMATION		
Persistence and degrad	lability :	Not readily biode	gradable.		
Environmental Toxici	ty :	Chemicals are not readily available as they are bound within the polymer matrix.			
Bioaccumulation Pote	ntial :	: Chemicals are not readily available as they are bound within the polymer matrix.			
Additional advice	:	: No data available			
	1	3. DISPOSAL CO	NSIDERATIONS		
Product	:	possible recycling generator of wast classification, tra	pplastic plastics the p g is preferred to disp e material has the re nsportation and disp l, state/provincial an	oosal or incinerations esponsibility for prosal in accordance	on. The oper waste with
Contaminated packaging		has the responsib	erred when possible. ility for proper wast coordance with appli ons.	e classification, tra	ansportation
	1	4. TRANSPORT	INFORMATION		
U.S. DOT Classification	on .	Not regulated for	transportation		
	· ·	-	-		
ICAO/IATA (air)		Refer to specific regulation.			
IMO / IMDG (maritim	ne) :	Refer to specific	regulation.		
	1/	DECILIATODA	INFORMATION		

PolyOne.

MATERIAL SAFETY DATA SHEET **#297 BLUE PEARL**

Version Number 1.0 Revision Date 06/29/2007	Page 7 of 8 Print Date <i>11/29/2011</i>
OSHA Status :	Classified as hazardous based on components.
TSCA Status :	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous Sub	stances (40 CFR 302)
Not applicable	
California Proposition : 65	Not applicable
SARA Title III Section 302 Extreme	ely Hazardous Substance
Unless specific chemicals are identi	fied under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 Toxic C	Chemicals:
Unless specific chemicals are identi	fied under this section, this product is Not Applicable under this regulation
Canadian Regulations:	
National Pollutant Release In	nventory (NPRI)
Not applicable	
WHMIS Classification :	D2A
WHMIS Ingredient Disclosu	re List
CAS-No.	
57583-35-4 12001-26-2	
15571-58-1	
DSL :	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS :	Not determined
China IECS :	Not determined
Europe EINECS :	Not determined

PolyOne.

MATERIAL SAFETY DATA SHEET #297 BLUE PEARL

Version Number 1.0 Revision Date 06/29/2007 Page 8 of 8 Print Date 11/29/2011

Japan ENCS

: Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.