MATERIAL SAFETY DATA SHEET ORANGE

Version Number 1.0 Revision Date 07/19/2007 Page 1 of 7 Print Date 11/30/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	ORANGE
Product code	:	CC10102471
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5
Rutile, antimony chromium buff	68186-90-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET **ORANGE**

Version Number 1.0 Revision Date 07/19/2007 Page 2 of 7 Print Date 11/30/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit		Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	:	Not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage		Keep containers dry and tightly closed to avoid moisture absorption

2/7



MATERIAL SAFETY DATA SHEET **ORANGE**

Version Number 1.0 Revision Date 07/19/2007

_

Page 3 of 7 Print Date 11/30/2011

8.1	EXPOSURE	CONTROLS / PERSONAL P	ROTECTION			
Respiratory protection	: N	lo personal respiratory protective	e equipment normally	required.		
Eye/Face Protection	n : Safety glasses with side-shields					
Hand protection	: P	rotective gloves				
Skin and body protection	: L	ong sleeved clothing				
Additional Protective Measures	: S	afety shoes				
General Hygiene Considerations		landle in accordance with good in Vash hands before breaks and at		safety practice		
Engineering measures		leat only in areas with appropria ppropriate exhaust ventilation at		. Provide		
Exposure limit(s)			machinery.			
				List:		
Components Rutile, antimony	Value 0.5 mg/m3	Exposure time Time Weighted Average	Exposure type as Cr	List: ACGIH		
Components Rutile, antimony	Value 0.5 mg/m3	Exposure time	Exposure type			
Components	Value	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average	Exposure type as Cr	ACGIH		
Components Rutile, antimony	Value 0.5 mg/m3 0.5 mg/m3	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average	Exposure type as Cr	ACGIH OSHA Z1		
Components Rutile, antimony	Value 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA):	Exposure type as Cr as Cr	ACGIH OSHA Z1 MX OEL		
Components Rutile, antimony	Value 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average	Exposure type as Cr as Cr as Sb	ACGIH OSHA Z1 MX OEL ACGIH		
Components Rutile, antimony	Value 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL:	Exposure type as Cr as Cr as Sb as Sb	ACGIH OSHA Z1 MX OEL ACGIH OSHA Z1		
Components Rutile, antimony chromium buff	Value 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average	Exposure type as Cr as Cr as Sb as Sb	ACGIH OSHA Z1 MX OEL ACGIH OSHA Z1 MX OEL		
Rutile, antimony chromium buff	Value 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 10 mg/m3	Exposure time Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA):	Exposure type as Cr as Cr as Sb as Sb as Sb as Sb	ACGIH OSHA Z1 MX OEL ACGIH OSHA Z1 MX OEL ACGIH		

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range
- Solid
 pellets
 ORANGE
 Very faint
 Not determined
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density
- Not applicableNot determinedNot establishedNot applicableNot applicable





MATERIAL SAFETY DATA SHEET ORANGE

Version Number 1.0 Revision Date 07/19/2007

Page 4 of 7 Print Date 11/30/2011

Boiling Point: Water solubility	Not applicable Insoluble	рН	: Not applicable
	10. STABILITY AND	REACTIVITY	l
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from oxic decomposition, do no	00	nd open flame. To avoid thermal
Incompatible Materials	: Incompatible with str	ong acids and	oxidizing agents.
Hazardous decomposition products			oxide (CO), oxides of nitrogen nd smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
68186-90-3	Rutile, antimony chromium buff	Irritant	Eyes, Skin, Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET **ORANGE**

Version Number 1.0 Revision Date 07/19/2007 Page 5 of 7 Print Date 11/30/2011

Persistence and degradability	: Not readily biodegradable.
reisistence and degradability	. Not readily blodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	

PolyOne.

MATERIAL SAFETY DATA SHEET **ORANGE**

Version Number 1.0 Revision Date 07/19/2007 Page 6 of 7 Print Date 11/30/2011

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight %
CHROMIUM III COMPOUNDSANTIMONY	68186-90-3	5.00 - 10.00
COMPOUNDS		

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Rutile, antimony chromium buff	68186-90-3	5.00 - 10.00	69
		5.00 - 10.00	17

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
68186-90-3	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

:

PolyOne

MATERIAL SAFETY DATA SHEET **ORANGE**

Version Number 1.0 Revision Date 07/19/2007 Page 7 of 7 Print Date 11/30/2011

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.