MATERIAL SAFETY DATA SHEET WM SIGN GREEN

Version Number 1.0 Revision Date 07/24/2007 Page 1 of 8 Print Date 11/30/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:		ewardship (770) 271-5902 EC 1-800-424-9300 (24hrs for spill, leak, fire, exposure t).
Product name	WM SIGN	GREEN
Product code	CC101026	55
Chemical Name	Mixture	
CAS-No.	Mixture	
Product Use	Industrial A	Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
1,6-Hexanediamine,	70624-18-9	1 - 5
N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-,		
polymer with 2,4,6-trichloro-1,3,5-triazine,		
reaction products		
Calcium carbonate	1317-65-3	1 - 5
Calcium stearate	1592-23-0	1 - 5
Dioctyltin bis(2-ethylhexylmercaptoacetate)	15571-58-1	1 - 5
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.



MATERIAL SAFETY DATA SHEET WM SIGN GREEN

ion Number 1.0 sion Date 07/24/2007	Page 2 Print Date 11/30/2
Eyes Skin	 Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature	 Not applicable Not applicable Not applicable
Suitable extinguishing media Special Fire Fighting	 Carbon dioxide blanket, Water spray, Dry powder, Foam. Evillace calf contained breathing appendix (SCBA) used in positive
Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.



MATERIAL SAFETY DATA SHEET WM SIGN GREEN

ersion Number 1.0 evision Date 07/24/2007	Page 3 of 8 Print Date 11/30/2013
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSURE CONTROLS / PERSONAL PROTECTION
Respiratory protection	: No personal respiratory protective equipment normally required.
Eye/Face Protection	: Safety glasses with side-shields
Hand protection	: Protective gloves
Skin and body protection	: Long sleeved clothing
Additional Protective Measures	: Safety shoes
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)	

PolvOne.

MATERIAL SAFETY DATA SHEET WM SIGN GREEN

Version Number 1.0 Revision Date 07/24/2007

Page 4 of 8 Print Date 11/30/2011

Components	Value	Exposure tin	ne	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:		Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:		Total dust.	OSHA Z1
	10 mg/m3	Time Weighted A (TWA):	verage		MX OEL
	20 mg/m3	Short Term Exposu (STEL):	ire Limit		MX OEL
Calcium stearate	10 mg/m3	Time Weighted A (TWA):	verage		ACGIH
Titanium dioxide	10 mg/m3	Time Weighted A (TWA):	verage		ACGIH
	15 mg/m3	PEL:		Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		as Ti	MX OEL
Dioctyltin bis(2-ethylhexylmerca ptoacetate)	0.1 mg/m3	PEL:		as Sn	OSHA Z1
	0.1 mg/m3	Time Weighted A (TWA):	verage	as Sn	ACGIH
	0.2 mg/m3	Short Term Exposure Limit (STEL):		as Sn	ACGIH
	9. PHYSIC	CAL AND CHEMIC	CAL PRO	PERTIES	
Form	: Solic	1	Evapor	ration rate : Not	applicable
Appearance	: pellets Speci			5	determined
Color	: GRE	: GREEN Bulk de			established
Odour	: Very	faint			applicable
Melting point/range					applicable
Boiling Point:	: Not a	: Not applicable pH		: Not	applicable
** * * * ***					

10. STABILITY AND REACTIVITY

Stability

Water solubility

Hazardous Polymerization

Conditions to avoid

: Stable.

: Insoluble

: Will not occur.

: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.

Incompatible Materials : Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other.

MATERIAL SAFETY DATA SHEET WM SIGN GREEN

Version Number 1.0 Revision Date 07/24/2007 Page 5 of 8 Print Date 11/30/2011

Prevent cross contamination of feedstocks.

Hazardous decomposition
products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
(NOx), hydrogen chloride (HCl), other hazardous materials, and
smoke are all possible. Prolonged heating (approximately 30 minutes
or more) above 392 °F (200 °C) or short term heating at 482 °F (250
°C) may result in product decomposition and evolution of carbon
monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth	Irritant	Eyes, Skin, Respiratory system.
	yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products		
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
15571-58-1	Dioctyltin bis(2-ethylhexylmercaptoa cetate)	Systemic effects	Respiratory system, central nervous system (CNS).
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine,	Oral LD50	> 2,000 mg/kg	rat
	N,N'-bis(2,2,6,6-tetrameth	Dermal LD50	> 3,000 mg/kg	rat
	yl-4-piperidinyl)-,polymer			
	with			
	2,4,6-trichloro-1,3,5-triazi			
	ne, reaction products			
1592-23-0	Calcium stearate	Oral LD50	>10 gm/kg	rat
15571-58-1	Dioctyltin	Oral LD50	2,100 mg/kg	rat
	bis(2-ethylhexylmercaptoa			
	cetate)			

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

PolyOne.

MATERIAL SAFETY DATA SHEET WM SIGN GREEN

Version Number 1.0 Revision Date 07/24/2007

_

_

Page 6 of 8 Print Date 11/30/2011

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Fitanium dioxide	no	2B	no
2B - The component is po NTP Carcinogen Classifi 1 - The component is know	cinogenic to humans. robably carcinogenic to h ossibly carcinogenic to hu	imans. ogen.		
	12. ECOLOGIO	CAL INFORMATION		
Persistence and degradab	ility : Not readily bi	iodegradable.		
Environmental Toxicity	: Chemicals are polymer matr	e not readily available a ix.	s they are bound v	vithin the
Bioaccumulation Potentia	al : Chemicals are polymer matr	e not readily available a ix.	s they are bound v	vithin the
Additional advice	: No data avail	able		
	13. DISPOSAL	CONSIDERATIONS		
Product	possible recyc generator of v classification,	ermoplastic plastics the p cling is preferred to disp waste material has the re , transportation and disp deral, state/provincial an	oosal or incinerations of the second se	on. The oper waste with
Contaminated packaging	has the respon and disposal i	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
	14. TRANSPO	RT INFORMATION		
U.S. DOT Classification	: Not regulated	for transportation.		
ICAO/IATA (air)	: Refer to speci	ific regulation.		
IMO / IMDG (maritime)	: Refer to speci	ific regulation.		
	15. REGULATO	DRY INFORMATION		

PolyOne.

MATERIAL SAFETY DATA SHEET WM SIGN GREEN

ersion Number 1.0 evision Date 07/24/2007			Pri	Page 7 of 8 int Date 11/30/2011
OSHA Status	: Classified as ha	azardous based on	components.	
TSCA Status	: All component Inventory.	ts of this product a	re listed on or exen	npt from the TSCA
US. EPA CERCLA Hazardous		302)		
		,		
Not applicable				
California Proposition 65	: Not applicable			
SARA Title III Section 302 Ex	stremely Hazardous S	ubstance		
Unless specific chemicals are i	identified under this se	ection, this produc	ct is Not Applicable	e under this regulation
Unless specific chemicals are i Canadian Regulations: National Pollutant Rele				
Chemical Name		CAS-No.	Weight %	NPRI ID#
Phthalocyanine blue		147-14-8	0.10 - 1.00	71
Phthalocyanine green		1328-53-6	1.00 - 5.00	71
WHMIS Classification WHMIS Ingredient Dis CAS-No. 1328-53-6 15571-58-1				
DSL		ts of this product a t (DSL) or are exe	are on the Canadiar empt.	n Domestic
National Inventories:				
Australia AICS	: Not determined	1		
China IECS	: Not determined	1		

PolyOne

MATERIAL SAFETY DATA SHEET WM SIGN GREEN

Version Number 1.0 Revision Date 07/24/2007 Page 8 of 8 Print Date 11/30/2011

Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.