MATERIAL SAFETY DATA SHEET

Super Stay Silver 2

Version Number 1.0 Revision Date 08/09/2007 Page 1 of 6 Print Date 11/30/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	Super Stay Silver 2
Product code	:	CC10103116
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Mica	12001-26-2	5 - 10
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET Super Stay Silver 2

Version Number 1.0 Revision Date 08/09/2007 Page 2 of 6 Print Date 11/30/2011

Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
F1		
Flammable Limits		Not applicable
Upper explosion limit	:	Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	:	Not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting	:	Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures		pressure mode should be worn to prevent inhalation of airborne
		contaminants.
Unusual Fire/Explosion	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards		(NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

2/6

PolyOne.

MATERIAL SAFETY DATA SHEET Super Stay Silver 2

Version Number 1.0 Revision Date 08/09/2007

_

Page 3 of 6 Print Date 11/30/2011

Form: SolidEvaporAppearance: pelletsSpecificColor: GREYBulk deOdour: Very faintVapour						
Hand protection : Protective gloves Skin and body protection : Long sleeved clothing Additional Protective : Safety shoes Measures : Safety shoes General Hygiene : Handle in accordance with good Considerations : Wash hands before breaks and a Engineering measures : Heat only in areas with appropriation appropriate exhaust ventilation a Exposure limit(s) : Heat only in areas with appropriation a Mica 3 mg/m3 Time Weighted Average (TWA): Itanium dioxide 10 mg/m3 Time Weighted Average (TWA): Ising/m3 PEL: 10 mg/m3 Itanium dioxide 10 mg/m3 Time Weighted Average (TWA): Ising/m3 PEL: 10 mg/m3 Titanium dioxide 10 mg/m3 Short Term Exposure Limit (STEL): Very maint 20 mg/m3 Short Term Exposure Limit (STEL):	tive equipment normally r	equired.				
Skin and body protection : Long sleeved clothing Additional Protective : Safety shoes Measures : Handle in accordance with good General Hygiene : Handle in accordance with good Considerations : Heat only in areas with appropriate exhaust ventilation a Engineering measures : Heat only in areas with appropriate exhaust ventilation a Exposure limit(s) : Image: Safety shoes Mica 3 mg/m3 Time Weighted Average (TWA): Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): 15 mg/m3 PEL: 10 mg/m3 10 mg/m3 Time Weighted Average (TWA): 120 mg/m3 20 mg/m3 Short Term Exposure Limit (STEL): . PHYSICAL AND CHEMICAL PRO Form : Solid Evapor Appearance : pellets Specific Color : : : Solid Evapor Appearance : : Solid Evapor Appearance : : Solid Evapor Appearance : : Solid <	S					
Additional Protective Measures : Safety shoes General Hygiene Considerations : Handle in accordance with good Wash hands before breaks and at Engineering measures Engineering measures : Heat only in areas with appropriate exhaust ventilation at Exposure limit(s) Image: Components of the system of th						
Measures General Hygiene : Handle in accordance with good Considerations Wash hands before breaks and a Engineering measures : Heat only in areas with appropria appropriate exhaust ventilation a Exposure limit(s) : Heat only in areas with appropria appropriate exhaust ventilation a Exposure limit(s) : : Mica 3 mg/m3 Time Weighted Average (TWA): 3 mg/m3 Time Weighted Average (TWA): Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): 15 mg/m3 PEL: 10 mg/m3 Time Weighted Average (TWA): 20 mg/m3 Short Term Exposure Limit (STEL): PHYSICAL AND CHEMICAL PRO Form : Solid Evapor Appearance : pellets Specific Color Color : GREY Bulk de Odour Very faint Vapour						
Considerations Wash hands before breaks and a Engineering measures : Heat only in areas with appropriate exhaust ventilation a Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation a Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation a Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation a Exposure limit(s) : Exposure time Mica 3 mg/m3 Time Weighted Average (TWA): 3 mg/m3 Time Weighted Average (TWA): Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): 15 mg/m3 PEL: 10 mg/m3 Time Weighted Average (TWA): 20 mg/m3 Short Term Exposure Limit (STEL): PHYSICAL AND CHEMICAL PRO Form : Solid Evapor Appearance : pellets Specific Color : GREY Bulk de Odour : Very faint Vapour						
appropriate exhaust ventilation a Exposure limit(s) Components Value Exposure time Mica 3 mg/m3 Time Weighted Average (TWA): 3 mg/m3 Time Weighted Average (TWA): Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): 15 mg/m3 PEL: 10 mg/m3 Time Weighted Average (TWA): 20 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PRO Form : Solid Evapor : pellets Specific Specific Color : GREY Bulk de Odour :		afety practice.				
Components Value Exposure time Mica 3 mg/m3 Time Weighted Average (TWA): 3 mg/m3 Time Weighted Average (TWA): Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): 15 mg/m3 PEL: 10 mg/m3 Time Weighted Average (TWA): 20 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PRO Form : Solid Appearance : pellets Specific Odour Very faint Vapour		Provide				
Mica 3 mg/m3 Time Weighted Average (TWA): 3 mg/m3 Time Weighted Average (TWA): Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): 15 mg/m3 PEL: 10 mg/m3 Time Weighted Average (TWA): 12 mg/m3 PEL: 10 mg/m3 Time Weighted Average (TWA): 20 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PRO Form : Solid Evapor Appearance Appearance : pellets Specific Color Odour : Very faint Vapour						
Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Constraint of the second system Image: Consecond system<	Exposure type	List:				
3 mg/m3 Time Weighted Average (TWA): Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): 15 mg/m3 PEL: 10 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Time Weighted Average (TWA): 20 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PRO Form : Solid Evapor Appearance : pellets Color : GREY Bulk de Odour : Very faint Vapour	Respirable fraction.	ACGIH				
Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): 15 mg/m3 PEL: 10 mg/m3 Time Weighted Average (TWA): 20 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PRO Form : Solid Appearance : pellets Color : GREY Bulk de Odour : Very faint		MX OEL				
15 mg/m3 PEL: 10 mg/m3 Time Weighted Average (TWA): 20 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PRO Form : Solid Appearance : pellets Color : GREY Bulk de Odour : Very faint		ACGIH				
10 mg/m3 Time Weighted Average (TWA): 20 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PRO Form : Solid Evapor Appearance : pellets Specific Color : GREY Bulk de Odour : Very faint Vapour	Total dust.	OSHA Z1				
20 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PRO Form : Solid Evapor Appearance : pellets Specific Color : GREY Bulk de Odour : Very faint Vapour	as Ti	MX OEL				
Form: SolidEvaporAppearance: pelletsSpecificColor: GREYBulk deOdour: Very faintVapour	as Ti	MX OEL				
Appearance: pelletsSpecificColor: GREYBulk deOdour: Very faintVapour	9. PHYSICAL AND CHEMICAL PROPERTIES					
Boiling Point:: Not applicablepHWater solubility: Insoluble	fic Gravity: Notdensity: Notur pressure: Notur density: Not	applicable determined established applicable applicable applicable				
10. STABILITY AND REACTIV	VITY					
Stability : Stable.						

PolvUne

MATERIAL SAFETY DATA SHEET Super Stay Silver 2

Version Number 1.0 Revision Date 08/09/2007

Page 4 of 6 Print Date 11/30/2011

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
12001-26-2	Mica	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	:	No data available

PolyOne.

MATERIAL SAFETY DATA SHEET

Super Stay Silver 2

Version Number 1.0 Revision Date 08/09/2007 Page 5 of 6 Print Date 11/30/2011

	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	us Substances (40 CFR 302)
Not applicable	
California Propositior 65	: Not applicable
SARA Title III Section 302 E	Extremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulat
SARA Title III Section 313 T	oxic Chemicals:

PolyOne.

MATERIAL SAFETY DATA SHEET Super Stay Silver 2

Version Number 1.0 Revision Date 08/09/2007 Page 6 of 6 Print Date 11/30/2011

Unless specific chemicals are identifi	ed under this section, this product is Not Applicable under this regulation			
Canadian Regulations:				
National Pollutant Release Inv	ventory (NPRI)			
Not applicable				
WHMIS Classification :	D2A			
WHMIS Ingredient Disclosure	e List			
CAS-No. 12001-26-2				
DSL :	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.			
National Inventories:				
Australia AICS :	Listed			
China IECS :	Listed			
Europe EINECS :	Listed			
Japan ENCS : 1	Not determined			
Korea KECI :	Listed			
Philippines PICCS :	Listed			
	16. OTHER INFORMATION			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.